

# HVAC LINE SET TAPE

**SPECIALTY TAPE**



**Backing:** Polypropylene Film  
**Adhesive:** Acrylic  
**Liner:** N/A  
**Specifications:** N/A  
**Colors:** Black (Printed)  
**Available Size:** 1.89 in x 35 yd (48 mm x 32 m)

## Applications

- Secure and protect indoor and outdoor HVAC line sets and other HVAC components
- Designed specifically to bond to foam line set insulation materials without lifting or flagging

## Features

## Benefits

Acrylic Adhesive

- Aggressive, durable bond - won't flag or lift
- Solvent-Free, low odor
- Mold and moisture resistant
- UV Resistant for outdoor durability
- Tough and durable
- Hand tearable for easy installation

Polypropylene Film Backing

## Typical Test Values

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	3.0 mils	76 µm	ASTM D-1000
<b>Adhesion to Steel</b>	45 oz/in	4.92 N/cm	PSTC-101
<b>Tensile Strength</b>	32 lb/in	56.04 N/cm	ASTM D-1000
<b>Installation Temperature</b>	-10 to 180 °F	-17 to 82 °C	
<b>Operating Temperature</b>	-40 to 212 °F	-40 to 100 °C	
<b>VOC Content</b>	< 1 g/L		
Recommended Storage Conditions: 60 - 80 °F at 40-60% RH Standard Shelf Life (at 25 °C): 36 months from date of manufacture			

The information presented herein was prepared at BERRY GLOBAL, INC. (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To BERRY's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY assumes any legal responsibility.