

TurboShearFC



Work. Perform. Outlast.
Limited Lifetime Warranty



Attach to any drill for fast straight cuts, angles, precise trim cuts, and mild arcs in Fiber Cement Backer Board and Siding Plank. Turn Backer Board or Siding Plank finish-side-down to make clean cuts with minimal dust. Make fast, straight cuts and quick corners in 1/2 in. (13 mm) fiber cement backerboard, all with an easy one-hand operation. Designed to replace messy, imprecise, scoring and snapping methods of trimming backer board. A wide skid-plate on the head design stabilizes cutting action for extra smooth results. This versatile shear navigates curved-pattern cuts for window and door arches and will also cut 5/16 in. (8 mm) fiber cement siding plank. You can even rotate the tool's skid plate to maximize acceptable cutting life.



TSF2
Pat. No. 9,649,702



The 360-degree rotating head allows users to position and lock the drill so it doesn't interfere with material for quick, hassle-free cuts every time!




Drill Requirements:

1/4 in. (6.35 mm) Chuck,
Min. 14.4V - DC, Max 7A-AC

Capacities: Fiber Cement Backer Board - 1/2 in. (13 mm)

Catalog Number	Description	Net Wt. oz. (g)	Net Wt. lbs. (kg)
TSF2	TurboShear, Fiber Cement Backer Board	—	2.5 (1.13)
Replacement Parts			
TSDC	TurboShear Drill Clamp	8 (227)	—
TSCG	TurboShear Chuck Guard	.96 (27)	—
TSF2RBN	TurboShear Replacement Blades for TSF2 (shown)	8.8 (249)	—
TSF2RB	TurboShear Replacement Blades for original TSF2	8.8 (249)	—



WARNING:
Fiber cement contains crystalline silica.
Respirable silica contained in cutting dust is known to cause cancer.