



O-RING  
OPTIONAL  
ADD: R

2.32 APPROX.

0.39

10.5 APPROX.

LOCK NUT  
OPTIONAL  
ADD: L

PG 29 THREAD

DOUBLE WEAVE

SINGLE WEAVE

ITEM NO.	PART NUMBER	DESCRIPTION	MATERIAL	QTY.
1	RPG-29350-B	BODY	ALUMINUM	1
2	SRB-516	BUSHING	NEOPRENE	1
3	SOR-3	O-RING	BUNA-N	1
4	RSR-500-ND	NUT	ALUMINUM	1
5	RLP29-BR	LOCK NUT	BRASS, NICKLE PLATED	1
6	R-516-D	MESH	STAINLESS WIRE	1



CATALOG NUMBER	SEALING RANGE	BODY BORE
RPG-29516-E	.875 - 1.000	1.220

REV.	DATE	CHANGE	UNLESS OTHERWISE SPECIFIED:	NAME	DATE	<b>REMKE</b> <b>REMKE INDUSTRIES</b> 310 CHADDICK DR, WHEELING, IL. 60090	
A	8/6/13	DRAWING RELEASED	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1° BEND ± 1° ONE PLACE DECIMAL ± .015 TWO PLACE DECIMAL ± .010 THREE PLACE DECIMAL ± .005 INTERPRET GEOMETRIC TOLERANCING PER: MATERIAL <b>ALUMINUM</b> FINISH	DRAWN JCN CHECKED ENG APPR. MFG APPR. Q.A.	8/13	TITLE: <b>RPG-29516-E SERIES</b>	
			DO NOT SCALE DRAWING	<b>PROPRIETARY AND CONFIDENTIAL</b> THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF REMKE INDUSTRIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF REMKE INDUSTRIES IS PROHIBITED.		SIZE <b>A</b> DWG. NO. <b>RPG-29516-E ASSEMBLY</b>	SCALE: 1:1.6 SHEET 1 OF 1

5

↑

4

3

2

1