

O-RING  
OPTIONAL  
ADD: R

2.32 APPROX.

0.39

LOCK NUT  
OPTIONAL  
ADD: L

PG 29 THREAD

10.5 APPROX.


DOUBLE WEAVE

SINGLE WEAVE

ITEM NO.	PART NUMBER	DESCRIPTION	MATERIAL	QTY.
1	RPG-29350-B	BODY	ALUMINUM	1
2	SRB-516	BUSHING	NEOPRENE	1
3	SOR-3	O-RING	BUNA-N	1
4	RSR-500-ND	NUT	ALUMINUM	1
5	RLP29-BR	LOCK NUT	BRASS, NICKLE PLATED	1
6	R-516-D	MESH	STAINLESS WIRE	1



CATALOG NUMBER	SEALING RANGE	BODY BORE
RPG-29516-E	.875 - 1.000	1.220

REV.	DATE	CHANGE	UNLESS OTHERWISE SPECIFIED:		NAME	DATE			
A	8/6/13	DRAWING RELEASED	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL ± 1/64 ANGULAR: MACH ± 1° BEND ± 1° ONE PLACE DECIMAL ±.015 TWO PLACE DECIMAL ±.010 THREE PLACE DECIMAL ±.005	DRAWN	JCN	8/13			
				CHECKED			TITLE:  RPG-29516-E SERIES		
				ENG APPR.					
				MFG APPR.					
			INTERPRET GEOMETRIC TOLERANCING PER:	Q.A.			SIZE  A  DWG. NO. RPG-29516-E ASSEMBLY		
			MATERIAL  ALUMINUM	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF REMKE INDUSTRIES. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF REMKE INDUSTRIES IS PROHIBITED.					
			FINISH						
			DO NOT SCALE DRAWING				SCALE:1:1.6		SHEET 1 OF 1