

# Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

## 1 Identification

**Trade name:** FORD MUST BLUE  
**Other means of identification**

**Product code:** EN00560000  
**Recommended use:** Paint and coatings application.  
**Uses advised against:** Any that differs from the recommended use.

## 2 Hazard(s) identification

### Classification of the substance or mixture

Aerosols 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.  
 Eye irritation 2A H319 Causes serious eye irritation.  
 Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.  
 Specific target organ toxicity (single exposure) 3 H336 May cause drowsiness or dizziness.  
 Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

### Additional information:

#### GHS Hazard pictograms



GHS02 GHS07 GHS08

#### Signal word

Danger

#### Hazard-determining components of labeling:

Acetone  
 titanium dioxide  
 methyl isobutyl ketone

#### Hazard statements

Extremely flammable aerosol. Pressurized container: may burst if heated.  
 Causes serious eye irritation.  
 Suspected of causing cancer. Route of exposure: Inhalation.  
 May cause drowsiness or dizziness.  
 May cause damage to organs through prolonged or repeated exposure.

#### Precautionary statements

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Do not spray on an open flame or other ignition source.  
 Do not pierce or burn, even after use.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Avoid breathing fume/mist/vapors/spray.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 IF exposed or concerned: Get medical advice/attention.  
 Call a poison center/doctor if you feel unwell.  
 Get medical advice/attention if you feel unwell.  
 If eye irritation persists: Get medical advice/attention.  
 Store in a well-ventilated place.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).  
 Dispose of contents/container in accordance with local/regional/national/international regulations.  
 May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

#### Effects of chronic overexposure:

#### Classification according to (d)(1)(ii) of § 1910.1200

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

#### Hazards not otherwise classified

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

## 3 Composition/information on ingredients

### Chemical characterization: Mixtures

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

#### Dangerous components:

67-64-1	Acetone	25-50%
74-98-6	propane	15-25%
106-97-8	n-butane	5-10%
110-19-0	Isobutyl Acetate	5-10%
108-10-1	methyl isobutyl ketone	1-5%
107-87-9	Methyl Propyl Ketone	1-5%

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

Trade name: FORD MUST BLUE

2807-30-9 Glycol Ether EP

(Contd. of page 1)

1-5%

## 4 First-aid measures

### Description of first aid measures

<b>After inhalation:</b> <b>After skin contact:</b> <b>After eye contact:</b> <b>After swallowing:</b> <b>Most important symptoms and effects:</b> <b>Indication of any immediate medical attention needed:</b>	<p>Supply fresh air; consult doctor in case of complaints.</p> <p>Remove contaminated clothing. Wash exposed area with soap and water.</p> <p>Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.</p> <p>Rinse mouth with water. Do not induce vomiting.</p> <p>Dizziness</p> <p>No further relevant information available.</p>
--	--

## 5 Fire-fighting measures

<b>Extinguishing media</b> <b>Extinguishing agents:</b> <b>Special hazards:</b> <b>Protective equipment for firefighters:</b> <b>Additional information</b>	<p>CO2, extinguishing powder or water spray. Fight larger fires with water spray.</p> <p>Can form explosive gas-air mixtures.</p> <p>A respiratory protective device may be necessary.</p> <p>Cool endangered receptacles with water spray.</p>
---	---

## 6 Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures:</b> <b>Environmental precautions:</b> <b>Methods and material for containment and cleaning up:</b>	<p>Use respiratory protective device against the effects of fumes/dust/aerosol.</p> <p>Do not allow product to reach sewage systems or ground water.</p> <p>Absorb liquid components with liquid-binding material.</p>
--	--

## 7 Handling and storage

<b>Precautions for safe handling</b> <b>Fire/explosion protection:</b>  <b>Conditions for safe storage:</b> <b>Storage requirements:</b>	<p>Use only in well ventilated areas.</p> <p>Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.</p> <p>Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.</p>
--	---

## 8 Exposure controls/personal protection

**Components with limit values that require monitoring at the workplace:** The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.  
At this time, the remaining constituent has no known exposure limits.

### 67-64-1 Acetone

PEL	Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 590 mg/m <sup>3</sup> , 250 ppm
TLV	Short-term value: 1187 mg/m <sup>3</sup> , 500 ppm
	Long-term value: 594 mg/m <sup>3</sup> , 250 ppm
	A4, BEI

### 74-98-6 propane

PEL	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
REL	Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm
TLV	see Appendix F Minimal oxygen content ( D, EX)

### 106-97-8 n-butane

REL	Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm
TLV	Short-term value: 2370 mg/m <sup>3</sup> , 1000 ppm
	(EX)

### 110-19-0 Isobutyl Acetate

PEL	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
REL	Long-term value: 700 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 712 mg/m <sup>3</sup> , 150 ppm
	Long-term value: 238 mg/m <sup>3</sup> , 50 ppm

### 108-10-1 methyl isobutyl ketone

PEL	Long-term value: 410 mg/m <sup>3</sup> , 100 ppm
-----	--

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

**Trade name: FORD MUST BLUE**

(Contd. of page 2)

REL	Short-term value: 300 mg/m <sup>3</sup> , 75 ppm Long-term value: 205 mg/m <sup>3</sup> , 50 ppm
TLV	Short-term value: 307 mg/m <sup>3</sup> , 75 ppm Long-term value: 82 mg/m <sup>3</sup> , 20 ppm BEI, A3

**107-87-9 Methyl Propyl Ketone**

PEL	Long-term value: 700 mg/m <sup>3</sup> , 200 ppm
REL	Long-term value: 530 mg/m <sup>3</sup> , 150 ppm
TLV	Short-term value: 529 mg/m <sup>3</sup> , 150 ppm

**Ingredients with biological limit values:****67-64-1 Acetone**

BEI	25 mg/L Medium: urine Time: end of shift Parameter: Acetone (nonspecific)
-----	--

**108-10-1 methyl isobutyl ketone**

BEI	1 mg/L Medium: urine Time: end of shift Parameter: MIBK
-----	--

**Exposure controls****Hygienic protection:**

Immediately remove all soiled and contaminated clothing.  
Wash hands after use.

**Breathing equipment:**

Do not eat or drink while working.

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:**

Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

**Eye protection:**

Tightly sealed goggles

**9 Physical and chemical properties****General Information:****Physical state**

Aerosol

**Odor:**

Aromatic

**Odor threshold:**

Not determined.

**Melting point/Melting range**

Undetermined.

**Boiling point:**

-44.5 °C (-48.1 °F)

**Flammability:**

Extremely flammable.

**Lower Explosion Limit:**

1.7 Vol %

**Upper Explosion Limit:**

10.9 Vol %

**Flash point:**

-19 °C (-2.2 °F)

**Decomposition temperature:**

Not determined.

**pH-value:**

Not determined.

**Viscosity:**

Not determined.

**Kinematic:**

Not determined.

**Dynamic:**

Not determined.

**Solubility:**

Not determined.

**Vapor pressure:**

40 PSI 2750 hPa

**Vapor Pressure:**

40 PSI, 2750 hPa

**Relative Density:**

Between 0.77 and 0.85 (Water equals 1.00)

**Vapor density**

Not determined.

**Particle characteristics**

Not applicable.

**Appearance:**

Aerosol.

**Ignition temperature:**

Product is not self-igniting.

**Danger of explosion:**

Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit.

In use, may form flammable/explosive vapour-air mixture.

**Water:**

0.0 %

**Evaporation rate**

Not applicable.

**Partition coefficient: n-octonal/water:** Not determined.

**10 Stability and reactivity****Conditions to avoid:**

Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.

**Possibility of hazardous reactions:**

No dangerous reactions known.

**Conditions to avoid**

No further relevant information available.

**Incompatible materials:**

No further relevant information available.

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

Trade name: FORD MUST BLUE

**Hazardous decomposition:** No dangerous decomposition products known.

(Contd. of page 3)

## 11 Toxicological information

LD/LC50 values that are relevant for classification:

### 110-19-0 Isobutyl Acetate

Oral	LD50	4,763 mg/kg (rabbit)
------	------	----------------------

### 108-10-1 methyl isobutyl ketone

Oral	LD50	2,100 mg/kg (rat)
Dermal	LD50	16,000 mg/kg (rab)
Inhalative	LC50/4 h	11 mg/l (ATE)
		8.3-16.6 mg/l (rat)

**Skin effects:** No irritant effect.  
**Eye effects:** Irritating effect.  
**Sensitization:** No sensitizing effects known.  
**Aspiration hazard**  
**Interactive effects** No interactive effects between components are known.

### IARC (International Agency for Research on Cancer)

108-10-1 methyl isobutyl ketone

2B

### NTP (National Toxicology Program)

None of the ingredients is listed.

### Alternative sources for toxicological information

No non-standard sources for toxicological information where used.

## 12 Ecological information

**Toxicity**  
**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Other information:** This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.

**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Results of PBT and vPvB assessment**  
**PBT:** Not applicable.  
**vPvB:** Not applicable.  
**Other adverse effects:** No further relevant information available.

## 13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

### Waste treatment methods

**Recommendation:** Completely empty cans should be recycled.  
**Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

UN-Number	UN1950
DOT	UN1950
UN proper shipping name:	
DOT	Aerosols, flammable
Transport hazard class(es):	
Class	2.1 Gases
DOT	
Packaging Group:	--
Special precautions for user:	Warning: Gases
EMS Number:	F-D,S-U

## 15 Regulatory information

Reglamentación y legislación en materia de seguridad, salud y medio ambiente específicas para la sustancia o la mezcla

### Toxic Substances Control Act

(TSCA): All ingredients are found on the inventory list of substances.

### Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

### Hazardous Air Pollutants

108-10-1	methyl isobutyl ketone
1330-20-7	xylene (mix)

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

**Trade name: FORD MUST BLUE**

(Contd. of page 4)

100-41-4	ethyl benzene
136-52-7	cobalt bis(2-ethylhexanoate)

**California Proposition 65 chemicals known to cause cancer:**

108-10-1	methyl isobutyl ketone
13463-67-7	titanium dioxide
100-41-4	ethyl benzene

**Prop 65 chemicals known to cause birth defects or reproductive harm:**

108-10-1	methyl isobutyl ketone
----------	------------------------

**CANADIAN ENVIRONMENTAL PROTECTION ACT:**

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

<b>EPA:</b>		
67-64-1	Acetone	I
110-19-0	Isobutyl Acetate	D
108-10-1	methyl isobutyl ketone	I

**GHS label elements****Precautionary statements**

The product is classified and labeled according to the Globally Harmonized System (GHS).  
 Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 Do not spray on an open flame or other ignition source.  
 Do not pierce or burn, even after use.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Avoid breathing fume/mist/vapors/spray.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If inhaled: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 IF exposed or concerned: Get medical advice/attention.  
 Call a poison center/doctor if you feel unwell.  
 Get medical advice/attention if you feel unwell.  
 If eye irritation persists: Get medical advice/attention.  
 Store in a well-ventilated place.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).  
 Dispose of contents/container in accordance with local/regional/national/international regulations.  
 A Chemical Safety Assessment has not been carried out.

**Chemical safety assessment:****16 Other information**

This product was manufactured in the U.S.A.  
 The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Contact:** Regulatory Affairs  
**Date of previous version:** 05/20/2025  
**Date of preparation:** 01/13/2026

**Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 VOC: Volatile Organic Compounds (USA, EU)  
 PNEC: Predicted No-Effect Concentration (REACH)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 EPA: Environmental Protection Agency  
 IARC: International Agency for the Research of Cancer  
 NIOSH: National Institute for Occupational Safety and Health  
 TSCA: Toxic Substances Control Act  
 CPSC: Consumer Product Safety Commission  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 BEI: Biological Exposure Limit  
 Aerosols 1: Aerosols – Category 1  
 Eye irritation 2A: Serious eye damage/eye irritation – Category 2A  
 Carcinogenicity 2: Carcinogenicity – Category 2  
 Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3  
 Specific target organ toxicity (repeated exposure) 2: Specific target organ toxicity (repeated exposure) – Category 2