

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
Product name : Log Jam
Product code : Not available

1.2. Recommended use and restrictions on use

Recommended use : Caulking

This SDS is designed for workplace employees, emergency personnel and for other situations where there is potential for large-scale or prolonged exposure, in accordance with the WHMIS GHS requirements.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label, SDS or both in accordance with applicable government regulations

1.3. Supplier

Supplier

Sashco Inc.
14802 Grant St.
Thornton, CO, 80023
USA
T 800-767-5656
info@sashco.com

Distributor

Add the name, address and tel. number of the Canadian manufacturer or importer who operates in Canada.

1.4. Emergency telephone number

Emergency number : 800-535-5053

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS CA)

Eye Irrit. 2	H319	Causes serious eye irritation.
STOT RE 2	H373	May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms (GHS-CA) :



Signal word (GHS CA) : Warning

Hazard statements (GHS-CA) : H319 - Causes serious eye irritation.
H373 - May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

Precautionary statements (GHS-CA) : P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read label before use.
P260 - Do not breathe fume, spray, vapours.
P264 - Wash hands, forearms and face thoroughly after handling.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.

Log Jam

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

P314 - Get medical advice/attention if you feel unwell.
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 - If eye irritation persists: Get medical advice/attention.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS CA)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%
Ethylene glycol	1,2-Dihydroxyethane / Ethane-1,2-diol / 1,2-Ethanediol / Ethanediol / GLYCOL / Glycol / Monoethylene glycol	CAS-No.: 107-21-1	1 – 5
Calcium oxide	Lime / Quicklime / CALCIUM OXIDE / Quicklime (CaO) / Calcium oxide (CaO) / Lime (calcium oxide)	CAS-No.: 1305-78-8	0.1 < 1
Sodium dodecylbenzenesulfonate	Dodecylbenzenesulphonic acid, sodium salt / Sodium laurylbenzenesulfonate / Sodium laurylbenzenesulphonate / sodium dodecylbenzenesulfonate / Sodium lauryl benzene sulphonate / SODIUM DODECYLBENZENESULFONATE / Benzenesulfonic acid, dodecyl-, sodium salt (1:1) / Sodium dodecylbenzenesulphonate / Dodecylbenzenesulfonic acid, sodium salt / Benzenesulfonic acid, dodecyl-, sodium salt / Benzenesulfonate, dodecyl-, sodium	CAS-No.: 25155-30-0	0.1 – 1

Comments

: *Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Log Jam

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.
First-aid measures general	: Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause damage to organs through prolonged or repeated exposure.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
-----------------------------------	--

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
------------------------------	---

5.2. Unsuitable extinguishing media

Unsuitable extinguishing media	: Direct water spray may cause frothing.
--------------------------------	--

5.3. Specific hazards arising from the hazardous product

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon.
-------------	---

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.
------------------	--

6.2. Methods and materials for containment and cleaning up

For containment	: Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
-----------------	---

Log Jam

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Do not breathe fume, spray, vapours. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.

Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Calcium oxide (1305-78-8)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA	2 mg/m ³
---------------	---------------------

USA - OSHA - Occupational Exposure Limits

OSHA PEL TWA [1]	5 mg/m ³
------------------	---------------------

Ethylene glycol (107-21-1)

USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA [ppm]	25 ppm (vapor fraction)
---------------------	-------------------------

ACGIH OEL STEL	10 mg/m ³ (inhalable particulate matter, aerosol only)
----------------	---

ACGIH OEL STEL [ppm]	50 ppm (vapor fraction)
----------------------	-------------------------

ACGIH chemical category	Not Classifiable as a Human Carcinogen
-------------------------	--

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves. Consult glove manufacturer's product information on material suitability and material thickness.

Eye protection:

Wear eye/face protection

Log Jam

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Viscous paste, textured.
Colour	: Various
Odour	: Slight Ammonia.
Odour threshold	: No data available
pH	: 9
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 212 °F (100 °C)
Flash point	: Not applicable
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not flammable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: 1.03
Density	: 1.03 g/cm ³
Solubility	: Negligible.
Partition coefficient n-octanol/water	: No data available
Viscosity, kinematic	: 178000 mm ² /s
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

Reactivity	: No dangerous reactions known under normal conditions of use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: None known.
Incompatible materials	: None known.
Hazardous decomposition products	: May include, and are not limited to: oxides of carbon.
Hardening time:	: No additional information available

Log Jam

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified.

Sodium dodecylbenzenesulfonate (25155-30-0)	
LD50 oral rat	500 mg/kg
LC50 inhalation rat	310 mg/m ³ (Exposure time: 4 h)
ATE CA (oral)	500 mg/kg bodyweight
ATE CA (vapours)	0.31 mg/l/4h
ATE CA (dust,mist)	0.31 mg/l/4h

Calcium oxide (1305-78-8)	
LD50 oral rat	500 mg/kg
LC50 inhalation rat	> 6.04 mg/l/4h
ATE CA (oral)	500 mg/kg bodyweight

Ethylene glycol (107-21-1)	
LD50 oral rat	4700 mg/kg
LD50 dermal rat	10600 mg/kg
LC50 inhalation rat	> 2.5 mg/l (Exposure time: 6 h)
ATE CA (oral)	500 mg/kg bodyweight

Skin corrosion/irritation : Not classified.
pH: 9

Serious eye damage/irritation : Causes serious eye irritation.
pH: 9

Respiratory or skin sensitization : Not classified.

Germ cell mutagenicity : Not classified.

Carcinogenicity : Not classified.

Reproductive toxicity : Not classified.

STOT-single exposure : Not classified.

STOT-repeated exposure : May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).

Aspiration hazard : Not classified.

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Chronic symptoms : May cause damage to organs through prolonged or repeated exposure.

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.

Log Jam

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : The generation of waste should be avoided or minimized wherever possible. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

SECTION 14: Transport information

In accordance with TDG

14.1. UN number

In accordance with TDG / DOT / IMDG / IATA

14.1. UN number

Not regulated for transport

14.2. UN proper shipping name

Proper Shipping Name (TDG) : Not applicable
Proper Shipping Name (DOT) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

TDG
Transport hazard class(es) (TDG) : Not applicable

DOT
Transport hazard class(es) (DOT) : Not applicable

IMDG
Transport hazard class(es) (IMDG) : Not applicable

IATA
Transport hazard class(es) (IATA) : Not applicable

Log Jam

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

14.4. Packing group

Packing group (TDG) : Not applicable
Packing group (DOT) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

TDG

No data available

DOT

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. National regulations

No additional information available


15.2. International regulations

No additional information available

SECTION 16: Other information

Issue date : 08-31-2017
Revision date : 08-30-2024
Supersedes : 05-24-2023

NFPA health hazard : 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

Health : 2 Moderate Hazard - Temporary or minor injury may occur
Health : * - Chronic (long-term) health effects may result from repeated overexposure

Log Jam

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Flammability	: 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical	: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.
Personal protection	: A - Safety glasses

Indication of changes			
Section	Changed item	Change	Comments
2	Classification (GHS CA)	Added	Version 2.1
SDS	SDS update	Modified	Version 2.1
14	Transport Information	Modified	Version 2.2

Other information	: None.
Prepared by	: Nexreg Compliance Inc. www.Nexreg.com



Safety Data Sheet (SDS), Canada - Nexreg 2022

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.