



PRESSURE CLEANERS



Made in Australia
SINCE 1982

HP3523

Cold Water Cleaner



Specifications

- ⇒ 350 bar (5076 psi) pump pressure
- ⇒ 435 bar (6309 psi) EWP pressure (optional)
- ⇒ 23 Litres Per Minute pump volume
- ⇒ 415 V 20 hp Electric motor
- ⇒ 1450 rpm low speed pump
- ⇒ Heavy duty machine

Standard Equipment

- ⇒ Interpump brass head pump
- ⇒ 10 Metre high pressure hose
- ⇒ RL56 Gun with S3 Lance, fixed nozzle & protector
- ⇒ VB350 Unloader valve & VS350 Safety Valve
- ⇒ 32 Amp three-phase plug
- ⇒ Water cooling tank
- ⇒ Operating and Maintenance manual

Features	Benefits
Interpump with ceramic pistons and brass head	Non-corrosive pump head to extend pump life and reduce maintenance costs
Water cooling tank	Protects the pump in bypass, when pistol trigger is closed
Inlet water filter	Stops debris from scoring pistons and seals
Pressure gauge	Easily monitor pump performance
3 Stage powder coated zinc annealed chassis and frame	Protects machine from corrosion and extends machine life

For more information,
please visit our website

spitwater.com.au

TOUGH + READY
CREATED BY **OTTICO**