

# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Revision Date 15-Jul-2025 Version 2

# 1. Identification

**Product identifier** 

Product Name PERMA SHIELD GASKET DRESSING & FLANGE SEALANT 2 FL.OZ

Other means of identification

Product Code 85420

UN number or ID number UN1133

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Restrictions on use No information available

Details of the supplier of the safety data sheet

Manufacturer Address May Also Be Distributed by:

ITW Permatex, Inc. ITW Permatex Canada 6875 Parkland Blvd. 101-2360 Bristol Circle

Solon, Ohio 44139 USA Oakville, ON Canada L6H 6M5 Telephone: 1-87-Permatex Telephone: (800) 924-6994

(866) 732-9502

E-mail address mail@permatex.com

Emergency telephone number

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

**24-hour emergency phone number** No information available

# 2. Hazard(s) identification

## Classification

Flammable liquids	Category 2
Serious eye damage/eye irritation	Category 2A
Respiratory sensitization	Category 1
Skin sensitization	Category 1
Carcinogenicity	Category 2
Reproductive toxicity	Category 1B
Specific target organ toxicity (single exposure)	Category 3

Specific target organ toxicity (repeated exposure)

Category 2

## Label elements

## Contains ACETONE; DIPHENYLMETHANEDIISOCYANATE; STANNE, DIBUTYLBIS(1-OXODODECYL)OXY



# **Danger**

### **Hazard statements**

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

May damage fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

# **Precautionary Statements - Prevention**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves, protective clothing, eye protection and face protection.

Wash face, hands and any exposed skin thoroughly after handling.

In case of inadequate ventilation wear respiratory protection.

Contaminated work clothing should not be allowed out of the workplace.

Use only outdoors or in a well-ventilated area.

Do not breathe dust.

Ground and bond container and receiving equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Use explosion-proof electrical, ventilating and lighting equipment.

Keep cool.

# **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see supplemental first aid instructions on this label).

#### Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice and attention.

### Skin

IF ON SKIN: Wash with plenty of water and soap.

If skin irritation or rash occurs: Get medical advice and attention.

Take off contaminated clothing and wash it before reuse.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

#### Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor.

Call a POISON CENTER or doctor if you feel unwell.

#### Fire

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

# **Precautionary Statements - Storage**

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

## **Precautionary Statements - Disposal**

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

8.72738 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

20.37211 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

61.76415 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

61.76415 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

18.70738 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

#### Other Information

May be harmful if inhaled. Causes mild skin irritation. Harmful to aquatic life.

# 3. Composition/information on ingredients

## Substance

Not applicable.

#### Mixture

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
ACETONE	67-64-1	30-60%	-	-
SILICA, AMORPHOUS	112926-00-8	3-7%	-	-
DIPHENYLMETHANEDIISOCY ANATE	101-68-8	1-5%	-	-
DIPHENYLMETHANE DIISOCYANATE [ISOMERS AND HOMOLOGUES]	9016-87-9	0.5-1.5%	-	-
STANNE, DIBUTYLBIS (1-OXOD ODECYL) OXY	77-58-7	0.1-1%	-	-

# 4. First-aid measures

### Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention.

**Inhalation** May cause allergic respiratory reaction. If breathing has stopped, give artificial respiration.

Get medical attention immediately. Remove to fresh air. Avoid direct contact with skin. Use

barrier to give mouth-to-mouth resuscitation.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes

and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic

reactions see a physician.

Ingestion May produce an allergic reaction. Do NOT induce vomiting. Rinse mouth. Never give

anything by mouth to an unconscious person. Get immediate medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Use

personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.

# Most important symptoms and effects, both acute and delayed

Symptoms May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/ or

wheezing. Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and

irritation.

Effects of Exposure May cause adverse reproductive effects - such as birth defect, miscarriages, or infertility.

May cause damage to organs through prolonged or repeated exposure. Suspected of

causing cancer.

## Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically.

# 5. Fire-fighting measures

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

**Unsuitable extinguishing media** Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by inhalation. May cause sensitization by skin contact.

**Explosion data** 

**Sensitivity to mechanical impact** None. **Sensitivity to static discharge** Yes.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

# 6. Accidental release measures

# Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the

product must be grounded. Do not touch or walk through spilled material.

**Other information** Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

## Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor

suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

# 7. Handling and storage

# Precautions for safe handling

#### Advice on safe handling

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Remove contaminated clothing and shoes.

## Conditions for safe storage, including any incompatibilities

## **Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.

# 8. Exposure controls/personal protection

# Control Parameters Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
ACETONE	TWA: 250 ppm	TWA: 1000 ppm	TWA: 250 ppm;
67-64-1	STEL: 500 ppm	TWA: 2400 mg/m <sup>3</sup>	TWA: 590 mg/m <sup>3</sup> ;
		(vacated) TWA: 750 ppm	IDLH: 2500 ppm
		(vacated) TWA: 1800 mg/m <sup>3</sup>	
		(vacated) STEL: 2400 mg/m <sup>3</sup>	
		The acetone STEL does not	
		apply to the cellulose acetate	
		fiber industry. It is in effect for	
		all other sectors.	
		(vacated) STEL: 1000 ppm	
SILICA, AMORPHOUS	-	TWA: 20 mppcf	-
112926-00-8		TWA: (80)/(% SiO2)	
		mg/m³	
		(vacated) TWA: 6 mg/m <sup>3</sup>	
		: (80)/(% SiO2) mg/m <sup>3</sup> TWA	
DIPHENYLMETHANEDIISOCYANATE	TWA: 0.005 ppm	Ceiling: 0.02 ppm	TWA: 0.005 ppm;
101-68-8		Ceiling: 0.2 mg/m <sup>3</sup>	TWA: 0.05 mg/m <sup>3</sup> ;
		(vacated) Ceiling: 0.02 ppm	Ceiling: 0.020 ppm 10 min
		regulated under Methylene	Ceiling: 0.2 mg/m <sup>3</sup> 10 min
		bisphenyl isocyanate	IDLH: 75 mg/m <sup>3</sup>
		(vacated) Ceiling: 0.2 mg/m <sup>3</sup>	
		regulated under Methylene	
		bisphenyl isocyanate	
STANNE, DIBUTYLBIS (1-OXODODEC	TWA: 0.1 mg/m <sup>3</sup> Sn	TWA: 0.1 mg/m <sup>3</sup> Sn	TWA: 0.1 mg/m <sup>3</sup> ; except

YL)OXY	STEL: 0.2 mg/m <sup>3</sup> Sn	(vacated) TWA: 0.1 mg/m <sup>3</sup> Sn	Cyhexatin Sn
77-58-7	pSk	Sdv	IDLH: 25 mg/m <sup>3</sup> Sn

Chemical name	Alberta	British Columbia	Ontario	Quebec
ACETONE	TWA: 500 ppm;	TWA: 250 ppm;	TWA: 250 ppm;	TWAEV: 250 ppm;
67-64-1	TWA: 1200 mg/m <sup>3</sup> ;	STEL: 500 ppm;	STEL: 500 ppm;	STEV: 500 ppm;
	STEL: 750 ppm;			
	STEL: 1800 mg/m <sup>3</sup> ;			
SILICA, AMORPHOUS	-	TWA: 4 mg/m³;	-	-
112926-00-8		TWA: 1.5 mg/m <sup>3</sup> ;		
		respirable		
DIPHENYLMETHANEDIISOCY	TWA: 0.005 ppm;	TWA: 0.005 ppm;	TWA: 0.005 ppm;	TWAEV: 0.005 ppm;
ANATE	TWA: 0.05 mg/m <sup>3</sup> ;	Ceiling: 0.01 ppm;	Ceiling: 0.02 ppm;	TWAEV: 0.051 mg/m <sup>3</sup> ;
101-68-8		RS		
DIPHENYLMETHANE	TWA: 0.005 ppm;	TWA: 0.005 ppm;	-	-
DIISOCYANATE [ISOMERS	TWA: 0.07 mg/m <sup>3</sup> ;	Ceiling: 0.01 ppm;		
AND HOMOLOGUES]				
9016-87-9				
STANNE, DIBUTYLBIS (1-OXOD	<b>5</b> ,	TWA: 0.1 mg/m <sup>3</sup> ;	TWA: 0.1 mg/m <sup>3</sup> ;	-
ODECYL)OXY	STEL: 0.2 mg/m <sup>3</sup> ;	STEL: 0.2 mg/m <sup>3</sup> ;	STEL: 0.2 mg/m <sup>3</sup> ;	
77-58-7	pSk	Sk	dSk	

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
ACETONE	TWA: 250 ppm; STEL: 500 ppm;			
DIPHENYLMETHANEDIISOCY ANATE	TWA: 0.005 ppm;	TWA: 0.005 ppm;	TWA: 0.005 ppm;	TWA: 0.005 ppm;

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
ACETONE	TWA: 500 ppm; TWA: 250 ppm; TWA		TWA: 500 ppm;	TWA: 1000 ppm;
	STEL: 750 ppm;	STEL: 500 ppm;	STEL: 750 ppm;	TWA: 2400 mg/m <sup>3</sup> ;
				STEL: 1250 ppm;
				STEL: 3000 mg/m <sup>3</sup> ;
SILICA, AMORPHOUS	TWA: 10 mg/m <sup>3</sup> ;		TWA: 10 mg/m <sup>3</sup> ;	
	STEL: 20 mg/m <sup>3</sup> ;		STEL: 20 mg/m <sup>3</sup> ;	
DIPHENYLMETHANEDIISOCY	TWA: 0.005 ppm;	TWA: 0.005 ppm;	TWA: 0.005 ppm;	Ceiling: 0.02 ppm;
ANATE	STEL: 0.015 ppm;		STEL: 0.015 ppm;	Ceiling: 0.2 mg/m <sup>3</sup> ;

# **Biological occupational exposure limits**

Chemical name	ACGIH
ACETONE	25 mg/L - urine (Acetone) - end of shift
67-64-1	

# **Appropriate engineering controls**

Engineering controls Showers

Eyewash stations Ventilation systems.

# Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles). Tight sealing safety goggles.

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Antistatic boots. Chemical resistant apron. Wear fire/flame

resistant/retardant clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required. Use

appropriate respiratory protection.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not

be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

# 9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid

**Appearance** No information available

Color Blue Odor Ketone

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No data available
Melting point / freezing point
Boiling point / boiling range
Flash point
No data available
S4 °C / 129.2 °F
-18 °C / -0.4 °F

**Evaporation rate** < 1 Butyl acetate = 1

Flammability (solid, gas) No data available

Flammability Limit in Air

Upper flammability limit: 12.8% Lower flammability limit: 2.6%

Vapor pressure No data available

Vapor density >1 Air = 1

Relative density 1.04

Water solubility
Solubility(ies)
Partially soluble
No data available
Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
No data available

Particle characteristics

Particle Size No data available
Particle Size Distribution No data available

Other information

Explosive properties
Oxidizing properties
No information available
No information available
No information available
No information available

VOC content < 1%

DensityNo information availableBulk densityNo information available

# 10. Stability and reactivity

**Reactivity** No information available.

**Chemical stability** Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

**Conditions to avoid** Heat, flames and sparks.

**Incompatible materials**None known based on information supplied.

Hazardous decomposition products Carbon oxides. Nitrogen oxides (NOx). Isocyanates.

# 11. Toxicological information

### Information on likely routes of exposure

## **Product Information**

**Inhalation** Specific test data for the substance or mixture is not available. May cause sensitization in

susceptible persons, (based on components). May cause irritation of respiratory tract. May

cause drowsiness or dizziness. May be harmful if inhaled.

**Eye contact** Specific test data for the substance or mixture is not available. Causes serious eye irritation.

(based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. Repeated or prolonged skin

contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitization by skin contact. Prolonged contact may cause redness and

irritation. Causes mild skin irritation.

**Ingestion** Specific test data for the substance or mixture is not available. May cause additional effects

as listed under "Inhalation". Ingestion may cause gastrointestinal irritation, nausea, vomiting

and diarrhea.

## Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling

of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Prolonged contact may cause redness and

irritation.

Acute toxicity

# **Numerical measures of toxicity**

## The following ATE values have been calculated for the mixture

 ATEmix (oral)
 12,157.80 mg/kg

 ATEmix (dermal)
 29,541.80 mg/kg

 ATEmix (inhalation-gas)
 99,999.00 ppm

 ATEmix (inhalation-vapor)
 99,999.00 mg/l

 ATEmix (inhalation-dust/mist)
 18.80 mg/l

8.72738 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

20.37211 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

61.76415 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

61.76415 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

18.70738 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

**Component Information** 

Component innormation				
Chemical name	Oral LD50	Dermal LD50	Inhalation LC50	
ACETONE	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m <sup>3</sup> (Rat) 8 h	
67-64-1				

Revision Date 1	15	Jul-2025
-----------------	----	----------

SILICA, AMORPHOUS 112926-00-8	> 20000 mg/kg (Rat)	-	-
DIPHENYLMETHANEDIISOCYANATE 101-68-8	= 31600 mg/kg (Rat)	-	= 369 mg/m <sup>3</sup> (Rat) 4 h
DIPHENYLMETHANE DIISOCYANATE [ISOMERS AND HOMOLOGUES] 9016-87-9	= 49 g/kg (Rat)	> 9.4 g/kg (Rabbit)	= 490 mg/m <sup>3</sup> (Rat) 4 h
STANNE,DIBUTYLBIS(1-OXODODEC YL)OXY 77-58-7	= 45 mg/kg (Rat)	> 2000 mg/kg (Rat)	-

Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Skin corrosion/irritation**Classification based on data available for ingredients. Causes mild skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an

allergic skin reaction.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. Suspected of causing cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
ACETONE	A4 - Not Classifiable as	-	-	-
67-64-1	a Human Carcinogen			
SILICA, AMORPHOUS	-	Group 3 -	-	-
112926-00-8		Unclassifiable as to		
		carcinogenicity in		
		humans		
DIPHENYLMETHANEDIISOCY	-	Group 3 -	-	-
ANATE		Unclassifiable as to		
101-68-8		carcinogenicity in		
		humans		
DIPHENYLMETHANE	-	Group 3 -	-	-
DIISOCYANATE [ISOMERS		Unclassifiable as to		
AND HOMOLOGUES]		carcinogenicity in		
9016-87-9		humans		
STANNE, DIBUTYLBIS (1-OXOD		-	-	-
ODECYL)OXY	a Human Carcinogen			
77-58-7				

## Legend

IARC (International Agency for Research on Cancer)

Group 3 - Not classifiable as to carcinogenicity in humans

Reproductive toxicity Contains a known or suspected reproductive toxin. Classification based on data available

for ingredients. May damage fertility or the unborn child.

**STOT - single exposure** May cause drowsiness or dizziness.

**STOT - repeated exposure** May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** No information available.

# 12. Ecological information

**Ecotoxicity** Harmful to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
ACETONE	-	LC50: 4.74 - 6.33mL/L	-	EC50: 10294 -
67-64-1		(96h, Oncorhynchus		17704mg/L (48h,
		mykiss)		Daphnia magna)
		LC50: 6210 - 8120mg/L		EC50: 12600 -
		(96h, Pimephales		12700mg/L (48h,
		promelas)		Daphnia magna)
		LC50: =8300mg/L (96h,		_
		Lepomis macrochirus)		

Persistence and degradability

No information available.

#### **Bioaccumulation**

**Component Information** 

Chemical name	Partition coefficient	
ACETONE	-0.24	
67-64-1		
DIPHENYLMETHANEDIISOCYANATE	4.51	
101-68-8		
STANNE, DIBUTYLBIS (1-OXODODECYL) OXY	4.44	
77-58-7		

Other adverse effects

No information available.

# 13. Disposal considerations

## Waste treatment methods

Waste from residues/unused

products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

**US EPA Waste Number** 

Waste designations and classifications should be determined by the end user based on the application for which the product was used.

California waste information

This product contains one or more substances that are listed with the State of California as a hazardous waste.

# 14. Transport information

DOT

UN1133 **UN** number or ID number Proper shipping name Adhesives Transport hazard class(es) 3 Packing group Ш

**DOT Marine Pollutant** NF

**Description** UN1133, Adhesives, 3, II **Special Provisions** 149, B52, IB2, T4, TP1, TP8

Emergency Response Guide 128

Number

**TDG** 

UN number or ID number
UN proper shipping name
Transport hazard class(es)
UN1133
Adhesives
3

Packing group

**Description** UN1133, Adhesives, 3, II

**MEX** 

UN number or ID number UN1133 UN proper shipping name Adhesives Transport hazard class(es)

Packing group

**Description** UN1133, Adhesives, 3, II, Limited Quantity

ICAO (air)

UN number or ID number
UN proper shipping name
Adhesives

Transport hazard class(es) 3
Packing group ||

**Description** UN1133, Adhesives, 3, II

Special Provisions A3

IATA

UN number or ID number UN1133 UN proper shipping name Adhesives

Transport hazard class(es) 3
Packing group II
ERG Code 3L
Special Provisions A3

**Description** UN1133, Adhesives, 3, II

<u>IMDG</u>

UN number or ID number UN1133 UN proper shipping name Adhesives

Transport hazard class(es)

Packing group

EmS-No.

F-E. S-D

**Description** UN1133, Adhesives, 3, II, (-18°C c.c.), Limited Quantity

# 15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

**International Regulations** 

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

**International Inventories** 

TSCA Complies
DSL/NDSL Complies
EINECS/ELINCS Complies

# 85420 - PERMA SHIELD GASKET DRESSING & FLANGE SEALANT 2 FL.OZ

Revision Date 15-Jul-2025

ENCS Not determined IECSC Complies KECI Complies PICCS Complies AICS Not determined NZIOC Not determined Complies

## Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances **IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing Chemicals Inventory

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances
NZIOC - New Zealand Inventory of Chemicals

## **US Federal Regulations**

## **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %	
DIPHENYLMETHANEDIISOCYANATE - 101-68-8	1.0	
DIPHENYLMETHANE DIISOCYANATE [ISOMERS AND	1.0	
HOMOLOGUES] - 9016-87-9		

## SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

# **CWA (Clean Water Act)**

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

## **CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous	Reportable Quantity (RQ)
Chemical hame	Tiazardous Substances NQS		Reportable Quantity (NQ)
		Substances RQs	
ACETONE	5000 lb /	-	RQ 5000 lb final RQ
67-64-1	kg (final RQ)		RQ 2270 kg final RQ
DIPHENYLMETHANEDIISOCYANATE	5000 lb /	-	RQ 5000 lb final RQ
101-68-8	kg (final RQ)		RQ 2270 kg final RQ

## **US State Regulations**

# **California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65	
Ethanol - 64-17-5	Carcinogen	
	Developmental	

Ethanol has been shown to be a reproductive toxin only when consumed as an alcoholic beverage Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage

# **U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
ACETONE	X	X	X
67-64-1			
SILICA, AMORPHOUS	X	X	X

Revision Date	15-Jul-2025
---------------	-------------

112926-00-8			
DIPHENYLMETHANEDIISOCYANATE	X	X	X
101-68-8			
DIPHENYLMETHANE	X	-	-
DIISOCYANATE [ISOMERS AND			
HOMOLOGUES]			
9016-87-9			
Ethanol	X	X	X
64-17-5			
2,4'-Diphenylmethane Diisocyanate	X	-	-
(MDI)			
5873-54-1			
2,2'-Diphenylmethane Diisocyanate	X	-	-
2536-05-2			

## U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

# 16. Other information

NFPA<br/>HMISHealth hazards3Flammability3Instability0Special hazards-Chronic Hazard Star Legend\*= Chronic Health Hazard\*= Chronic Health Hazard\*= Chronic Health Hazard

### Key or legend to abbreviations and acronyms used in the safety data sheet

## Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

# Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value \* Skin designation

+ Sensitizers

#### Key literature references and sources for data used to compile the SDS

U.S. Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

U.S. Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program

# 85420 - PERMA SHIELD GASKET DRESSING & FLANGE SEALANT 2 FL.OZ

Revision Date 15-Jul-2025

International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set United Nations World Health Organization (WHO)

Revision Date 15-Jul-2025

Revision Note No information available.

**Disclaimer** 

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.