

PROJECT: _____

TYPE: _____

DATE: _____

NOTES: _____

2"

47204 LENSED ROUND FIXED DOWNLIGHT



2700K . 3000K . 3500K . 4000K . 5000K



The Midway collection is a family of integrated led recessed lights available in sizes ranging from 2"-6". With their durable die cast aluminum bodies and built on CCT color selecting switch Midway family fixtures are aesthetically appealing, functional and extremely versatile. Their IC rated shallow bodies allow them to be used in most residential and commercial installations with or without insulation in the ceiling. Midway fixtures are available in white or black finish and come standard with a reliable phase dimming power supply.

SPECIFICATIONS

LIGHT HOUSING

- IC Airtight Cast aluminum body.
- Remodel application. C/W spring loaded clips.
- Mates to driver box with quick connector.
- Max Ceiling thickness 5/8".
- Approved for wet location.

DIMENSIONS

- Cut hole: ø2 7/8".
- Fixture: ø3 1/8" x 2 3/8"H.

ELECTRICAL

- 120 V Input class 2 constant current dimmable driver enclosed in junction box.
- TRIAC and ELV dimming.
- Min operating temperature (-4°F~-104°F) (-20°C~-40°C).

LIGHT MODULE

- 1 x 8W Integrated LED COB.
- Lumen maintenance 70% 50,000 hrs.
- CRI: 90+
- Beam angle: 38 degree.
- Kelvin (CCT): 27K | 30K | 35K | 40K | 50K
- Delivered Lumen: 467 lm | 490 lm | 525 lm | 548 lm | 554 lm

CERTIFICATIONS



ORDERING GUIDE

MODEL	FINISH
47204-010	White

	WATTS	LUMENS	KELVIN	DIMMABLE	CRI	BEAM ANGLE	ADJUSTABLE
2 7/8"	8W	Up to 554	CCT Selectable	TRIAC/ELV	90+	38°	NO




PRODUCT DIMENSIONS



FINISHES



010- White



ACCESSORIES



45612-015
60"
3 pin Connector



45363-016
NEW CONSTRUCTION
SMASH PLATE
13 1/4" x 6 1/2"
ø2 3/4"





47205-017
15W REMOTE
EMERGENCY
BACKUP BATTERY



NO IC BOX
REQUIRED

PHOTOMETRICS

Imperial



Metrics

