



- Notes:
1. A symbol "△" means "Key control" dimensions;
 2. A symbol "Ⓜ" will be next to any dimensions view or note which has been modified with the current drawing revision;
 3. RoHs compliant ;
 4. Operating temperature: 0°C~70°C ;
 5. 100% bit error test and performance test;
 6. Electrical and mechanical performance shall meet SFF-8431;

Item	L (Unit: M)	Tolerance (Unit: CM)
1	≤1	+5/-0
2	1<L≤4.5	+15/-0
3	4.5<L≤14.5	+30/-0
4	≥14.5	+2%/-0

date	signature	Discription	Version
2020-06-05	Rex-Yu	new shell	A1
2019-4-17	Rex-Yu	New drawing	A0

7					
6					
5	82050005	A0	Module protector, material is PVC	pcs	2
4	83020010	A0	25*11mm module label, white	pcs	2
3		A0	SFP28 25G OM3 LSZH optical cable, aqua blue	pcs	1
2	22020002	A0	SFP28 25G AOC PCBA	pcs	2
1	23020004	A0	SFP28 25G AOC shell, blue pull tab	set	2
Item	PN	Version	Discription	Unit	Quantity
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN METRIC TOLERANCE ARE: DECIMALS			CAD GENERATED DRAWING, DO NOT MANUALLY UPDATE		
Unit: mm					
MATERIAL:			THE FIRST VIEW	TITLE: 25G SFP28 AOC (OM3)	
DESIGNED			APPROVALS / DATE		
SURFACE AND COLOR:			DESIGNED	SIZE A4 PART NO: AOC-SFP28-25G-xxxM REV. A1	
CUSTOMER CODE:			Rex-Yu/2020-06-05 CHECKED Rex-Yu/2020-06-05 APPROVED	SCALE: 1:1 CAD FILE: SHEET: 1 OF 1	