



IPL1/0-3C SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPL1/0-3C	3	2.24
IPL1/0-4C	4	2.89
IPL1/0-5C	5	3.54
IPL1/0-6C	6	4.19
IPL1/0-8C	8	5.49
IPL1/0-10C	10	6.79
IPL1/0-12C	12	8.09
IPL1/0-14C	14	9.39

NOTES:

- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
- UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
- DUAL RATED FOR 90°C COPPER AND/OR ALUMINUM CONDUCTOR.
- COLD TEMPERATURE RATED TO -45°C.
- HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION AND CHEMICAL RESISTANT.

CONTACT NSi FOR SALES @ 800.321.5847

		POLARIS SALES . CO . INC
<small>PROPRIETARY AND CONFIDENTIAL</small>		<small>11625 PROSPEROUS DRIVE ODESSA, FL 33556</small>
<small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.</small>		TITLE: CLEAR INSULATED 1/0 CONNECTOR
<small>NAME</small> <small>DATE</small>		DWG. NO. IPL1/0C SERIES
<small>DRAWN BY</small> T.MITCHELL <small>DATE</small> 11/29/2021		
MATERIAL: N/A		SCALE: N/A
		SHEET: 1 OF 1