

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : eXactColor Base

1.2. Recommended use and restrictions on use

Recommended use : Caulking

This SDS is designed for workplace employees, emergency personnel and for other situations where there is potential for large-scale or prolonged exposure, in accordance with the OSHA requirements.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label, MSDS or both in accordance with applicable government regulations.

1.3. Supplier

Supplier

Sashco Inc.
14802 Grant St.
Thornton, CO, 80023
USA
T 800-767-5656
info@sashco.com

1.4. Emergency telephone number

Emergency number : 800-535-5053

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

STOT RE 2

May cause damage to organs (kidneys) through prolonged or repeated exposure (oral)

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Warning

Hazard statements (GHS US) :

May cause damage to organs (kidneys) through prolonged or repeated exposure (oral)

Precautionary statements (GHS US) :

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Do not breathe fume, spray, vapors.

Get medical advice/attention if you feel unwell.

Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards which do not result in classification

No additional information available

eXactColor Base

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Distillates, petroleum, hydrotreated heavy paraffinic	CAS-No.: 64742-54-7	3 - 7
Silica, amorphous, precipitated and gel	CAS-No.: 112926-00-8	1 – 5
Ethylene glycol	CAS-No.: 107-21-1	1 – 5
Sodium dodecylbenzenesulfonate	CAS-No.: 25155-30-0	0.1 < 1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general	: Get medical advice/attention if you feel unwell.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: If skin irritation occurs: Wash skin with plenty of water. Obtain medical attention if irritation persists.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause damage to organs through prolonged or repeated exposure.

4.3. Immediate medical attention and special treatment, if necessary

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Direct water spray may cause frothing.

eXactColor Base

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

5.2. Specific hazards arising from the chemical

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon. Acrylic monomers.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Prevent further leakage or spillage. Keep away from drains, surface and ground-water and soil. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with skin and eyes. Do not breathe fume, spray, vapors. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.

Hygiene measures : Wash contaminated clothing before reuse. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store at room temperature. Keep from freezing. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

eXactColor Base

No additional information available

eXactColor Base

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Sodium dodecylbenzenesulfonate (25155-30-0)	
No additional information available	

Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)	
No additional information available	

Ethylene glycol (107-21-1)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA [ppm]	25 ppm (vapor fraction)
ACGIH OEL STEL	10 mg/m ³ (inhalable particulate matter, aerosol only)
ACGIH OEL STEL [ppm]	50 ppm (vapor fraction)
ACGIH chemical category	Not Classifiable as a Human Carcinogen

Silica, amorphous, precipitated and gel (112926-00-8)	
USA - OSHA - Occupational Exposure Limits	
Local name	Silica, amorphous, precipitated and gel
OSHA PEL (TWA) [1]	20 mppcf
OSHA PEL (TWA) [2]	20 mppcf
Remark (OSHA)	Table Z-3. For OSHA PEL (TWA): Use formula: (80 mg/m ³ / (%SiO ₂)) for mg/m ³ . CAS No. source: eCFR Table Z-1.
Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts

Exposure limit values of other components

Formaldehyde (50-00-0)	
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [2]	0.75 ppm
OSHA PEL (STEL) [2]	2 ppm (see 29 CFR 1910.1048)
Remark (OSHA)	Formaldehyde is subject to the standard 29 CFR 1910.1048, which may contain specific requirements for handling including protective equipment, regulated areas, monitoring and medical surveillance. The employer should review the standard and assure compliance with applicable requirements.

Ethylene oxide (75-21-8)	
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (TWA) [2]	1 ppm
OSHA PEL (STEL) [2]	5 ppm (see 29 CFR 1910.1047)
Remark (OSHA)	Ethylene Oxide is subject to the standard 29 CFR 1910.1047, which may contain specific requirements for handling including protective equipment, regulated areas, monitoring and medical surveillance. The employer should review the standard and assure compliance with applicable requirements.

8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.
Environmental exposure controls	: Avoid release to the environment.

eXactColor Base

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves. Consult glove manufacturer's product information on material suitability and material thickness.

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: White liquid.
Color	: White
Odor	: Slight ammonia
Odor threshold	: No data available
pH	: 6.5
Melting point	: No data available
Freezing point	: No data available
Boiling point	: 212 °F (100 °C)
Flash point	: Not applicable
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.04
Solubility	: Negligible.
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: 12500 mm ² /s
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

eXactColor Base

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Sodium dodecylbenzenesulfonate (25155-30-0)	
LD50 oral rat	500 mg/kg
LC50 inhalation rat	310 mg/m ³ (Exposure time: 4 h)
ATE US (oral)	500 mg/kg body weight
ATE US (gases)	100 ppmV/4h
ATE US (vapors)	0.31 mg/l/4h
ATE US (dust, mist)	0.31 mg/l/4h
Distillates, petroleum, hydrotreated heavy paraffinic (64742-54-7)	
LD50 oral rat	> 15 g/kg
LD50 dermal rabbit	> 5000 mg/kg
Ethylene glycol (107-21-1)	
LD50 oral rat	4700 mg/kg
LD50 dermal rat	10600 mg/kg
LC50 inhalation rat	> 2.5 mg/l (Exposure time: 6 h)
ATE US (oral)	500 mg/kg body weight

Skin corrosion/irritation : Not classified
pH: 6.5

eXactColor Base

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Serious eye damage/irritation	: Not classified pH: 6.5
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: May cause damage to organs (kidneys) through prolonged or repeated exposure (oral).
Aspiration hazard	: Not classified
Viscosity, kinematic	: 12500 mm ² /s
Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/effects after eye contact	: May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with possible redness and swelling.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause damage to organs through prolonged or repeated exposure.
Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

14.1. UN number

Not regulated for transport

eXactColor Base

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable
Proper Shipping Name (IMDG) : Not applicable
Proper Shipping Name (IATA) : Not applicable

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : Not applicable

IMDG
Transport hazard class(es) (IMDG) : Not applicable

IATA
Transport hazard class(es) (IATA) : Not applicable

14.4. Packing group

Packing group (DOT) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information


15.1. US Federal regulations

No additional information available

15.2. International regulations

No additional information available

15.3. US State regulations

 **WARNING:** This product can expose you to Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

SECTION 16: Other information

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Issue date : 11/04/2014
Revision date : 05/19/2023
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com




eXactColor Base

Safety Data Sheet

according to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2012.

Full text of H-phrases	
STOT SE 1	Specific target organ toxicity (single exposure) Category 1

NFPA health hazard : 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating
Health : 2 Moderate Hazard - Temporary or minor injury may occur
Health : * - Chronic (long-term) health effects may result from repeated overexposure
Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Indication of changes:			
Section	Changed item	Change	Comments
2	GHS-US classification	Modified	V3.2
3	Composition/Information on ingredients	Modified	V3.2
SDS	SDS update	Modified	V3.2

Safety Data Sheet (SDS), USA

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.