BE ORANGE.

BE FAST.

3000-RT AND 3100-RT SERIES RAINTIGHT RIGID FITTINGS

- GREAT FOR WET/EXPOSED LOCATION INSTALLATIONS
- PARKING GARAGES, LOADING DOCKS, WAREHOUSE AND TRANSIT FACILITY APPLICATIONS
- ½" THROUGH 2" TRADE SIZES AVAILABLE
- SAVE TIME CONNECTING THREADLESS RIGID IN WET LOCATIONS





RAINTIGHT COMPRESSION FITTINGS FOR RIGID AND IMC

Raintight Rigid Compression Connectors



Zinc Plated Steel

| Catalog Number | Trade Size | Unit Qty. | Std. Pkg. |
|-------------------|---------------|--------------|--------------|
| 3000-RT | 1/2" | 25 | 100 |
| 3001-RT | 3/4" | 25 | 100 |
| 3002-RT | 1" | 5 | 25 |
| 3003-RT | 1 1/4" | 5 | 25 |
| 3004-RT | 1 1/2" | 2 | 10 |
| 3005-RT | 2" | 1 | 5 |





Compression type connector used to join unthreaded steel rigid conduit to box or enclosure in a wet location.

ւ(Սև)սs File No. E9391

Raintight Rigid



Zinc Plated Steel

| Catalog | Trade | Unit | Std. |
|---------|--------|------|------|
| Number | Size | Qty. | Pkg. |
| 3100-RT | 1/2" | 25 | 100 |
| 3101-RT | 3/4" | 25 | 100 |
| 3102-RT | 1" | 5 | 25 |
| 3103-RT | 1 1/4" | 5 | 25 |
| 3104-RT | 1 1/2" | 2 | 10 |
| 3105-RT | 2" | 1 | 5 |
| | | | |

Compression Couplings



Compression type connector used to join unthreaded steel rigid conduit to box or enclosure in a wet location.

c(VL)us File No. E9391