


## Professional Nuclear Grade Duct Tape



**Backing**

**Adhesive**



**Backing:** PE Coated Cloth

**Adhesive:** Rubber

**Liner:** N/A

**Colors:** White, Yellow, Silver

**Specifications:** Meets NRC Reg 1.38 & ASME NQA-1  
 Tested in accordance with UL 723

**Standard Sizes:** 48mm x 55m, 72mm x 55m

### Applications

- Multiple uses in powerplants and on ships
- Heavy-duty packaging and bundling
- Color Coding
- Holding dosimeters, securing clothing and gloves, wrapping pipe ends, insulation, and duct sealing

### Features

- PE-Coated Cloth Backing
- Natural Rubber Adhesive

### Benefits

- Excellent balance of tensile strength and tearability
- Aggressive adhesion to rough surfaces
- Superior holding power for hanging applications

### Typical Test Values

	Standard UOM	Metric UOM	Test Method
<b>Total Thickness</b>	11.0 mils	0.279 mm	ASTM D-1000
<b>Adhesion to Steel</b>	99 oz/in	10.80 N/cm	PSTC-101
<b>Tensile Strength</b>	23 lb/in	40.30 N/cm	ASTM D-1000
<b>Operating Temperature</b>	40 to 200 °F	4 to 93 °C	
<b>Elongation</b>	21%		ASTM D-1000
<b>VOC Content</b>	<1 g/L		

Recommended Storage Conditions: 60-80 °F at 40-60% RH  
 Standard Shelf Life (at 25 °C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY GLOBAL, INC. by qualified technical personnel. To Berry Global's knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which Berry Global assumes any legal responsibility.

2320 Bowling Green Road | Franklin, KY 42134  
 1-800-343-7878 Fax 1-800-328-4822

www.vybond.com

8/10/25