

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Revision Date 14-Oct-2024 Version 2

1. Identification

Product identifier

Product Name PX ENGINE OIL STOP LEAK 12 OZ

Other means of identification

Product Code 30302

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use See directions provided with product

Restrictions on useAll other applications

Details of the supplier of the safety data sheet

Manufacturer AddressMay Also Be Distributed by:ITW Permatex, Inc.ITW Permatex Canada6875 Parkland Blvd.101-2360 Bristol Circle

Solon, Ohio 44139 USA Oakville, ON Canada L6H 6M5 Telephone: 1-87-Permatex Telephone: (800) 924-6994

(866) 732-9502

E-mail address mail@permatex.com

Emergency telephone number

Company Phone Number 866-732-9502

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

24-hour emergency phone number No information available

2. Hazard(s) identification

Classification

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Carcinogenicity	Category 1B
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 2

Label elements





Danger

Hazard statements

Harmful if inhaled.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use personal protective equipment as required.

Use only outdoors or in a well-ventilated area.

Do not breathe dust, fume, gas, mist, vapors and spray.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Precautionary Statements - Storage

Store locked up.

Precautionary Statements - Disposal

Dispose of contents and container to an approved waste disposal plant.

Unknown acute toxicity

12.54 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

80.13 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

91.99 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Other Information

May be harmful in contact with skin. Causes mild skin irritation.

3. Composition/information on ingredients

Substance

Not applicable.

<u>Mixture</u>

Chemical name	CAS No.	Weight-%	Information Review	Date HMIRA filed and date exemption granted (if applicable)
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC	64742-55-8	5-10%	-	-
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY	64742-54-7	5-10%	-	-

PARAFFINIC				
XYLENE	1330-20-7	1-5%	-	-
TOLUENE	108-88-3	1-5%	-	-
ETHYL BENZENE	100-41-4	1-5%	-	-

4. First-aid measures

Description of first aid measures

General advice IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the

doctor in attendance.

Inhalation Remove to fresh air. If symptoms persist, call a physician. If breathing has stopped, give

artificial respiration. Get medical attention immediately.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin contact Wash skin with soap and water.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. Get medical attention.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved, take precautions to

protect themselves and prevent spread of contamination. Avoid breathing vapors or mists.

Use personal protective equipment as required. See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms Prolonged contact may cause redness and irritation. Coughing and/ or wheezing. Difficulty

in breathing.

Effects of Exposure May cause cancer. May cause adverse reproductive effects - such as birth defect,

miscarriages, or infertility. May cause damage to organs through prolonged or repeated

exposure.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

surrounding environment.

Small Fire In case of fire, use water spray, foam, dry chemical, or CO2. Large Fire In case of fire, use water spray, foam, dry chemical, or CO2.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

No information available.

Hazardous combustion products No information available.

Explosion data

Sensitivity to mechanical impact None. **Sensitivity to static discharge** None.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation. Avoid breathing vapors or mists. Use personal protective

equipment as required.

Other information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Avoid breathing vapors or mists. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up. Keep containers tightly closed in a dry, cool and well-ventilated place.

Keep out of the reach of children.

8. Exposure controls/personal protection

Control parameters Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
XYLENE	TWA: 20 ppm	TWA: 100 ppm	-
1330-20-7		TWA: 435 mg/m ³	
		(vacated) TWA: 100 ppm	
		(vacated) TWA: 435 mg/m ³	
		(vacated) STEL: 150 ppm	
		(vacated) STEL: 655 mg/m ³	
TOLUENE	TWA: 20 ppm	TWA: 200 ppm	IDLH: 500 ppm
108-88-3	Ototoxicant - potential to	(vacated) TWA: 100 ppm	TWA: 100 ppm
	cause hearing disorders	(vacated) TWA: 375 mg/m ³	TWA: 375 mg/m ³
		(vacated) STEL: 150 ppm	STEL: 150 ppm
		(vacated) STEL: 560 mg/m ³	STEL: 560 mg/m ³
		Ceiling: 300 ppm	
ETHYL BENZENE	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm
100-41-4	Ototoxicant - potential to	TWA: 435 mg/m ³	TWA: 100 ppm

cause hearing disorders	(vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³	TWA: 435 mg/m ³ STEL: 125 ppm
	(vacated) STEL: 125 ppm	STEL: 545 mg/m ³
	(vacated) STEL: 545 mg/m ³	•

Chemical name	Alberta	British Columbia	Ontario	Quebec
XYLENE	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm
1330-20-7	TWA: 434 mg/m ³	STEL: 150 ppm	STEL: 150 ppm	TWA: 434 mg/m ³
	STEL: 150 ppm			STEL: 150 ppm
	STEL: 651 mg/m ³			STEL: 651 mg/m ³
TOLUENE	TWA: 50 ppm	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm
108-88-3	TWA: 188 mg/m ³	Adverse reproductive		
	Sk*	effect		
ETHYL BENZENE	TWA: 100 ppm	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm
100-41-4	TWA: 434 mg/m ³			
	STEL: 125 ppm			
	STEL: 543 mg/m ³			

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
XYLENE	TWA: 20 ppm	TWA: 100 ppm STEL: 150 ppm	TWA: 20 ppm	TWA: 20 ppm
TOLUENE	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm
ETHYL BENZENE	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm	TWA: 20 ppm

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
XYLENE	TWA: 100 ppm STEL: 150 ppm	TWA: 20 ppm	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 435 mg/m³ STEL: 150 ppm STEL: 650 mg/m³ Sk*
TOLUENE	TWA: 50 ppm STEL: 60 ppm Sk*	TWA: 20 ppm	TWA: 50 ppm STEL: 60 ppm Skin	TWA: 100 ppm TWA: 375 mg/m³ STEL: 150 ppm STEL: 560 mg/m³ Sk*
ETHYL BENZENE	TWA: 100 ppm STEL: 125 ppm Designated substance	TWA: 20 ppm	TWA: 100 ppm STEL: 125 ppm Designated Chemical Substance	TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³

Biological occupational exposure limits

Chemical name	ACGIH
XYLENE	0.3 g/g creatinine - urine (total of all isomers of
1330-20-7	Methylhippuric acids) - end of shift
TOLUENE	0.02 mg/L - blood (Toluene) - prior to last shift of workweek
	0.03 mg/L - urine (Toluene) - end of shift
	0.3 mg/g creatinine - urine (o-Cresol with hydrolysis) - end
	of shift
ETHYL BENZENE	150 mg/g creatinine - urine (Sum of mandelic acid and
100-41-4	phenylglyoxylic acid) - end of shift

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves.

Skin and body protectionWear suitable protective clothing.

Respiratory protection Appropriate respiratory protection should be selected and used according to the chemical

nature, hazards and use of this product and safety requirements of the local jurisdiction. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be

required.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and

immediately after handling the product.

Thermal hazards No information available.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid

Appearance No information available

Color Amber

Odor No information available
Odor threshold No information available

PropertyValuesRemarks • MethodpHNo data available10% in deionized water

Melting point / freezing point No data available Estimated

Boiling point / boiling range > 35 °C / 95 °F Flash point > 35 °C / 375.8 °F

Evaporation rate Not applicable Butyl acetate = 1

Flammability (solid, gas)

No data available

Flammable in the presence of the following materials

or conditions: open flames, sparks and static

discharge.

Flammability Limit in Air None known

Upper flammability limit:

Lower flammability limit:

No data available

No data available

Vapor pressureNo Data AvailablemmHgVapor densityNo data availableAir = 1

Relative density 0.87

Water solubilityNo data availablePolymerizationSolubility(ies)No Data AvailableNone knownPartition coefficientNo Data AvailableNone knownAutoignition temperatureNo data availableEstimated

Decomposition temperatureNo data available
Remarks: Self-Accelerating decomposition

temperature (SADT): 50 °C SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a

self-accelerating decomposition reaction.

Kinematic viscosity 3080 mm2/s

Dynamic viscosityNo data available
Remarks: Self-Accelerating decomposition

temperature (SADT): 50 °C SADT-Self Accelerating Decomposition Temperature. Lowest temperature at which the tested package size will undergo a self-accelerating decomposition reaction.

Other information

Explosive properties
Oxidizing properties
No information available

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Hazardous polymerization No information available.

Conditions to avoid Excessive heat.

Incompatible materialsNone known based on information supplied.

Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Harmful by inhalation. (based

on components).

Eye contact Specific test data for the substance or mixture is not available.

Skin contact Specific test data for the substance or mixture is not available. Causes mild skin irritation.

May be harmful in contact with skin.

Ingestion Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Prolonged contact may cause redness and irritation. Coughing and/ or wheezing.

Acute toxicity Harmful by inhalation.

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 5,082.10 mg/kg

 ATEmix (dermal)
 3,352.40 mg/kg

 ATEmix (inhalation-gas)
 99,999.00 ppm

 ATEmix (inhalation-vapor)
 99,999.00 mg/l

 ATEmix (inhalation-dust/mist)
 2.12 mg/l

Unknown acute toxicity

12.54 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

80.13 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

100 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

91.99 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Component information			
Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
DISTILLATES (PETROLEUM),	-	-	= 3900 mg/m ³ (Rat) 4 h
HYDROTREATED LIGHT			
PARAFFINIC			
64742-55-8			
DISTILLATES (PETROLEUM),	> 15 g/kg (Rat)	> 5000 mg/kg (Rabbit)	-
HYDROTREATED HEAVY			
PARAFFINIC			
64742-54-7			
XYLENE	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
1330-20-7			
TOLUENE	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
108-88-3			1
ETHYL BENZENE	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
100-41-4			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes mild skin irritation.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen

The table below indicates whether each agency has listed any ingredient as a carcinogen.				
Chemical name	ACGIH	IARC	NTP	OSHA
DISTILLATES (PETROLEUM),	A2	Group 1	Known	X
HYDROTREATED LIGHT				
PARAFFINIC				
64742-55-8				
DISTILLATES (PETROLEUM),	A2	Group 1	Known	X
HYDROTREATED HEAVY				
PARAFFINIC				
64742-54-7				
XYLENE	-	Group 3	-	-
1330-20-7				
TOLUENE	-	Group 3	-	-
108-88-3				
ETHYL BENZENE	A3	Group 2B	-	X
100-41-4				

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected Human Carcinogen

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity Classification based on data available for ingredients. Suspected of damaging fertility or the

unborn child.

STOT - single exposure No information available.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard No information available.

Neurological effects No information available.

12. Ecological information

Ecotoxicity The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT PARAFFINIC 64742-55-8	-	LC50: >5000mg/L (96h, Oncorhynchus mykiss)	microorganisms -	EC50: >1000mg/L (48h, Daphnia magna)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC 64742-54-7	-	LC50: >5000mg/L (96h, Oncorhynchus mykiss)	-	EC50: >1000mg/L (48h, Daphnia magna)
XYLENE 1330-20-7	_	LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: =780mg/L (96h, Cyprinus carpio) LC50: >780mg/L (96h, Cyprinus carpio)	-	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, Gammarus lacustris)

	1	LC50: 30,26 -		
		40.75mg/L (96h,		
TOLLIENE	5050 400 # /001	Poecilia reticulata)		5050 5 40 0 00 "
TOLUENE	EC50: >433mg/L (96h,	LC50: 15.22 -	-	EC50: 5.46 - 9.83mg/L
108-88-3	Pseudokirchneriella	19.05mg/L (96h,		(48h, Daphnia magna)
	subcapitata)	Pimephales promelas)		EC50: =11.5mg/L (48h,
	EC50: =12.5mg/L (72h,			Daphnia magna)
	Pseudokirchneriella	Pimephales promelas)		
	subcapitata)	LC50: 5.89 - 7.81mg/L		
		(96h, Oncorhynchus		
		mykiss)		
		LC50: 14.1 - 17.16mg/L		
		(96h, Oncorhynchus		
		mykiss)		
		LC50: =5.8mg/L (96h,		
		Oncorhynchus mykiss)		
		LC50: 11.0 - 15.0mg/L		
		(96h, Lepomis		
		macrochirus)		
		LC50: =54mg/L (96h,		
		Oryzias latipes)		
		LC50: =28.2mg/L (96h,		
		Poecilia reticulata)		
		LC50: 50.87 -		
		70.34mg/L (96h,		
		Poecilia reticulata)		
ETHYL BENZENE	EC50: =4.6mg/L (72h,	LC50: 11.0 - 18.0mg/L	_	EC50: 1.8 - 2.4mg/L
100-41-4	Pseudokirchneriella	(96h, Oncorhynchus	_	(48h, Daphnia magna)
100-41-4	subcapitata)	mykiss)		(4011, Daprillia Illaglia)
	EC50: >438mg/L (96h,	LC50: =4.2mg/L (96h,		
	Pseudokirchneriella	Oncorhynchus mykiss)		
		LC50: 7.55 - 11mg/L		
	subcapitata)			
	EC50: 2.6 - 11.3mg/L	(96h, Pimephales		
	(72h,	promelas)		
	Pseudokirchneriella	LC50: =32mg/L (96h,		
	subcapitata)	Lepomis macrochirus)		
	EC50: 1.7 - 7.6mg/L	LC50: 9.1 - 15.6mg/L		
	(96h,	(96h, Pimephales		
	Pseudokirchneriella	promelas)		
	subcapitata)	LC50: =9.6mg/L (96h,		
		Poecilia reticulata)		

Persistence and degradability

No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient	
XYLENE	3.15	
1330-20-7		
TOLUENE	3.93	
108-88-3		
ETHYL BENZENE	3.6	
100-41-4		

Other adverse effects

No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

US EPA Waste Number Waste designations and classifications should be determined by the end user based on the

application for which the product was used.

California waste information This product contains one or more substances that are listed with the State of California as

a hazardous waste.

14. Transport information

DOT Not regulated

TDG Not regulated

MEX Not regulated

ICAO (air) Not regulated

IATA Not regulated

IMDG Not regulated

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Complies.

*Contact supplier for details. One or more substances in this product are either not listed on the US TSCA inventory, listed on the confidential US TSCA inventory or are otherwise exempted from inventory listing requirements

DSL/NDSL Complies. EINECS/ELINCS Complies.

ENCS Does not comply.

IECSC Complies.

KECI Does not comply.

PICCS Complies.

AICS Does not comply.

NZIoC Complies.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing Chemicals Inventory

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %	
ETHYL BENZENE - 100-41-4	0.1	
TOLUENE - 108-88-3	1.0	
XYLENE - 1330-20-7	1.0	
PHOSPHORODITHIOIC ACID - 68442-22-8	1.0	

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE	100 lb	-	-	X
1330-20-7				
TOLUENE	1000 lb	X	Χ	X
108-88-3				
ETHYL BENZENE	1000 lb	X	X	X
100-41-4				

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive

Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
XYLENE 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
TOLUENE 108-88-3	1000 lb 1 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ RQ 1 lb final RQ RQ 0.454 kg final RQ
ETHYL BENZENE 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:.

Chemical name	California Proposition 65		
ETHYL BENZENE - 100-41-4	Carcinogen		
TOLUENE - 108-88-3	Developmental		

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
DISTILLATES (PETROLEUM),	-	X	-
HYDROTREATED LIGHT			
PARAFFINIC			
64742-55-8			
ETHYL BENZENE	X	X	X
100-41-4			
TOLUENE	X	X	X
108-88-3			
XYLENE	X	X	X
1330-20-7			
PHOSPHORODITHIOIC ACID	X	-	X
68442-22-8			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards 2 Flammability 1 Instability 0 Special hazards - HMIS Health hazards 2 Flammability 1 Physical hazards 0 Personal protection X

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

+ Sensitizers

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR) U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA) Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

Organization for Economic Co-operation and Development Environment, Health, and Safety Publications

Organization for Economic Co-operation and Development High Production Volume Chemicals Program Organization for Economic Co-operation and Development Screening Information Data Set World Health Organization

Revision Date 14-Oct-2024

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.