

Safety Data Sheet

Date of issue: 01/12/2026

Revised On 01/12/2026

1 Identification of the substance and manufacturer

Trade name: CHROME ALUMINUM
Other means of identification
Product code: 0000980041
Article category
Recommended use: Paint and coatings application.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178 USA
 phone: 815-895-9101
 www.seymourpaint.com
Emergency telephone number: 1-800-255-3924

Seymour of Sycamore
 3041 Dougall Avenue, Suite 503
 Windsor, ONT N9E 1S3 CANADA
 phone: 800-435-4482
 www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Aerosols 1 H222-H229 Extremely flammable aerosol. Pressurized container: may burst if heated.
 Skin irritation 2 H315 Causes skin irritation.
 Eye irritation 2A H319 Causes serious eye irritation.
 Reproductive toxicity 2 H361 Suspected of damaging fertility or the unborn child.
 Specific target organ toxicity (single exposure) 3 H336 May cause drowsiness or dizziness.
 Specific target organ toxicity (repeated exposure) 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:
GHS Hazard pictograms


GHS02 GHS07 GHS08

Signal word

Danger

Hazard statements

Extremely flammable aerosol. Pressurized container: may burst if heated.
 Causes skin irritation.
 Causes serious eye irritation.
 Suspected of damaging fertility or the unborn child.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Avoid breathing fume/mist/vapors/spray.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 Wear protective gloves.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin: Wash with plenty of water.
 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 Get medical advice/attention if you feel unwell.
 Take off contaminated clothing and wash it before reuse.
 If skin irritation occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Store in a well-ventilated place.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

| | | |
|----------|--------------------|----------|
| 616-38-6 | dimethyl carbonate | 15-25% |
| 108-88-3 | Toluene | ≥20-≤25% |
| 74-98-6 | propane | 15-25% |
| 106-97-8 | n-butane | 10-15% |
| 67-64-1 | Acetone | ≥5-<10% |

(Contd. on page 2)

Safety Data Sheet

Date of issue: 01/12/2026

Revised On 01/12/2026

Trade name: CHROME ALUMINUM

7429-90-5 Aluminum flake

(Contd. of page 1)

1-5%

4 First-aid measures

| | |
|--|--|
| After inhalation: | Supply fresh air; consult doctor in case of complaints. |
| After skin contact: | Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. Wash exposed area with soap and water. |
| After eye contact: | Rinse opened eye for several minutes under running water. Then consult a doctor. |
| After swallowing: | Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting. |
| Most important symptoms and effects: | Dizziness |
| Indication of any immediate medical attention needed: | No further relevant information available. |

5 Fire-fighting measures

| | |
|---|---|
| Extinguishing agents: | CO ₂ , extinguishing powder or water spray. Fight larger fires with water spray. |
| Special hazards: | Can form explosive gas-air mixtures. |
| Protective equipment for firefighters: | A respiratory protective device may be necessary. |

6 Accidental release measures

| | |
|---|---|
| Personal precautions, protective equipment and emergency procedures: | Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol. |
| Methods and material for containment and cleaning up: | Ensure adequate ventilation. Dispose contaminated material as waste according to section 13. |

7 Handling and storage

| | |
|--------------------------------------|---|
| Precautions for safe handling | Use only in well ventilated areas. |
| Storage requirements: | Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up. |

8 Exposure controls/personal protection**Components with limit values that require monitoring at the workplace:****108-88-3 Toluene**

| | |
|-----------|---|
| PEL (USA) | Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift |
| REL (USA) | Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm |
| TLV (USA) | Long-term value: 20 ppm BEI, OTO, A4 |

74-98-6 propane

| | |
|-----------|--|
| PEL (USA) | Long-term value: 1800 mg/m ³ , 1000 ppm |
| REL (USA) | Long-term value: 1800 mg/m ³ , 1000 ppm |
| TLV (USA) | see Appendix F Minimal oxygen content (D, EX) |

106-97-8 n-butane

| | |
|-----------|---|
| REL (USA) | Long-term value: 1900 mg/m ³ , 800 ppm |
| TLV (USA) | Short-term value: 2370 mg/m ³ , 1000 ppm (EX) |

67-64-1 Acetone

| | |
|-----------|---|
| PEL (USA) | Long-term value: 2400 mg/m ³ , 1000 ppm |
| REL (USA) | Long-term value: 590 mg/m ³ , 250 ppm |
| TLV (USA) | Short-term value: 1187 mg/m ³ , 500 ppm Long-term value: 594 mg/m ³ , 250 ppm A4, BEI |

7429-90-5 Aluminum flake

| | |
|-----------|--|
| PEL (USA) | Long-term value: 15*; 5** mg/m ³ *Total dust; ** Respirable fraction |
| REL (USA) | Long-term value: 10* 5** mg/m ³ as Al*Total dust**Respirable/pyro powd./welding f. |
| TLV (USA) | Long-term value: 1* mg/m ³ as Al; *as respirable fraction, A4 |

(Contd. on page 3)

Safety Data Sheet

Date of issue: 01/12/2026

Revised On 01/12/2026

Trade name: CHROME ALUMINUM

(Contd. of page 2)

Ingredients with biological limit values:**108-88-3 Toluene**

BEI (USA) 0.02 mg/L
 Medium: blood
 Time: prior to last shift of workweek
 Parameter: Toluene

0.03 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Toluene

0.3 mg/g creatinine
 Medium: urine
 Time: end of shift
 Parameter: o-Cresol with hydrolysis (background)

67-64-1 Acetone

BEI (USA) 25 mg/L
 Medium: urine
 Time: end of shift
 Parameter: Acetone (nonspecific)

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use. Immediately remove all soiled and contaminated clothing. Wash hands after use. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection: Nitrile gloves.
 The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Physical state: Aerosol
Odor: Aromatic
Odor threshold: Not determined.
Melting point/Melting range: Undetermined.
Boiling point: -44 °C (-47.2 °F)
Flammability: Extremely flammable.
Lower Explosion Limit: 1.7 Vol %
Upper Explosion Limit: 10.9 Vol %
Flash point: -19 °C (-2.2 °F)
Flammability (solid, gas): Extremely flammable.
Decomposition temperature: Not determined.
pH-value: Not determined.
Viscosity: Not determined.
Solubility: Not determined.
Vapor pressure: Not determined.
Relative Density: Between 0.77 and 0.85 (Water equals 1.00)
Vapor density: Not determined.
Particle characteristics: Not applicable.
Appearance: Aerosol.
Ignition temperature: Product is not self-igniting.
Danger of explosion: In use, may form flammable/explosive vapour-air mixture.
Evaporation rate: Not applicable.
Partition coefficient: n-octanol/water: Not determined.

10 Stability and reactivity

Reactivity: Stable at normal temperatures.
Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Chemical stability: Not fully evaluated.
Possibility of hazardous reactions: No dangerous reactions known.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

(Contd. on page 4)

Safety Data Sheet

Date of issue: 01/12/2026

Revised On 01/12/2026

Trade name: CHROME ALUMINUM

(Contd. of page 3)

11 Toxicological information

LD/LC50 values that are relevant for classification:

616-38-6 dimethyl carbonate

Oral LD50 13,000 mg/kg (rat)

Information on toxicological effects: No data available.
Skin effects: Irritant to skin and mucous membranes.
Eye effects: No irritating effect.
Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.
Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.
Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.
Recommendation: Completely empty cans should be recycled.
Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number: UN1950
DOT: UN1950
DOT: Aerosols, flammable
ADR: 1950 Aerosols
Transport hazard class(es):
Class: 2.1 Gases
Marine pollutant: No
Special marking (IATA):
Packaging Group: --
Special precautions for user: Warning: Gases
EMS Number: F-D,S-U
UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

7429-90-5 Aluminum flake

Toxic Substances Control Act**(TSCA):** All ingredients are found on the inventory list of substances.**Canadian Domestic Substances List****(DSL):** All ingredients are listed or exempted.**Consumer Product Safety****Commission (CPSC):** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.**California Proposition 65 chemicals known to cause cancer:**

None of the ingredients in this product are listed.

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 Toluene

EPA:

67-64-1 Acetone

16 Other information**Contact:** Regulatory Affairs