NSI INDUSTRIES LLC
EASY-TWIST™ LARGE JAR LABEL
WWC-B-J_ET-TOWC_Pack-aging_Label
v2
228mm x 107.95mm
06/2025

DO NOT PRINT CYAN
LINE-PLACEMENT ONLY

BLACK	PMS 186 C

The colors on the package are CMYK, but they should match the spot colors shown above.

107.95mm

WARNING
PRECAUTION/ADVERTISSEMENT

Turn off power before installing or removing connectors
Couper l'alimentation avant d'installer ou de retirer les raccords
Apague la alimentación antes de instalar o retirar los conectores

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

INSTRUCTIONS
1. Strip wires 7/8" (22.2 mm)
2. Pre-twisting unnecessary, hold stripped wires together with ends even. Lead stranded wires slightly
3. Align any frayed strands or conductors
4. Push wires into connector and screw on until two twists are visible in wires

SPECIFICATIONS
Listed as a pressure-type wire connector
Temperature Rating: 105°C (221°F) max
Voltage Rating: 600V max building wiring; 1000V max in signs or luminaries
FOR USE WITH COPPER TO COPPER CONDUCTOR

WWC-B-J

EASY-TWIST®
WINGED WIRE CONNECTORS
Blue Winged Connectors
Raccords Ailes Bleu
Conectores Azules Con Clip De Seguridad

125
Qty/Qte/Ctd
14–6 AWG
Solid & Stranded

***For complete listing of wire combinations and voltage ratings, scan QR code or contact Customer Service at 800-321-5847**

SCAN ME

RoHS Compliant
REACH Compliant
UL LISTED WIRE CONNECTORS E155027 8100
SP

NSI
NSI Industries
800.321.5847
nsiindustries.com

Made in Taiwan
Fabrique en Taïwan
Hecho en Taiwán

6 62381 14148 4

228.6mm

WIRE COMBINATIONS*
For UL Listed and CQC Certified
1 or 2 #6
2 #8
2 to 4 #10
3 #12
1 #8 w/3 #10
1 #10 w/3 #12

For CSA and CQC Certified
2 or 3 #8
2 to 4 #10
1 #8 w/1 to 3 #10
1 or 2 #8 w/1 to 3 #12
1 or 2 #8 w/1 to 4 #14
3 #8 w/1 #12 or #14

INSTRUCCIONES
1. Desforre los cables 7/8" (22.2 mm)
2. No es necesario que estén previamente trenzados, sostenga los cables desforrados juntos con las puntas al mismo nivel. Meta un poco los cables trenzados
3. Alinee los cables trenzados o conductores deshilachados
4. Introduzca los cables en el conector y enrosque hasta que se vean dos trenzas en los cables

SPÉCIFICATIONS
Répertorié comme un connecteur de fil de type à pression
Température nominale : 105°C (221°F) max
Tension nominale : 600V max. pour le câblage des bâtiments ; 1000V max. pour les luminaires et les panneaux
À UTILISER AVEC UN CONDUCTEUR CUIVRE À CUIVRE

ESPECIFICACIONES
Certificado como conector de cables tipo a presión
Temperatura nominal: 105 °C (221 °F) máx.
Voltaje nominal: 600 V máximo en el cableado del edificio; 1000 V máximo en artefactos y letreros
PARA USARSE CON CONDUCTORES DE COBRE A COBRE

⚠ **WARNING:** Cancer and reproductive harm
⚠ **ADVERTENCIA:** Cáncer y daño reproductivo
⚠ **ADVERTISSEMENT:** Cancer et troubles de l'appareil reproducteur
www.P65Warnings.ca.gov.

63.5mm