



PRESSURE CLEANERS



Made in Australia SINCE 1982

# HP30-275P

CBM Cold Water Cleaner



### Specifications

- ⇒ 275 bar (3989 psi) pump pressure
- ⇒ 355 bar (5148 psi) EWP pressure (optional)
- ⇒ 30 Litres Per Minute pump volume
- ⇒ GX690 Honda petrol engine
- ⇒ 1450 rpm low speed pump
- ⇒ Electric start
- ⇒ Heavy duty machine

### Standard Equipment

- ⇒ Compact Base Mount (CBM)
- ⇒ Stainless steel heavy duty skid
- ⇒ Interpump brass head pump
- ⇒ Inlet water filter
- ⇒ VRT3 Unloader valve & S284 Safety valve
- ⇒ Stainless steel gun with Dual Lance
- ⇒ Operating and Maintenance manual

Features	Benefits
Interpump with ceramic pistons and brass head	Non-corrosive pump head for longer pump life and lower maintenance costs
Spitwater 'Oz-Tuff' belt drive	Efficient and reliable transfer of power, needs 15% less power to drive, uses less fuel
Inlet water filter	Stops debris from scoring pistons and seals
Pressure gauge	Easily monitor pump performance
Heavy duty stainless steel skid	Corrosion resistance and narrow footprint for longer life and easy fit for trailers and vehicles
Anti-vibration engine mounts	Absorb engine vibrations for better performance and longer machine life

For more information, please visit our website

[spitwater.com.au](http://spitwater.com.au)

**TOUGH + READY**

CREATED BY OTTICO