

330X
HVAC

EXTREME WEATHER

FOIL TAPE



Backing: Aluminum Foil
Adhesive: Acrylic
Liner: Unbleached Natural Kraft Paper
Colors: Aluminum
Available Size: 2.83 in x 50.3 yd (72 mm x 46 m)

Applications

- Sealing insulation and repairing in cooler/refrigeration applications
- Insulation seaming and patching
- Sealing joints and seams in duct work for A/C, heating and ventilation systems
- Emergency household and auto repairs

Features

High Performance Acrylic Adhesive

Aluminum Foil Backing

Wide Width

Low VOC Content

Benefits

- Excellent performance in extreme indoor or outdoor temperatures
- High tack, aggressive bond to surfaces
- Non-solvent for less odor
- Conformable to fit corners and joints
- Mold and mildew resistant
- UV and moisture resistant
- 2.83" width allows for greater surface coverage and less overlaps
- Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	3.5 mils	89 µm	ASTM D-1000
Adhesion to Steel	55 oz/in	6.02 N/cm	ASTM-D3330
Tensile Strength	14 lb/in	24.53 N/cm	ASTM D-1000
Operating Temperature	-35 to 260 °F	-37 to 126 °C	
Application Temperature	-5 to 150 °F	-20 to 65 °C	
Smoke Developed	25		
Flame Spread	50		
VOC Content	< 30 g/L		

Recommended Storage Conditions: 60 - 80 °F at 40-60% RH

Standard Shelf Life (at 25 °C): 36 months from date of manufacture

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.