



## RENEW Rubberized Sealant

This is a multi-purpose sealant that seals small cracks and does not lose flexibility. Resists water, protects against UV sunlight, and will not crack in cold temperatures. The thermoplastic elastomer base makes it an ideal product for sealing leaks around roofs, windows and doors. It can also be topcoated with oil or latex paints.

### Suggested Uses:

Skylights  
 Windows  
 Flashings  
 Air vents  
 Driveway and sidewalk cracks  
 Gutters  
 Shingles

### Packaging:

Cans per case	12
Shipping weight per case	19 lbs.
Container	20 fluid ounce can
Label weight	15 ounces (425 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

### Properties:

Coverage	Up to 18 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4F
Specific Gravity	0.80
Solids Content	13%
MIR value	0.86, cannot exceed 0.95
HAPs content	~10%
Storage Temperature	40-100F
Application Temperature	50-90F
Heat Resistance	250F
Resin System	Synthetic Rubber
Shelf life	Guaranteed for 2 years
Food contact rating	No

### Dry Time\*:

To touch	10 minutes
To topcoat	30 minutes

\*At 72F, 50% humidity,  
 1.5 mil thickness

\*\*Curing/Recoat time is extended with  
 multiple coats and excessively thick coats\*\*

**Gloss\*:** Flat, <15

\*as measured on a 60 degree gloss meter

### Available Colors:

Part #	Description	UPC Code
#20-148	Black	043281005036
#20-149	Clear	043281005043

### Additional Information:

This product leaves a slightly bubbly film. When covering a broad area it is recommended that two coats be applied to ensure a non-porous final coating. Allow first coat to dry to touch (about 8-10 minutes) before applying the second and final coat.

5-24-2023