

Page: 1/10

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 02, 2019

1 Identification

· Product identifier

• Trade name: <u>DUROSEAL Fiber Reinforced Duct Sealer (EDS-RF1, EDS-RFC)</u>
DUROSEAL White Fiber Reinforced Duct Sealer (WEDS-RF1, WEDS-RFC)

· Product code: #5230 (EDS-RF1), #5232 (EDS-RFC), #5234 (WEDS-RF1), #5235 (WEDS-RFC)

· Recommended use and restriction on use

· Recommended use: Sealant

· Restrictions on use: For professional use only.

Details of the supplier of the Safety Data Sheet

· Manufacturer/Supplier:

DURO DYNE CORPORATION

81 Spence Street Bay Shore, NY 11706 800-899-3876

· Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America)

+1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer. STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:





GHS07 GHS08

· Signal word: Warning

· Hazard statements:

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

· Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing mist, vapors, or spray. Wash thoroughly after handling.

(Cont'd. on page 2)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 02, 2019

Trade name: DUROSEAL Fiber Reinforced Duct Sealer (EDS-RF1, EDS-RFC)
DUROSEAL White Fiber Reinforced Duct Sealer (WEDS-RF1, WEDS-RFC)

(Cont'd. of page 1) P271 Use only outdoors or in a well-ventilated area. P272 Contaminated work clothing must not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection. P302+P352 If on skin: Wash with plenty of soap and water. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. P308+P313 Call a poison center/doctor if you feel unwell. P312 P333+P313 If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. P337+P313 P362+P364 Take off contaminated clothing and wash it before reuse. Store in a well-ventilated place. Keep container tightly closed. P403+P233 P405 Store locked up. Dispose of contents/container in accordance with local/regional/national/international P501 regulations.

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Componen	ts:	
1317-65-3	Limestone	40-50%
140-88-5	ethyl acrylate Flam. Liq. 2, H225 Carc. 2, H351 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	5-10%
14808-60-7	Quartz	<1%
13463-67-7	Titanium dioxide	<1%

Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

- Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly. If skin irritation or rash occurs: Get medical advice/attention.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

(Cont'd. on page 3)



Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 02, 2019

Trade name: DUROSEAL Fiber Reinforced Duct Sealer (EDS-RF1, EDS-RFC) **DUROSEAL White Fiber Reinforced Duct Sealer (WEDS-RF1, WEDS-RFC)**

(Cont'd. of page 2)

Page: 3/10

Do not induce vomiting; immediately call for medical help.

Most important symptoms and effects, both acute and delayed:

Irritating to eyes, respiratory system and skin.

Coughing

Allergic reactions

Nausea in case of ingestion.

May cause gastro-intestinal irritation if ingested.

- · **Danger:** Suspected of causing cancer.
- Indication of any immediate medical attention and special treatment needed:

Contains ethyl acrylate. May produce an allergic reaction.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- For safety reasons unsuitable extinguishing agents: No relevant information available.
- Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters
- · Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required.

Ensure adequate ventilation.

- Environmental precautions Avoid release to the environment.
- · Methods and material for containment and cleaning up

Towel or mop up material and collect in a suitable container.

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling
- · Precautions for safe handling:

Handle with care.

Keep out of reach of children.

• Conditions for safe storage, including any incompatibilities

(Cont'd. on page 4)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 02, 2019

Trade name: DUROSEAL Fiber Reinforced Duct Sealer (EDS-RF1, EDS-RFC)
DUROSEAL White Fiber Reinforced Duct Sealer (WEDS-RF1, WEDS-RFC)

(Cont'd. of page 3)

Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Store in cool, dry conditions in well sealed receptacles.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

- · Further information about storage conditions: Storage Temperatures: 35-110 °F / 2-43 °C.
- · Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parar	
-	vith limit values that require monitoring at the workplace:
1317-65-3 Lime	estone
PEL (USA)	Long-term value: 15* 5** mg/m³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m³ *total dust **respirable fraction
TLV (USA)	TLV withdrawn
140-88-5 ethyl a	acrylate
PEL (USA)	Long-term value: 100 mg/m³, 25 ppm Skin
REL (USA)	See Pocket Guide App. A
TLV (USA)	Short-term value: 61 mg/m³, 15 ppm Long-term value: 20 mg/m³, 5 ppm
EL (Canada)	Short-term value: 15 ppm Long-term value: 5 ppm IARC 2B; S(D)
EV (Canada)	Short-term value: 15 ppm Long-term value: 5 ppm Skin
LMPE (Mexico)	Short-term value: 15 ppm Long-term value: 5 ppm A4
14808-60-7 Qua	artz
PEL (USA)	Long-term value: 0.05* mg/m³ *resp. dust; 30mg/m3/%SiO2+2
REL (USA)	Long-term value: 0.05* mg/m³ *respirable dust; See Pocket Guide App. A
TLV (USA)	Long-term value: 0.025* mg/m³ *as respirable fraction
EL (Canada)	Long-term value: 0.025 mg/m³ ACGIH A2; IARC 1
EV (Canada)	Long-term value: 0.10* mg/m³
	(Cont'd. on page



Page: 5/10

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 02, 2019

Trade name: DUROSEAL Fiber Reinforced Duct Sealer (EDS-RF1, EDS-RFC)
DUROSEAL White Fiber Reinforced Duct Sealer (WEDS-RF1, WEDS-RFC)

		(Cont'd. of page 4)
	*respirable fraction	
LMPE (Mexico)	Long-term value: 0.025* mg/m³	
	A2, *fracción respirable	
13463-67-7 Tita	nium dioxide	
PEL (USA)	Long-term value: 15* mg/m³	
	*total dust	
REL (USA)	See Pocket Guide App. A	
TLV (USA)	Long-term value: 10 mg/m³	
EL (Canada)	Long-term value: 10* 3** mg/m³	
	*total dust;**respirable fraction; IARC 2B	
EV (Canada)	Long-term value: 10 mg/m³	
	total dust	
LMPE (Mexico)	Long-term value: 10 mg/m³	
	A4	

- Exposure controls
- · General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid breathing vapors.

Avoid contact with the eyes and skin.

- Engineering controls: Provide adequate ventilation.
- · Breathing equipment:

Not required under normal conditions of use.

Use suitable respiratory protective device in case of insufficient ventilation.

Use respiratory protection when grinding or cutting material.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- · Material of gloves
- Nitrile rubber, NBR

Neoprene gloves

Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- · Body protection: Protective work clothing
- Limitation and supervision of exposure into the environment

No relevant information available.

· Risk management measures No relevant information available.





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 02, 2019

Trade name: DUROSEAL Fiber Reinforced Duct Sealer (EDS-RF1, EDS-RFC)

DUROSEAL White Fiber Reinforced Duct Sealer (WEDS-RF1, WEDS-RFC)

(Cont'd. of page 5)

Physical and chemical prope	erties
Information on basic physical a	
Appearance:	
Form:	Liquid
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Melting point/Melting range:	Not determined.
· Boiling point/Boiling range:	Not determined.
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive a vapor mixtures are possible.
· Explosion limits	
Lower:	Not determined.
Upper:	Not determined.
· Oxidizing properties:	Non-oxidizing.
· Vapor pressure:	Not determined.
· Density:	
Relative density:	Not determined.
Vapor density:	Not determined.
Evaporation rate:	Not determined.
· Solubility in / Miscibility with	
Water:	Not determined.
· Partition coefficient (n-octanol/wat	ter): Not determined.
· Viscosity	
Dynamic:	Not determined.
Kinematic:	Not determined.
· VOC content:	0
Other information	No relevant information available.

10 Stability and reactivity

- · **Reactivity:** No relevant information available.
- · Chemical stability:
- · Thermal decomposition / conditions to be avoided:

No decomposition if used and stored according to specifications.

(Cont'd. on page 7)



Page: 7/10

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 02, 2019

Trade name: DUROSEAL Fiber Reinforced Duct Sealer (EDS-RF1, EDS-RFC) **DUROSEAL White Fiber Reinforced Duct Sealer (WEDS-RF1, WEDS-RFC)**

(Cont'd. of page 6)

- · Possibility of hazardous reactions Reacts with strong oxidizing agents.
- · Conditions to avoid Excessive heat.
- · Incompatible materials Oxidizers
- · Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

11 Toxicological information

- Information on toxicological effects
- · Acute toxicity: Based on available data, the classification criteria are not met.

· LD/LC50	· LD/LC50 values that are relevant for classification:				
140-88-5	140-88-5 ethyl acrylate				
Oral	LD50	800 mg/kg (rat)			
Dermal	LD50	1834 mg/kg (rabbit)			
Inhalative	LC50/4h	2180 mg/l (rat)			

· Primary irritant effect:

14808-60-7 Quartz

- On the skin: Irritant to skin and mucous membranes.
- · On the eye: Causes eye irritation.
- · **Sensitization**: Contains ethyl acrylate. May produce an allergic reaction.

· IARC (International Agency for Research on Cancer):		
140-88-5	ethyl acrylate	2B
14808-60-7	Quartz	1
13463-67-7	Titanium dioxide	2B

NTP (National Toxicology Program):

OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed. · Probable route(s) of exposure:

Ingestion.

Eye contact.

Skin contact.

- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Suspected of causing cancer.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- · **STOT-single exposure**: May cause respiratory irritation.
- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · Aspiration hazard: Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity No relevant information available.

(Cont'd. on page 8)

K





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 02, 2019

Trade name: DUROSEAL Fiber Reinforced Duct Sealer (EDS-RF1, EDS-RFC)
DUROSEAL White Fiber Reinforced Duct Sealer (WEDS-RF1, WEDS-RFC)

(Cont'd. of page 7)

- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- · Mobility in soil: No relevant information available.
- Additional ecological information
- · General notes: Avoid release to the environment.
- Other adverse effects No relevant information available.

13 Disposal considerations

- Waste treatment methods
- · Recommendation:

Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

- Uncleaned packagings
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number · DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.
UN proper shipping name DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.
· Transport hazard class(es)	
· DOT, ADR/RID/ADN, IMDG, IATA · Class	Not regulated.
Packing group DOT, ADR/RID/ADN, IMDG, IATA	Not regulated.
· Environmental hazards · Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.

15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

(Cont'd. on page 9)



Page: 9/10

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: July 02, 2019

Trade name: DUROSEAL Fiber Reinforced Duct Sealer (EDS-RF1, EDS-RFC)
DUROSEAL White Fiber Reinforced Duct Sealer (WEDS-RF1, WEDS-RFC)

(Cont'd. of page 8) · United States (USA) · Section 302 (extremely hazardous substances): None of the ingredients are listed. · Section 355 (extremely hazardous substances): None of the ingredients are listed. Section 313 (Specific toxic chemical listings): 140-88-5 ethyl acrylate TSCA (Toxic Substances Control Act) All ingredients are listed or exempt. · Proposition 65 (California) · Chemicals known to cause cancer: 140-88-5 ethyl acrylate 14808-60-7 Quartz 13463-67-7 Titanium dioxide Chemicals known to cause developmental toxicity for females: None of the ingredients are listed. · Chemicals known to cause developmental toxicity for males: None of the ingredients are listed. Chemicals known to cause developmental toxicity: None of the ingredients are listed. EPA (Environmental Protection Agency): None of the ingredients are listed. · IARC (International Agency for Research on Cancer): 140-88-5 ethyl acrylate 2B 14808-60-7 Quartz 13463-67-7 Titanium dioxide 2B Canadian Domestic Substances List (DSL): All ingredients are listed or exempt.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

(Cont'd. on page 10)



Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Page: 10/10

Revision: July 02, 2019

Trade name: DUROSEAL Fiber Reinforced Duct Sealer (EDS-RF1, EDS-RFC) **DUROSEAL White Fiber Reinforced Duct Sealer (WEDS-RF1, WEDS-RFC)**

(Cont'd. of page 9)

Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/ overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com