

## Safety Data Sheet

Printing date 01/03/2024

Revised On 01/03/2024

## 1 Identification of the substance and manufacturer

**Trade name:** SAFETY RED (MRO) GALLONS  
**Product code:** 0000011423  
**Recommended use:** Paint and coatings application.  
**Uses advised against:** Any that differs from the recommended use.  
**Manufacturer/Supplier:** Seymour of Sycamore  
 917 Crosby Avenue  
 Sycamore, IL 60178 USA  
 phone: 815-895-9101  
 www.seymourpaint.com  
**Emergency telephone number:** 1-800-255-3924

Seymour of Sycamore  
 3041 Dougall Avenue, Suite 503  
 Windsor, ONT N9E 1S3 CANADA  
 phone: 800-435-4482  
 www.seymourpaint.com

## 2 Hazard(s) identification

## Classification of the substance or mixture

Flammable Liquids 2 H225 Highly flammable liquid and vapor.  
 Eye Irritation 2A H319 Causes serious eye irritation.  
 Carcinogenicity 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.  
 Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information:  
GHS Hazard pictograms

GHS02 GHS07 GHS08

Signal word  
Hazard statements

Danger  
 Highly flammable liquid and vapor.  
 Causes serious eye irritation.  
 Suspected of causing cancer. Route of exposure: Inhalation.  
 May cause damage to organs through prolonged or repeated exposure.  
 Obtain special instructions before use.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wash thoroughly after handling.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical advice/attention.  
 In case of fire: Use CO2, powder or water spray to extinguish.  
 Store in a well-ventilated place.  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

## Chemical characterization: Mixtures

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

## Dangerous components:

|            |                             |        |
|------------|-----------------------------|--------|
| 64742-47-8 | Mineral Spirits             | 15-25% |
| 7727-43-7  | barium sulfate              | 15-25% |
| 108-65-6   | PM acetate                  | 1-5%   |
| 64742-48-9 | Naphtha, hydrotreated heavy | 1-5%   |
| 1330-20-7  | xylene (mix)                | 1-5%   |
| 111-76-2   | Glycol Ether EB             | 0.2-1% |

## 4 First-aid measures

**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.  
**After eye contact:** Rinse opened eye for several minutes under running water.  
**After swallowing:** Rinse out mouth and then drink plenty of water.  
 Rinse mouth with water. Do not induce vomiting.  
**Most important symptoms and effects:** No further relevant information available.  
**Indication of any immediate medical attention needed:** No further relevant information available.

## 5 Fire-fighting measures

**Special hazards:** No further relevant information available.  
**Protective equipment for firefighters:** No special measures required.

(Contd. on page 2)

## Safety Data Sheet

Printing date 01/03/2024

Revised On 01/03/2024

Trade name: SAFETY RED (MRO) GALLONS

(Contd. of page 1)

## 6 Accidental release measures

## Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

## Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

## 7 Handling and storage

## Precautions for safe handling

Use only in well ventilated areas.

## Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

## 8 Exposure controls/personal protection

## Components with limit values that require monitoring at the workplace:

## 7727-43-7 barium sulfate

|           |   |
|-----------|---|
| PEL (USA) | Long-term value: 15* 5** mg/m <sup>3</sup><br>*total dust **respirable fraction |
|-----------|---|

|           |   |
|-----------|---|
| REL (USA) | Long-term value: 10* 5** mg/m <sup>3</sup><br>*total dust **respirable fraction |
|-----------|---|

|           |   |
|-----------|---|
| TLV (USA) | Long-term value: 5* mg/m <sup>3</sup><br>*inhalable fraction; E |
|-----------|---|

## 108-65-6 PM acetate

|            |                         |
|------------|-------------------------|
| WEEL (USA) | Long-term value: 50 ppm |
|------------|-------------------------|

## 1330-20-7 xylene (mix)

|           |  |
|-----------|--|
| PEL (USA) | Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |
|-----------|--|

|           |   |
|-----------|---|
| REL (USA) | Short-term value: 655 mg/m <sup>3</sup> , 150 ppm<br>Long-term value: 435 mg/m <sup>3</sup> , 100 ppm |
|-----------|---|

|           |                                    |
|-----------|------------------------------------|
| TLV (USA) | Long-term value: 20 ppm<br>BEI, A4 |
|-----------|------------------------------------|

## 111-76-2 Glycol Ether EB

|           |   |
|-----------|---|
| PEL (USA) | Long-term value: 240 mg/m <sup>3</sup> , 50 ppm<br>Skin |
|-----------|---|

|           |   |
|-----------|---|
| REL (USA) | Long-term value: 24 mg/m <sup>3</sup> , 5 ppm<br>Skin |
|-----------|---|

|           |                                    |
|-----------|------------------------------------|
| TLV (USA) | Long-term value: 20 ppm<br>BEI, A3 |
|-----------|------------------------------------|

## Ingredients with biological limit values:

## 1330-20-7 xylene (mix)

|           |  |
|-----------|--|
| BEI (USA) | 1.5 g/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: Methylhippuric acids |
|-----------|--|

## 111-76-2 Glycol Ether EB

|           |  |
|-----------|--|
| BEI (USA) | 200 mg/g creatinine<br>Medium: urine<br>Time: end of shift<br>Parameter: Butoxyacetic acid (BAA) (with hydrolysis) |
|-----------|--|

## Hygienic protection:

Keep away from foodstuffs and animal feed. Wash hands after use.  
Wash hands after use.

Do not eat or drink while working.

## Breathing equipment:

Not required.

## Hand protection:

Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

## Eye protection:

Tightly sealed goggles

## 9 Physical and chemical properties

|             |         |
|-------------|---------|
| Appearance: | Liquid. |
|-------------|---------|

|                 |                 |
|-----------------|-----------------|
| Odor threshold: | Not determined. |
|-----------------|-----------------|

|           |                 |
|-----------|-----------------|
| pH-value: | Not determined. |
|-----------|-----------------|

|                             |               |
|-----------------------------|---------------|
| Melting point/Melting range | Undetermined. |
|-----------------------------|---------------|

|                |                   |
|----------------|-------------------|
| Boiling point: | 146 °C (294.8 °F) |
|----------------|-------------------|

|              |                  |
|--------------|------------------|
| Flash point: | -19 °C (-2.2 °F) |
|--------------|------------------|

|                            |                   |
|----------------------------|-------------------|
| Flammability (solid, gas): | Highly flammable. |
|----------------------------|-------------------|

(Contd. on page 3)

## Safety Data Sheet

Printing date 01/03/2024

Revised On 01/03/2024

Trade name: SAFETY RED (MRO) GALLONS

(Contd. of page 2)

|  |  |
|--|--|
| <b>Decomposition temperature:</b>              | Not determined.  |
| <b>Auto igniting:</b>                          | Product is not self-igniting.                            |
| <b>Danger of explosion:</b>                    | In use, may form flammable/explosive vapour-air mixture. |
| <b>Lower Explosion Limit:</b>                  | 0.5 Vol %  |
| <b>Upper Explosion Limit:</b>                  | 6.5 Vol %  |
| <b>Vapor pressure:</b>                         | Not determined.  |
| <b>Vapor density</b>                           | Not determined.  |
| <b>Evaporation rate</b>                        | Not determined.  |
| <b>Partition coefficient: n-octonal/water:</b> | Not determined.  |
| <b>Solubility:</b>                             | Not determined.  |
| <b>Viscosity:</b>                              | Not determined.  |
| <b>Water:</b>                                  | 0.0 %  |

**10 Stability and reactivity**

|  |   |
|--|---|
| <b>Conditions to avoid:</b>                | No decomposition if used according to specifications. |
| <b>Possibility of hazardous reactions:</b> | No dangerous reactions known.                         |
| <b>Incompatible materials:</b>             | No further relevant information available.            |
| <b>Hazardous decomposition:</b>            | No dangerous decomposition products known.            |

**11 Toxicological information****LD/LC50 values that are relevant for classification:****108-65-6 PM acetate**

|            |          |                   |
|------------|----------|-------------------|
| Oral       | LD50     | 8,500 mg/kg (rat) |
| Inhalative | LC50/4 h | 35.7 mg/l (rat)   |

**64742-48-9 Naphtha, hydrotreated heavy**

|        |      |                    |
|--------|------|--------------------|
| Oral   | LD50 | >5,000 mg/kg (rat) |
| Dermal | LD50 | >3,000 mg/kg (rab) |

**1330-20-7 xylene (mix)**

|            |          |                   |
|------------|----------|-------------------|
| Oral       | LD50     | 8,700 mg/kg (rat) |
| Dermal     | LD50     | 2,000 mg/kg (rbt) |
| Inhalative | LC50/4 h | 6,350 mg/l (rat)  |

**111-76-2 Glycol Ether EB**

|            |          |                   |
|------------|----------|-------------------|
| Oral       | LD50     | 1,200 mg/kg (ATE) |
|            |          | 1,480 mg/kg (rat) |
| Dermal     | LD50     | 400 mg/kg (rab)   |
| Inhalative | LC50/4 h | 3 mg/l (ATE)      |

|  |                               |
|--|-------------------------------|
| <b>Information on toxicological effects:</b> | No data available.            |
| <b>Skin effects:</b>                         | No irritant effect.           |
| <b>Eye effects:</b>                          | No irritating effect.         |
| <b>Sensitization:</b>                        | No sensitizing effects known. |

**12 Ecological information**

|                                       |  |
|---------------------------------------|--|
| <b>Aquatic toxicity:</b>              | Hazardous for water, do not empty into drains.   |
| <b>Persistence and degradability:</b> | The product is degradable after prolonged exposure to natural weathering processes.  |
| <b>Other information:</b>             | This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents. |
| <b>Bioaccumulative potential:</b>     | No further relevant information available.   |
| <b>Mobility in soil:</b>              | No further relevant information available.   |
| <b>Other adverse effects:</b>         | No further relevant information available.   |

**13 Disposal considerations**

|   |  |
|---|--|
| Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. |  |
| <b>Recommendation:</b>  | Completely empty cans should be recycled.  |
| <b>Recommended cleansing agent:</b>   | Water, if necessary with cleansing agents. |

**14 Transport information**

|                                    |                     |
|------------------------------------|---------------------|
| <b>UN-Number</b>                   | 1263 Paint          |
| <b>ADR</b>                         |                     |
| <b>Transport hazard class(es):</b> |                     |
| <b>Class</b>                       | 3 Flammable liquids |
| <b>Marine pollutant:</b>           | No                  |

(Contd. on page 4)

## Safety Data Sheet

Printing date 01/03/2024

Revised On 01/03/2024

Trade name: SAFETY RED (MRO) GALLONS

**Special precautions for user:** Warning: Flammable liquids  
**EMS Number:** F-E, S-E  
**Packaging Group:** II  
**UN "Model Regulation":** UN1263, Paint, 3, II

(Contd. of page 3)

## 15 Regulatory information

**SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

7727-43-7 barium sulfate

1330-20-7 xylene (mix)

**Toxic Substances Control Act (TSCA):**

All hazardous ingredients are found on the inventory list of substances.

**Canadian Domestic Substances List (DSL):**

All ingredients are listed or exempted.

**Consumer Product Safety****Comission (CPSC):**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

**California Proposition 65 chemicals known to cause cancer:**

13463-67-7 titanium dioxide

100-41-4 ethyl benzene

**Prop 65 chemicals known to cause birth defects or reproductive harm:**

None of the ingredients is listed.

**EPA:**

7727-43-7 barium sulfate

D, CBD(inh), NL(oral)

1330-20-7 xylene (mix)

I

## 16 Other information

**Contact:** Regulatory Affairs