



## MRO INDUSTRIAL PRIMERS

#620-1407 Red Oxide, #620-1431 Light Gray

A rust proof industrial primer formulated specifically for use with MRO Industrial Protective Coatings. This high solids paint gives twice the coverage of conventional aerosol primers. Heat resistant, VOC compliant, and fast drying.

### Suggested Uses:

Rusted metal  
 Restore equipment  
 Refinish machinery  
 Protect metal structures

### Packaging:

UPC Code 620-1407	043281006989
620-1431	043281006798
Cans per case	6
Shipping weight per case	9 lbs.
Container	20 fluid ounce can
Label weight	17 ounces (482 grams)
Shipping Classification	limited quantity, UN 1950
Hazard Class	2.1

### Properties:

Coverage	Up to 18 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4 F
Specific Gravity	0.81
Solids Content	24%
MIR value	0.69, cannot exceed 0.70
HAPs content	11%
Storage Temperature	40-100F
Application Temperature	50-90F
Heat Resistance	250F
Resin System	Phenolic
Shelf life	Guaranteed for 2 years
Food contact rating	No

### Dry Time\*:

To touch 5 minutes  
 To recoat 20 minutes

\*At 72F, 50% humidity,  
 1.5 mil thickness

\*\*Curing/Recoat time is extended with  
 multiple coats and excessively thick coats\*\*

### Gloss\*:

Flat, <15  
 \*as measured on a 60 degree gloss meter

12-2-2021