

FEATURES:

1. Compact, versatile and durable
2. 90 °C and 600V.
3. High-impact bases
4. One-piece connectors .
5. No assembly on job site.
6. Default SCCR Rating 10,000 Amps.
7. Connector Blok™ covers are available in 3 sizes and fits all styles and configurations.

SPECIFICATIONS:

1. CSA
2. UL Recognize.

POLARIS®

PROGRAM:	SOLIDWORKS
UPDATED:	08/2023
SALES REV:	B
SIZE:	C

AS, AM, AL Series: Multiple Primary, Multiple Secondary

CAT. NO.	FIG. NO.	DRAWING	CONFIGURATION		AMPS PER POLE	LENGTH (L) (IN.)	HEIGHT (W) (IN.)	WIDTH (H) (IN.)	STD. PKG. QTY.	STD. CTN. QTY.
			PRIMARY LINE SIDE	DRAWING						
AS-K2-H6	1		2/0-14 AWG		350	2.900	2.714	1.040	1	3
AM-K2-H6	1		2/0-14 AWG		350	4.000	2.620	1.710	1	3
AM-K2-H12	1		2/0-14 AWG		350	4.000	2.620	1.710	1	3
AM-K2-I6	1		2/0-14 AWG		350	4.000	2.620	1.710	1	3
AL-P2-H12	1		350 MCM-6 AWG		620	5.500	3.250	2.900	1	3
AL-P2-K6	1		350 MCM-6 AWG		620	5.500	3.250	2.900	1	3
AL-R2-H12	1		500 MCM-4 AWG		760	5.500	3.250	2.900	1	3
AL-R2-K6	1		500 MCM-4 AWG		760	5.500	3.250	2.900	1	3
AL-R2-M4	1		500 MCM-4 AWG		760	5.500	3.250	2.900	1	3

