



# SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:  
US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS  
which includes the amended Hazardous Products Act (HPA) and the Hazardous Products  
Regulation (HPR)

Revision Date 19-May-2026

Version 2

## 1. Identification

### Product identifier

Product Name LIQUID METAL FILLER 3.5 FL.OZ

### Other means of identification

Product Code 25909

UN number or ID number UN1133

Synonyms None

### Recommended use of the chemical and restrictions on use

Recommended Use Adhesive Filler.

Restrictions on use No information available

### Details of the supplier of the safety data sheet

#### Manufacturer Address

ITW Permatex, Inc.  
6875 Parkland Blvd.  
Solon, Ohio 44139 USA  
Telephone: 1-87-Permatex  
(866) 732-9502

#### May Also Be Distributed by:

ITW Permatex Canada  
101-2360 Bristol Circle  
Oakville, ON Canada L6H 6M5  
Telephone: (800) 924-6994

E-mail address mail@permatex.com

### Emergency telephone number

Company Phone Number 866-732-9502

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924  
International Emergency:  
00+1+ 813-248-0585  
Contract Number: MIS0003453

24-hour emergency phone number No information available

## 2. Hazard(s) identification

### Classification

Flammable liquids	Category 2
Acute toxicity - Oral	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Serious eye damage/eye irritation	Category 2A

Emergency Response Guide Number 128

Carcinogenicity	Category 1A
-----------------	-------------

**Label elements**

Contains BARIUM SULFATE; SILICA, QUARTZ; TITANIUM DIOXIDE; CARBON BLACK

**Danger****Hazard statements**

Highly flammable liquid and vapor.  
Harmful if swallowed.  
Harmful if inhaled.  
Causes serious eye irritation.  
May cause cancer.

**Precautionary Statements - Prevention**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Wear protective gloves, protective clothing, eye protection and face protection.  
Wash face, hands and any exposed skin thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Avoid breathing dust, fume, gas, mist, vapors and spray.  
Use only outdoors or in a well-ventilated area.  
Ground and bond container and receiving equipment.  
Use non-sparking tools.  
Take action to prevent static discharges.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Keep container tightly closed.  
Use explosion-proof electrical, ventilating and lighting equipment.

**Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention.

**Eyes**

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If eye irritation persists: Get medical advice and attention.

**Skin**

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

**Inhalation**

IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
Call a POISON CENTER or doctor if you feel unwell.

**Ingestion**

IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.  
Rinse mouth.

**Fire**

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

**Precautionary Statements - Storage**

Store locked up.  
Store in a well-ventilated place. Keep cool.

**Precautionary Statements - Disposal**

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

**Unknown acute toxicity**

9.8542 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.  
56.0242 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.  
76.0142 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).  
76.0142 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

16.8442 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

#### Other Information

No information available.

### **3. Composition/information on ingredients**

#### Substance

Not applicable.

#### Mixture

The product contains no substances which at their given concentration, are considered to be hazardous to health.

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
BARIUM SULFATE	7727-43-7	30-60%	-	-
KAOLIN	1332-58-7	10-30%	-	-
ACETONE	67-64-1	10-30%	-	-
ISOBUTYL ACETATE	110-19-0	3-7%	-	-
CALCIUM CARBONATE	1317-65-3	0.5-1.5%	-	-
TITANIUM DIOXIDE	13463-67-7	0.1-1%	-	-
SILICA, QUARTZ	14808-60-7	0.1-1%	-	-
CARBON BLACK	1333-86-4	0.1-1%	-	-

### **4. First-aid measures**

#### Description of first aid measures

##### **General advice**

Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.

##### **Inhalation**

Remove to fresh air. If symptoms persist, call a physician. If breathing has stopped, give artificial respiration. Get medical attention immediately.

##### **Eye contact**

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

##### **Skin contact**

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

##### **Ingestion**

Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Get medical attention.

##### **Self-protection of the first aider**

Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists.

#### Most important symptoms and effects, both acute and delayed

##### **Symptoms**

May cause redness and tearing of the eyes. Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.

##### **Effects of Exposure**

May cause cancer.

#### Indication of any immediate medical attention and special treatment needed

**Note to physicians** Treat symptomatically.

## 5. Fire-fighting measures

<b>Suitable Extinguishing Media</b>	Dry chemical. Carbon dioxide (CO <sub>2</sub> ). Water spray. Alcohol resistant foam.
<b>Small Fire</b>	In case of fire, use water spray, foam, dry chemical, or CO <sub>2</sub> .
<b>Large Fire</b>	In case of fire, use water spray, foam, dry chemical, or CO <sub>2</sub> .
<b>Unsuitable extinguishing media</b>	Do not scatter spilled material with high pressure water streams.
<b>Specific hazards arising from the chemical</b>	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
<b>Hazardous combustion products</b>	No information available.
<b>Explosion data</b>	
<b>Sensitivity to mechanical impact</b>	None.
<b>Sensitivity to static discharge</b>	Yes.
<b>Special protective equipment and precautions for fire-fighters</b>	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protective equipment.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

<b>Personal precautions</b>	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Avoid breathing vapors or mists.
<b>Other information</b>	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

### Methods and material for containment and cleaning up

<b>Methods for containment</b>	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
<b>Methods for cleaning up</b>	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.
<b>Prevention of secondary hazards</b>	Clean contaminated objects and areas thoroughly observing environmental regulations.

## 7. Handling and storage

### Precautions for safe handling

<b>Advice on safe handling</b>	Use personal protective equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof
--------------------------------	---

equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment.

### Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Keep out of the reach of children.

## **8. Exposure controls/personal protection**

### Control Parameters

#### **Exposure Limits**

This product, as supplied, does not contain any hazardous materials with occupational exposure limits established by the region specific regulatory bodies

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
BARIUM SULFATE 7727-43-7	TWA: 5 mg/m <sup>3</sup> inhalable particulate matter particulate matter containing no Asbestos and <1% Crystalline silica	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> ; total dust TWA: 5 mg/m <sup>3</sup> ; respirable dust
KAOLIN 1332-58-7	TWA: 2 mg/m <sup>3</sup> respirable particulate matter particulate matter containing no Asbestos and <1% Crystalline silica	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> ; total dust TWA: 5 mg/m <sup>3</sup> ; respirable dust
ACETONE 67-64-1	TWA: 250 ppm STEL: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m <sup>3</sup> (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m <sup>3</sup> (vacated) STEL: 2400 mg/m <sup>3</sup> The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors. (vacated) STEL: 1000 ppm	TWA: 250 ppm; TWA: 590 mg/m <sup>3</sup> ; IDLH: 2500 ppm
ISOBUTYL ACETATE 110-19-0	TWA: 50 ppm STEL: 150 ppm	TWA: 150 ppm TWA: 700 mg/m <sup>3</sup> (vacated) TWA: 150 ppm (vacated) TWA: 700 mg/m <sup>3</sup>	TWA: 150 ppm; TWA: 700 mg/m <sup>3</sup> ; IDLH: 1300 ppm
CALCIUM CARBONATE 1317-65-3	-	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction	TWA: 10 mg/m <sup>3</sup> ; total dust TWA: 5 mg/m <sup>3</sup> ; respirable dust
TITANIUM DIOXIDE 13463-67-7	TWA: 0.2 mg/m <sup>3</sup> nanoscale respirable particulate matter TWA: 2.5 mg/m <sup>3</sup> finescale respirable particulate matter	TWA: 15 mg/m <sup>3</sup> total dust (vacated) TWA: 10 mg/m <sup>3</sup> total dust	TWA: 2.4 mg/m <sup>3</sup> ; CIB 63 fine TWA: 0.3 mg/m <sup>3</sup> ; CIB 63 ultrafine, including engineered nanoscale IDLH: 5000 mg/m <sup>3</sup>
SILICA, QUARTZ 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> respirable particulate matter	TWA: 50 µg/m <sup>3</sup> TWA: 50 µg/m <sup>3</sup> excludes	TWA: 0.05 mg/m <sup>3</sup> ; respirable dust

		construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 0.1 mg/m <sup>3</sup> respirable dust : (250)/(%SiO <sub>2</sub> + 5) mppcf TWA respirable fraction : (10)/(%SiO <sub>2</sub> + 2) mg/m <sup>3</sup> TWA respirable fraction	IDLH: 50 mg/m <sup>3</sup> respirable dust
CARBON BLACK 1333-86-4	TWA: 3 mg/m <sup>3</sup> inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup> (vacated) TWA: 3.5 mg/m <sup>3</sup>	TWA: 3.5 mg/m <sup>3</sup> ; TWA: 0.1 mg/m <sup>3</sup> ; Carbon black in presence of Polycyclic aromatic hydrocarbons PAH IDLH: 1750 mg/m <sup>3</sup>

Chemical name	Alberta	British Columbia	Ontario	Quebec
BARIUM SULFATE 7727-43-7	TWA: 10 mg/m <sup>3</sup> ;	TWA: 5 mg/m <sup>3</sup> ; inhalable	TWA: 5 mg/m <sup>3</sup> ; inhalable particulate matter	TWAEV: 5 mg/m <sup>3</sup> ; inhalable dust
KAOLIN 1332-58-7	TWA: 2 mg/m <sup>3</sup> ; respirable	TWA: 2 mg/m <sup>3</sup> ; respirable particulate	TWA: 2 mg/m <sup>3</sup> ; respirable particulate matter	TWAEV: 2 mg/m <sup>3</sup> ; respirable dust
ACETONE 67-64-1	TWA: 500 ppm; TWA: 1200 mg/m <sup>3</sup> ; STEL: 750 ppm; STEL: 1800 mg/m <sup>3</sup> ;	TWA: 250 ppm; STEL: 500 ppm;	TWA: 250 ppm; STEL: 500 ppm;	TWAEV: 250 ppm; STEV: 500 ppm;
ISOBUTYL ACETATE 110-19-0	TWA: 150 ppm; TWA: 713 mg/m <sup>3</sup> ;	TWA: 50 ppm; STEL: 150 ppm;	TWA: 50 ppm; STEL: 150 ppm;	TWAEV: 50 ppm; STEV: 150 ppm;
CALCIUM CARBONATE 1317-65-3	TWA: 10 mg/m <sup>3</sup> ;	TWA: 10 mg/m <sup>3</sup> ; total dust TWA: 3 mg/m <sup>3</sup> ; respirable fraction STEL: 20 mg/m <sup>3</sup> ;	-	TWAEV: 10 mg/m <sup>3</sup> ; total dust
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m <sup>3</sup> ;	TWA: 10 mg/m <sup>3</sup> ; total dust TWA: 3 mg/m <sup>3</sup> ; respirable fraction	TWA: 10 mg/m <sup>3</sup> ;	TWAEV: 10 mg/m <sup>3</sup> ; total dust
SILICA, QUARTZ 14808-60-7	TWA: 0.025 mg/m <sup>3</sup> ; respirable particulate	TWA: 0.025 mg/m <sup>3</sup> ; respirable	TWA: 0.10 mg/m <sup>3</sup> ; respirable fraction	TWAEV: 0.05 mg/m <sup>3</sup> ; respirable dust
CARBON BLACK 1333-86-4	TWA: 3.5 mg/m <sup>3</sup> ;	TWA: 3 mg/m <sup>3</sup> ; inhalable	TWA: 3 mg/m <sup>3</sup> ; inhalable particulate matter	TWAEV: 3 mg/m <sup>3</sup> ; inhalable dust

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
BARIUM SULFATE	TWA: 5 mg/m <sup>3</sup> ; inhalable particulate matter	TWA: 5 mg/m <sup>3</sup> ; inhalable fraction	TWA: 5 mg/m <sup>3</sup> ; inhalable particulate matter	TWA: 5 mg/m <sup>3</sup> ; inhalable particulate matter
KAOLIN	TWA: 2 mg/m <sup>3</sup> ; particulate matter, respirable particulate matter	TWA: 2 mg/m <sup>3</sup> ;	TWA: 2 mg/m <sup>3</sup> ; particulate matter, respirable particulate matter	TWA: 2 mg/m <sup>3</sup> ; particulate matter, respirable particulate matter
ACETONE	TWA: 250 ppm; STEL: 500 ppm;	TWA: 250 ppm; STEL: 500 ppm;	TWA: 250 ppm; STEL: 500 ppm;	TWA: 250 ppm; STEL: 500 ppm;
ISOBUTYL ACETATE	TWA: 50 ppm; STEL: 150 ppm;	TWA: 50 ppm; STEL: 150 ppm;	TWA: 50 ppm; STEL: 150 ppm;	TWA: 50 ppm; STEL: 150 ppm;
TITANIUM DIOXIDE	TWA: 0.2 mg/m <sup>3</sup> ; nanoscale respirable particulate matter TWA: 2.5 mg/m <sup>3</sup> ; finescale respirable particulate matter	TWA: 10 mg/m <sup>3</sup> ;	TWA: 0.2 mg/m <sup>3</sup> ; nanoscale respirable particulate matter TWA: 2.5 mg/m <sup>3</sup> ; finescale respirable particulate matter	TWA: 0.2 mg/m <sup>3</sup> ; nanoscale respirable particulate matter TWA: 2.5 mg/m <sup>3</sup> ; finescale respirable particulate matter

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
SILICA, QUARTZ	TWA: 0.025 mg/m <sup>3</sup> ; respirable particulate matter	TWA: 0.025 mg/m <sup>3</sup> ; respirable fraction	TWA: 0.025 mg/m <sup>3</sup> ; respirable particulate matter	TWA: 0.025 mg/m <sup>3</sup> ; respirable particulate matter
CARBON BLACK	TWA: 3 mg/m <sup>3</sup> ; inhalable particulate matter	TWA: 3 mg/m <sup>3</sup> ; inhalable fraction	TWA: 3 mg/m <sup>3</sup> ; inhalable particulate matter	TWA: 3 mg/m <sup>3</sup> ; inhalable particulate matter

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
BARIUM SULFATE	TWA: 10 mg/m <sup>3</sup> ; STEL: 20 mg/m <sup>3</sup> ;	TWA: 5 mg/m <sup>3</sup> ; inhalable particulate matter	TWA: 10 mg/m <sup>3</sup> ; STEL: 20 mg/m <sup>3</sup> ;	
KAOLIN	TWA: 2 mg/m <sup>3</sup> ; respirable fraction STEL: 4 mg/m <sup>3</sup> ; respirable fraction	TWA: 2 mg/m <sup>3</sup> ; particulate matter, respirable particulate matter	TWA: 2 mg/m <sup>3</sup> ; respirable fraction STEL: 4 mg/m <sup>3</sup> ; respirable fraction	TWA: 30 mppcf; TWA: 10 mg/m <sup>3</sup> ; STEL: 20 mg/m <sup>3</sup> ;
ACETONE	TWA: 500 ppm; STEL: 750 ppm;	TWA: 250 ppm; STEL: 500 ppm;	TWA: 500 ppm; STEL: 750 ppm;	TWA: 1000 ppm; TWA: 2400 mg/m <sup>3</sup> ; STEL: 1250 ppm; STEL: 3000 mg/m <sup>3</sup> ;
ISOBUTYL ACETATE	TWA: 150 ppm; STEL: 188 ppm;	TWA: 50 ppm; STEL: 150 ppm;	TWA: 150 ppm; STEL: 188 ppm;	TWA: 150 ppm; TWA: 700 mg/m <sup>3</sup> ; STEL: 187 ppm; STEL: 875 mg/m <sup>3</sup> ;
CALCIUM CARBONATE	TWA: 10 mg/m <sup>3</sup> ; STEL: 20 mg/m <sup>3</sup> ;		TWA: 10 mg/m <sup>3</sup> ; STEL: 20 mg/m <sup>3</sup> ;	TWA: 30 mppcf; TWA: 10 mg/m <sup>3</sup> ; STEL: 20 mg/m <sup>3</sup> ;
TITANIUM DIOXIDE	TWA: 10 mg/m <sup>3</sup> ; STEL: 20 mg/m <sup>3</sup> ;	TWA: 0.2 mg/m <sup>3</sup> ; nanoscale respirable particulate matter TWA: 2.5 mg/m <sup>3</sup> ; finescale respirable particulate matter	TWA: 10 mg/m <sup>3</sup> ; STEL: 20 mg/m <sup>3</sup> ;	TWA: 30 mppcf; TWA: 10 mg/m <sup>3</sup> ; STEL: 20 mg/m <sup>3</sup> ;
SILICA, QUARTZ	TWA: 0.05 mg/m <sup>3</sup> ; respirable fraction	TWA: 0.025 mg/m <sup>3</sup> ; respirable particulate matter	TWA: 0.05 mg/m <sup>3</sup> ; respirable fraction	TWA: 300 particle/mL;
CARBON BLACK	TWA: 3.5 mg/m <sup>3</sup> ; STEL: 7 mg/m <sup>3</sup> ;	TWA: 3 mg/m <sup>3</sup> ; inhalable particulate matter	TWA: 3.5 mg/m <sup>3</sup> ; STEL: 7 mg/m <sup>3</sup> ;	TWA: 3.5 mg/m <sup>3</sup> ; STEL: 7 mg/m <sup>3</sup> ;

Chemical name	ACGIH
ACETONE 67-64-1	25 mg/L - urine (Acetone) - end of shift

### Appropriate engineering controls

#### Engineering controls

Showers  
Eyewash stations  
Ventilation systems.

### Individual protection measures, such as personal protective equipment

#### Eye/face protection

Tight sealing safety goggles.

#### Hand protection

Wear suitable gloves.

#### Skin and body protection

Wear suitable protective clothing. Antistatic boots. Chemical resistant apron. Wear fire/flame resistant/retardant clothing.

<b>Respiratory protection</b>	Use appropriate respiratory protection. Consult with an industrial hygienist to determine the appropriate respiratory protection for your specific use of this material.
<b>General hygiene considerations</b>	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.
<b>Thermal hazards</b>	No information available.

## 9. Physical and chemical properties

### Information on basic physical and chemical properties

<b>Physical state</b>	Liquid
<b>Appearance</b>	No information available
<b>Color</b>	Black
<b>Odor</b>	No information available
<b>Odor threshold</b>	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
<b>pH</b>	No data available	
<b>Melting point / freezing point</b>	No data available	
<b>Boiling point / boiling range</b>	54 - 118 °C / 129.2 - 244.4 °F	
<b>Flash point</b>	-18 °C / -0.4 °F	Tag Closed Cup
<b>Evaporation rate</b>	<1	Butyl acetate = 1
<b>Flammability (solid, gas)</b>	No data available	
<b>Flammability Limit in Air</b>		
<b>Upper flammability limit:</b>	12.8%	
<b>Lower flammability limit:</b>	2.4%	
<b>Vapor pressure</b>	181 mm Hg @ 68°F	
<b>Vapor density</b>	>1	Air = 1
<b>Relative density</b>	1.8	
<b>Water solubility</b>	Partially soluble	
<b>Solubility(ies)</b>	No data available	
<b>Partition coefficient</b>	No data available	
<b>Autoignition temperature</b>	No data available	
<b>Decomposition temperature</b>	No data available	
<b>Kinematic viscosity</b>	No data available	
<b>Dynamic viscosity</b>	No data available	
<b>Particle characteristics</b>		
<b>Particle Size</b>	No data available	
<b>Particle Size Distribution</b>	No data available	

### Other information

<b>Explosive properties</b>	No information available
<b>Oxidizing properties</b>	No information available
<b>Softening point</b>	No information available
<b>Molecular weight</b>	No information available
<b>VOC content</b>	No information available
<b>Density</b>	No information available
<b>Bulk density</b>	No information available

## 10. Stability and reactivity

<b>Reactivity</b>	No information available.
<b>Chemical stability</b>	Stable under normal conditions.
<b>Possibility of hazardous reactions</b>	None under normal processing.
<b>Hazardous polymerization</b>	No information available.

<b>Conditions to avoid</b>	Heat, flames and sparks. Excessive heat.
<b>Incompatible materials</b>	None known based on information supplied.
<b>Hazardous decomposition products</b>	Carbon oxides. Hydrogen chloride.

## 11. Toxicological information

### Information on likely routes of exposure

#### Product Information

<b>Inhalation</b>	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Harmful by inhalation. (based on components).
<b>Eye contact</b>	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
<b>Skin contact</b>	Specific test data for the substance or mixture is not available. May cause irritation. Prolonged contact may cause redness and irritation.
<b>Ingestion</b>	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Harmful if swallowed. (based on components).

### Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** May cause redness and tearing of the eyes. Coughing and/ or wheezing.

**Acute toxicity** Harmful if swallowed. Harmful by inhalation.

#### Numerical measures of toxicity

#### The following ATE values have been calculated for the mixture

<b>ATEmix (oral)</b>	1,052.20 mg/kg
<b>ATEmix (dermal)</b>	35,760.00 mg/kg
<b>ATEmix (inhalation-gas)</b>	99,999.00 ppm
<b>ATEmix (inhalation-vapor)</b>	99,999.00 mg/L
<b>ATEmix (inhalation-dust/mist)</b>	2.69 mg/L

#### Unknown acute toxicity

9.8542 % of the mixture consists of ingredient(s) of unknown acute oral toxicity  
 56.0242 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity  
 76.0142 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)  
 76.0142 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)  
 16.8442 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
BARIUM SULFATE 7727-43-7	= 307000 mg/kg ( Rat )	-	-
KAOLIN 1332-58-7	> 5000 mg/kg ( Rat )	> 5000 mg/kg ( Rat )	-
ACETONE 67-64-1	= 5800 mg/kg ( Rat )	> 15700 mg/kg ( Rabbit )	= 50100 mg/m <sup>3</sup> ( Rat ) 8 h
ISOBUTYL ACETATE 110-19-0	= 15400 mg/kg ( Rat )	> 17400 mg/kg ( Rabbit )	-
TITANIUM DIOXIDE 13463-67-7	> 2000 mg/kg ( Rat )	-	> 5.09 mg/L ( Rat ) 4 h
CARBON BLACK 1333-86-4	> 10000 mg/kg ( Rat )	> 2000 mg/kg ( Rabbit )	> 4.6 mg/m <sup>3</sup> ( Rat ) 4 h

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Skin corrosion/irritation** No information available.

**Serious eye damage/eye irritation** Classification based on data available for ingredients. Causes serious eye irritation.

**Respiratory or skin sensitization** No information available.

**Germ cell mutagenicity** No information available.

**Carcinogenicity** Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

Chemical name	ACGIH	IARC	NTP	OSHA
KAOLIN 1332-58-7	A4 - Not Classifiable as a Human Carcinogen	-	-	-
ACETONE 67-64-1	A4 - Not Classifiable as a Human Carcinogen	-	-	-
TITANIUM DIOXIDE 13463-67-7	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 2B - Possibly carcinogenic to humans	-	Present
SILICA, QUARTZ 14808-60-7	A2 - Suspected Human Carcinogen	Group 1 - Carcinogenic to humans	Known Human Carcinogen	Present
CARBON BLACK 1333-86-4	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 2B - Possibly carcinogenic to humans	-	Present

**Reproductive toxicity** No information available.

**STOT - single exposure** No information available.

**STOT - repeated exposure** No information available.

**Aspiration hazard** No information available.

**12. Ecological information**

**Ecotoxicity** The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
ACETONE 67-64-1	-	LC50: 4.74 - 6.33mL/L (96h, Oncorhynchus mykiss) LC50: 6210 - 8120mg/L (96h, Pimephales promelas) LC50: =8300mg/L (96h, Lepomis macrochirus)	-	EC50: 10294 - 17704mg/L (48h, Daphnia magna) EC50: 12600 - 12700mg/L (48h, Daphnia magna)
ISOBUTYL ACETATE 110-19-0	-	LC50: =17mg/L (96h, Oryzias latipes)	-	-

**Persistence and degradability** No information available.

**Bioaccumulative potential** There is no data for this product.

Chemical name	Partition coefficient
ACETONE 67-64-1	-0.24
ISOBUTYL ACETATE 110-19-0	2.3

**Other adverse effects** No information available.

### 13. Disposal considerations

#### Waste treatment methods

**Waste from residues/unused products** Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

**Contaminated packaging** Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

**US EPA Waste Number** Waste designations and classifications should be determined by the end user based on the application for which the product was used.

### 14. Transport information

#### DOT

**UN number or ID number** UN1133  
**Proper shipping name** Adhesives  
**Transport hazard class(es)** 3  
**Packing group** II  
**DOT Marine Pollutant** NP  
**Description** UN1133, Adhesives, 3, II, Limited Quantity  
**Special Provisions** 149, B52, IB2, T4, TP1, TP8  
**Emergency Response Guide Number** 128

#### TDG

**UN number or ID number** UN1133  
**UN proper shipping name** Adhesives  
**Transport hazard class(es)** 3  
**Packing group** II  
**Description** UN1133, Adhesives, 3, II, Limited Quantity

#### MEX

**UN number or ID number** UN1133  
**UN proper shipping name** Adhesives  
**Transport hazard class(es)** 3  
**Packing group** II  
**Description** UN1133, Adhesives, 3, II, Limited Quantity

#### ICAO (air)

**UN number or ID number** UN1133  
**UN proper shipping name** Adhesives  
**Transport hazard class(es)** 3  
**Packing group** II  
**Description** UN1133, Adhesives, 3, II, Limited Quantity  
**Special Provisions** A3

**IATA**

UN number or ID number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	3
Packing group	II
ERG Code	3L
Special Provisions	A3
Description	UN1133, Adhesives, 3, II, Limited Quantity

**IMDG**

UN number or ID number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	3
Packing group	II
EmS-No.	F-E, S-D
Description	UN1133, Adhesives, 3, II, (-18°C c.c.), Limited Quantity

**15. Regulatory information****Safety, health and environmental regulations/legislation specific for the substance or mixture****International Regulations**

**The Montreal Protocol on Substances that Deplete the Ozone Layer** Not applicable

**The Stockholm Convention on Persistent Organic Pollutants** Not applicable

**The Rotterdam Convention** Not applicable

**International Inventories**

<b>TSCA</b>	Complies
<b>DSL/NDSL</b>	Complies
<b>EINECS/ELINCS</b>	Complies
<b>ENCS</b>	Not determined
<b>IECSC</b>	Complies
<b>KECI</b>	Complies
<b>PICCS</b>	Complies
<b>AICS</b>	Complies
<b>NZIoC</b>	Not Determined

**Legend:**

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**EINECS/ELINCS** - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

**IECSC** - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing Chemicals Inventory

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**US Federal Regulations****SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
BARIUM SULFATE - 7727-43-7	1.0

**SARA 311/312 Hazard Categories**

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

**CWA (Clean Water Act)**

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ISOBUTYL ACETATE 110-19-0	-	-	-	X

**CERCLA**

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
ACETONE 67-64-1	5000 lb / kg (final RQ)	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
ISOBUTYL ACETATE 110-19-0	5000 lb / kg (final RQ)	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

**US State Regulations****California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
AMORPHOUS SILICA - 7631-86-9	*Carcinogen
TITANIUM DIOXIDE - 13463-67-7	*Carcinogen (airborne, unbound particles of respirable size)
SILICA, QUARTZ - 14808-60-7	*Carcinogen (airborne particles of respirable size only)
CARBON BLACK - 1333-86-4	*Carcinogen (airborne, unbound particles of respirable size)

\*The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product

**U.S. State Right-to-Know Regulations**

Chemical name	New Jersey	Massachusetts	Pennsylvania
BARIUM SULFATE 7727-43-7	X	X	X
KAOLIN 1332-58-7	X	X	X
ACETONE 67-64-1	X	X	X
ISOBUTYL ACETATE 110-19-0	X	X	X
CALCIUM CARBONATE 1317-65-3	X	X	X
AMORPHOUS SILICA 7631-86-9	-	X	X
TITANIUM DIOXIDE 13463-67-7	X	X	X
SILICA, QUARTZ 14808-60-7	X	X	X
CARBON BLACK 1333-86-4	X	X	X

**U.S. EPA Label Information**

**EPA Pesticide Registration Number** Not applicable

**16. Other information**

<b>NFPA</b>	<b>Health hazards</b> 2	<b>Flammability</b> 3	<b>Instability</b> 0	<b>Special hazards</b> -
<b>HMIS</b>	<b>Health hazards</b> 2 *	<b>Flammability</b> 3	<b>Physical hazards</b> 0	<b>Personal protection</b> X

Chronic Hazard Star Legend \* = Chronic Health Hazard

**Key or legend to abbreviations and acronyms used in the safety data sheet****Legend**

SVHC: Substances of Very High Concern for Authorization:  
 PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances  
 vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances  
 STOT: Specific Target Organ Toxicity  
 ATE: Acute Toxicity Estimate  
 LC50: 50% Lethal Concentration  
 LD50: 50% Lethal Dose

**Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitizers		

**Key literature references and sources for data used to compile the SDS**

U.S. Agency for Toxic Substances and Disease Registry (ATSDR)  
 U.S. Environmental Protection Agency ChemView Database  
 European Food Safety Authority (EFSA)  
 U.S. Environmental Protection Agency  
 U.S. EPA Acute Exposure Guideline Level(s) (AEGL(s))  
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act  
 U.S. Environmental Protection Agency High Production Volume Chemicals  
 Food Research Journal  
 Hazardous Substance Database  
 International Uniform Chemical Information Database (IUCLID)  
 Japan National Institute of Technology and Evaluation (NITE)  
 Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)  
 NIOSH (National Institute for Occupational Safety and Health)  
 National Library of Medicine's ChemID Plus (NLM CIP)  
 National Library of Medicine's PubMed database (NLM PUBMED)  
 U.S. National Toxicology Program (NTP)  
 New Zealand's Chemical Classification and Information Database (CCID)  
 International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications  
 International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program  
 International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set  
 United Nations World Health Organization (WHO)

**Revision Date** 19-May-2026

**Revision Note** No information available.

**Disclaimer**

**The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.**