


FEATURES:

- Multiple connectors are made from either copper or aluminum bar and can be used in a variety of neutral and grounding applications. Aluminum connectors are tin plated for low contact resistance and are suitable for use with copper or aluminum conductors. Aluminum connectors are dual rated for use with aluminum and copper cables.
- Copper connectors are suitable for use with copper wire only.
- *Supplied with screws unassembled.



PROGRAM:	SOLIDWORKS
UPDATED:	10/2024
SALES REV:	A
SIZE:	B (11x17)

MULTIPLE CONNECTORS: 4C SERIES USED IN NEUTRAL ASSEMBLIES & GROUNDING APPLICATIONS



CAT. NO.	MATERIAL	WIRE RANGE	NO. OF CIRCUITS	TOTAL NO. OF HOLES	LENGTH (IN.)	HEIGHT (IN.)	WIDTH (IN.)	HOLE SPACING (IN.)	MTNG. HOLE POSITION	STD. CTN. QTY.
4C-14-616	Copper	4-14	4	6	1.940	0.440	0.310	0.312	1 & 6	100
4C-14-717	Copper	4-14	5	7	2.250	0.440	0.310	0.312	1 & 7	100
4C-14-818	Copper	4-14	6	8	2.56	0.440	0.310	0.312	1 & 8	100
4C-14-14114	Copper	4-14	12	14	4.430	0.440	0.310	0.312	1 & 14	50
4C-14-15313	Copper	4-14	13	15	4.740	0.440	0.310	0.312	3 & 13	50
4C-14-15611	Copper	4-14	13	15	4.740	0.440	0.310	0.312	6 & 11	50
4C-190*	Copper	4-14	190	190	60.000	0.440	0.310	0.312	-	10

