

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 09.04.2013

Revision: 09.03.2021

1 Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name:** LEAK LOCK GOLD
- **Article number:** 11001, 11002, 11004, 11016, 11128, 11550
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the preparation** Sealant
- **1.3 Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
Highside Chemicals, Inc.
11114 Reichold Road
Gulfport, MS 39503 USA
Phone: (228) 896-9220
- **1.4 Emergency telephone number:**
ChemTel Inc.
(800)255-3924, +1 (813)248-0585

2 Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



F+; Highly flammable

R11: Highly flammable.

R67: Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

The classification is in accordance with the latest editions of international substances lists, and is supplemented by information from technical literature and by information provided by the company.

- **2.2 Label elements**

- **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 09.04.2013

Revision: 09.03.2021

Trade name: LEAK LOCK GOLD

(Contd. of page 1)

· **Hazard pictograms**

GHS02 GHS07

· **Signal word** Danger· **Hazard statements**

H225 Highly flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P280 Wear protective gloves and eye protection.

P233 Keep container tightly closed.

P261 Avoid breathing mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

· **Hazard description:**· **WHMIS-symbols:**

B2 - Flammable liquid

D2B - Toxic material causing other toxic effects

· **NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

HEALTH 1 Health = 1

FIRE 3 Fire = 3

REACTIVITY 0 Reactivity = 0

· **HMIS Long Term Health Hazard Substances**

64-17-5 ethanol

· **2.3 Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.

(Contd. on page 3)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 09.04.2013

Revision: 09.03.2021

Trade name: LEAK LOCK GOLD

· **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5	ethanol  F R11  Flam. Liq. 2, H225	25-50%
CAS: 14807-96-6 EINECS: 238-877-9	Talc (Mg3H2(SiO3)4)	25-50%
CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0	propan-2-ol  Xi R36;  F R11 R67  Flam. Liq. 2, H225  Eye Irrit. 2, H319; STOT SE 3, H336	<10%

· **Additional information:**

For the wording of the listed risk phrases refer to section 16.

Dried product contains substances which are considered nuisance dusts which require a NIOSH Breathing airborne particles or dust from mixing, spraying, sanding, grinding, etc. may cause irritation to respiratory tract.

4 First aid measures

· 4.1 Description of first aid measures

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Take affected persons out into the fresh air.

· **After inhalation:**

Supply fresh air.

Seek medical treatment in case of complaints.

· **After skin contact:**

Immediately rinse with water.

Clean with water and soap.

If skin irritation continues, consult a doctor.

· **After eye contact:**

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

· 4.2 Most important symptoms and effects, both acute and delayed

Dizziness

(Contd. on page 4)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 09.04.2013

Revision: 09.03.2021

Trade name: LEAK LOCK GOLD

(Contd. of page 3)

Headache

Nausea

Thirst

Disorientation

- **Hazards** Condition may deteriorate with alcohol consumption.

- **4.3 Indication of any immediate medical attention and special treatment needed**

Monitor circulation.

If necessary oxygen respiration treatment.

Medical supervision for at least 48 hours.

Contains ethanol and isopropanol.

5 Firefighting measures

- **5.1 Extinguishing media**

- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.

- **For safety reasons unsuitable extinguishing agents:** None.

- **5.2 Special hazards arising from the substance or mixture**

In case of fire, the following can be released:

Carbon monoxide (CO)

- **5.3 Advice for firefighters**

- **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

- **Additional information**

Eliminate all ignition sources if safe to do so.

Cool endangered receptacles with water spray.

6 Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**

Use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Keep away from ignition sources.

Protect from heat.

- **6.2 Environmental precautions:**

Dilute with plenty of water.

Suppress gases/fumes/haze with water haze or fog.

- **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dilute with plenty of water.

Dispose contaminated material as waste according to item 13.

- **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 5)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 09.04.2013

Revision: 09.03.2021

Trade name: LEAK LOCK GOLD

See Section 13 for disposal information.

(Contd. of page 4)

7 Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Keep away from heat and direct sunlight.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Flammable gas-air mixtures may form in empty receptacles.
Fumes can combine with air to form an explosive mixture.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Provide ventilation for receptacles.
Avoid storage near extreme heat, ignition sources or open flame.
- **Information about storage in one common storage facility:**
Store away from foodstuffs.
Store away from oxidizing agents.
Do not store together with acids.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Keep container tightly sealed.
Protect from heat and direct sunlight.
Store receptacle in a well ventilated area.
- **7.3 Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

Ingredients with limit values that require monitoring at the workplace:

64-17-5 ethanol

PEL (USA)	1900 mg/m ³ , 1000 ppm
REL (USA)	1900 mg/m ³ , 1000 ppm
TLV (USA)	Short-term value: 1880 mg/m ³ , 1000 ppm
EL (Canada)	Short-term value: 1000 ppm
EV (Canada)	1,900 mg/m ³ , 1,000 ppm

67-63-0 propan-2-ol

PEL (USA)	980 mg/m ³ , 400 ppm
-----------	---------------------------------

(Contd. on page 6)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 09.04.2013

Revision: 09.03.2021

Trade name: LEAK LOCK GOLD

(Contd. of page 5)

REL (USA)	Short-term value: 1225 mg/m ³ , 500 ppm Long-term value: 980 mg/m ³ , 400 ppm
TLV (USA)	Short-term value: 984 mg/m ³ , 400 ppm Long-term value: 492 mg/m ³ , 200 ppm BEI
EL (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm
EV (Canada)	Short-term value: 400 ppm Long-term value: 200 ppm

- **DNELs** No further relevant information available.
- **PNECs** No further relevant information available.
- **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Do not inhale gases / fumes / aerosols.
- Avoid contact with the eyes and skin.

· Respiratory protection:

- Use suitable respiratory protective device in case of insufficient ventilation.
- Use suitable respiratory protective device when high concentrations are present.
- For spills, respiratory protection may be advisable.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 7)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 09.04.2013

Revision: 09.03.2021

Trade name: LEAK LOCK GOLD

(Contd. of page 6)

- **Body protection:** Protective work clothing
- **Limitation and supervision of exposure into the environment**
No further relevant information available.
- **Risk management measures**
See Section 7 for additional information.
No further relevant information available.

9 Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Pasty
Colour:	Gold coloured
Odour:	Alcohol-like
Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	172 °F / 78 °C

· Flash point: 59 °F / 15 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: >500 °F / 260 °C

· Decomposition temperature: Not determined.

· Self-igniting: Product is not self-igniting.

· Danger of explosion: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower:	3,5 Vol %
Upper:	15,0 Vol %

· Vapour pressure at 20 °C: 59 hPa

· Density at 20 °C: 1,2 g/cm³

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with
water:

Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

(Contd. on page 8)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 09.04.2013

Revision: 09.03.2021

Trade name: LEAK LOCK GOLD

(Contd. of page 7)

- | | |
|---|--|
| <ul style="list-style-type: none"> · Viscosity: <li style="padding-left: 20px;">Dynamic: Not determined. <li style="padding-left: 20px;">Kinematic: Not determined. | |
| <ul style="list-style-type: none"> · Solvent content: <li style="padding-left: 20px;">Organic solvents: Not determined. <li style="padding-left: 20px;">VOC (US EPA Method 24) 35 % | |
| <ul style="list-style-type: none"> · 9.2 Other information | No further relevant information available. |

10 Stability and reactivity

- **10.1 Reactivity**
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions**
Flammable.
Used empty containers may contain product gases which form explosive mixtures with air.
Can react violently with oxygen rich (oxidizing) material. Danger of Explosion.
Strong exothermic reaction with acids.
Develops readily flammable gases/fumes.
- **10.4 Conditions to avoid**
Keep ignition sources away - Do not smoke.
Store away from oxidizing agents.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:**
Carbon monoxide and carbon dioxide
Danger of forming toxic pyrolysis products.

11 Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Slight irritant effect on skin and mucous membranes.
- **on the eye:** Slight irritant effect on eyes.
- **Sensitization:** No sensitizing effects known.
- **Subacute to chronic toxicity:** Vapours have narcotic effect.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Irritant

(Contd. on page 9)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 09.04.2013

Revision: 09.03.2021

Trade name: LEAK LOCK GOLD

(Contd. of page 8)

Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.

12 Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** The product is partially biodegradable. Significant residuals remain.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
This statement was deduced from the properties of the single components.
Due to available data on eliminability/decomposition and bioaccumulation potential a prolonged damage of the environment is unlikely.
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

13 Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Can be burned with household garbage after consulting with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations.
Small amounts may be diluted with plenty of water and washed away. Dispose of bigger amounts in accordance with Local Authority requirements.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water only.

14 Transport information

- | | |
|--|------------------|
| <ul style="list-style-type: none"> · 14.1 UN-Number · DOT, ADR, IMDG, IATA | <p>UN1133</p> |
| <ul style="list-style-type: none"> · 14.2 UN proper shipping name · DOT, ADR, IMDG, IATA | <p>Adhesives</p> |

(Contd. on page 10)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 09.04.2013

Revision: 09.03.2021

Trade name: LEAK LOCK GOLD

(Contd. of page 9)

· 14.3 Transport hazard class(es)

· DOT



· Class 3 Flammable liquids.
· Label 3

· ADR



· Class 3 (F1) Flammable liquids.
· Label 3

· IMDG, IATA



· Class 3 Flammable liquids.
· Label 3

· 14.4 Packing group

· DOT, ADR, IMDG, IATA II

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user

· Danger code (Kemler): Warning: Flammable liquids.
33
· EMS Number: F-E, S-E

· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 5L
· Transport category 2
· Tunnel restriction code D/E

· UN "Model Regulation":

UN1133, ADHESIVES, 3, II

(Contd. on page 11)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 09.04.2013

Revision: 09.03.2021

Trade name: LEAK LOCK GOLD

(Contd. of page 10)

15 Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

67-63-0 | propan-2-ol

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65 (California):**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

Ethanol - listing refers specifically to alcoholic beverage consumption and is not applicable for product.

64-17-5 | ethanol

- **Carcinogenic Categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

- **IARC (International Agency for Research on Cancer)**

64-17-5 | ethanol

1

14807-96-6 | Talc (Mg₃H₂(SiO₃)₄)

2B

- **TLV (Threshold Limit Value established by ACGIH)**

64-17-5 | ethanol

A3

14807-96-6 | Talc (Mg₃H₂(SiO₃)₄)

A4

67-63-0 | propan-2-ol

A4

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

- **Canada**

- **Canadian Domestic Substances List (DSL)**

All ingredients are listed.

(Contd. on page 12)

Safety Data Sheet

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and
GHS

Printing date 09.04.2013

Revision: 09.03.2021

Trade name: LEAK LOCK GOLD

(Contd. of page 11)

· Canadian Ingredient Disclosure list (limit 0.1%)	
64-17-5	ethanol
· Canadian Ingredient Disclosure list (limit 1%)	
67-63-0	propan-2-ol

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

R11 Highly flammable.

R36 Irritating to eyes.

R67 Vapours may cause drowsiness and dizziness.

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

· **Sources**

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: www.chemtelinc.com