

Directional Couplers 380-6000 MHz

SKU: 781004, 781005

FEATURES

- Wide Frequency Band 380-6000 MHz
- Low VSWR
- Low Insertion Loss
- Indoor & Outdoor Application IP65
- Widely used for In-building Solutions
- 1-year warranty



Specifications

TECHNICAL

Model	781004	781005
Frequency Band (MHz)	380-6000	
Coupling (dB)	7	10
Insertion Loss (dB)	≤1.5	≤1.1
Accuracy (dB)	±1.5	±1.5
Isolation (dB)		
575-2700 MHz	≥26	≥29
2700-3800 MHz	≥24	≥27
3800-4800 MHz	≥22	≥25
4800-6000 MHz	≥19	≥22

(cont'd)

VSWR	≤1.35
PIM(dBc)	≤-150dBc@2*43dBm (698-2700 MHz)
Impedance (Ω)	50
Power(W)	200/Port
Humidity (%)	5-95
Temperature	-22°F - +149°F (-30°C - +65°C)
Application	Indoor or Outdoor, IP65

⚠️WARNING: This product can expose you to chemicals including Nickel, which is known to the State of California to cause cancer, and Bisphenol A, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Package Dimensions

781004 7.0" L x 3.125" W x 1.25" H | .890 lbs.

781005 7.0" L x 3.125" W x 1.25" H | .910 lbs.

FOR PARTNER'S USE

Support



1 Year Warranty

US Web: wilsonconnectivity.com

US Phone: +1 800 871 1612

INTL Phone: +44 1223 982031

UPC

