


IPLD600-5C SHOWN

PART NUMBER	NO. OF PORTS	LENGTH
IPLD600-3C	3	4.47
IPLD600-4C	4	5.77
IPLD600-5C	5	7.07
IPLD600-6C	6	8.37
IPLD600-8C	8	10.97
IPLD600-10C	10	13.57
IPLD600-12C	12	16.17
IPLD600-14C	14	18.77

WIRE ENTRY POINT  
WIRE RANGE: 600MCM - #6AWG  
PRE-FILLED W/ OXIDE INHIBITOR

- NOTES:
- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
  - UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
  - DUAL RATED FOR 90C COPPER AND/OR ALUMINUM CONDUCTOR.
  - COLD TEMPERATURE RATED TO -45C.
  - HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION AND CHEMICAL RESISTANT



**POLARIS**  
SALES . CO . INC

PROPRIETARY AND CONFIDENTIAL		11625 PROSPEROUS DRIVE ODESSA, FL 33556	
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.		TITLE:	
		CLEAR INSULATED DUAL ENTRY 600 CONNECTOR	
DRAWN BY	NAME	DATE	DWG. NO.
L. HILL	L. HILL	07/25/2014	IPLD600C SERIES
MATERIAL: N/A		SCALE: N/A	SHEET: 1 OF 1