


NSI INDUSTRIES LLC
EASY-TWIST™ DRUM LABEL
WWC-R-D_ET-TOWC_Packaging_Label
v3
238mm x 95.25mm
9/2024

DO NOT PRINT CYAN
LINE-PLACEMENT ONLY



The colors on the package are
CMYK, but they should match
the spot colors shown above.

95.25mm

WARNING/PRECAUTION/ADVERTISSEMENT

Turn off power before installing or removing connectors
Couper l'alimentation avant d'installer ou de retirer les
raccords / Apague la alimentación antes de instalar o
retirar los conectores

**TO BE SOLD ONLY WITH
INSTALLATION INSTRUCTIONS**

INSTRUCTIONS
Strip solid wires 5/8" (15.9 mm)
Pre-twisting unnecessary, hold stripped wires together
with ends even. Lead stranded wires slightly
Align any frayed strands or conductors
Push wires into connector and screw on until two twists
are visible in wires

SPECIFICATIONS
Listed as a pressure-type wire connector
Temperature Rating: 105°C (221°F) max
Voltage Rating: 600V max building wiring; 1000V max in
luminaries and signs
FOR USE WITH COPPER TO COPPER CONDUCTOR

▲ **WARNING:** Cancer and reproductive harm
▲ **ADVERTENCIA:** Cáncer y daño reproductivo
▲ **ADVERTISSEMENT:** Cancer et troubles de l'appareil reproducteur
www.P65Warnings.ca.gov

WWC-R-D

EASY-TWIST™
WINGED WIRE CONNECTORS
Red Winged Connectors
Raccords Ailes Rouge
Conectores Rojos Con Clip
De Seguridad


20,000
Qty/Qte/Ctd
22-6 AWG
Solid & Stranded

WIRE COMBINATIONS*
1 #6
1 or 2 #8
1 to 4 #10
1 to 5 #12
1 to 6 #14 or #16
2 to 6 #18
3 to 6 #20
4 to 6 #22
1 #6 w/1 #10

SPÉCIFICATIONS
Répertorié comme un connecteur de fil
de type à pression
Température nominale : 105°C (221°F)
max
Tension nominale : 600V max. pour le
câblage des bâtiments ; 1000V max.
pour les luminaires et les panneaux
À UTILISER AVEC UN CONDUCTEUR
CUIVRE À CUIVRE

INSTRUCCIONES
Desforre los cables sólidos 5/8"
(15.9 mm)
No es necesario que estén
previamente trenzados, sostenga
los cables desforrados juntos con las
puntas al mismo nivel. Meta un poco
los cables trenzados
Alinee los cables trenzados o
conductores deshilachados
Introduzca los cables en el conector
y enrosque hasta que se vean dos
trenzas en los cables

ESPECIFICACIONES
Certificado como conector de cables
tipo a presión
Temperatura nominal: 105 °C (221
°F) máx.
Voltaje nominal: 600 V máximo en el
cableado del edificio; 1000 V máximo en
artefactos y letreros
PARA USARSE CON CONDUCTORES DE
COBRE A COBRE

*For complete listing of wire combinations and voltage ratings,
scan QR code or contact Customer Service at 800-321-5847



NSI Industries
800.321.5847
nsiindustries.com

Made in Taiwan
Fabrique en Taïwan
Hecho en Taiwán



LISTED
WIRE CONNECTORS
E158907
8100

UL

RoHS
Compliant

REACH
Compliant

SCAN ME



6 62381 14116 3

238mm