



Metal Hole Punches

Limited Lifetime Warranty

1/8 in. (3.2 mm) Ceiling Grid Punch

Malco's unique Ceiling Grid Punch makes a clean 1/8 in. (3.2 mm) hole in up to three layers of 25 gauge (0.53 mm) ceiling grid.

The tool's slim but strong steel "C" frame allows easy access in tight corners and is ideal for punching through main tees and perimeter wall angles that are to be secured with rivets. A generous throat opening allows full operation from the edge of both standard 1 and 1/2 in. (25.4 and 12.7 mm) grid profiles. The Malco Ceiling Grid Punch features durable all steel construction and rust-resistant nickel plate and black oxide finishes. The tool steel punch is easily replaceable. Lightweight, one hand operation, aided by compound leverage, helps assure a consistent professional quality installation. Ergonomic Redline Handles with unique one-hand operation latch offer maximum compound leverage performance and natural fit and feel.



CGPR



Work overhead
and in tight corners!

1/8 - 3/16 in. (3.2 - 4.8 mm) Hole Punch

Does the work of more expensive, bulkier punches faster and easier. Use in any edge application for making holes in window extrusions, metal ductwork, or sheet stock.

Compound leverage increases one hand mechanical advantage 8 to 1. Spring return handles allow quick set-up for repetitive applications. Stop gauge permits adjustments from 1/4 to 1-1/8 in. (6.4 to 28.6 mm) depths from edge of material. Punch and die are easily replaceable or changed to another size. Punch and dies are constructed from high quality tool steel used in commercial high production punch press dies. Body of tool consists of lightweight, aluminum die cast 'C' frame and rust resistant nickel plated steel handles and parts. Ergonomic Redline Handles with unique one-hand operation latch offer maximum compound leverage performance and natural fit and feel.



HP18KR



Compound Handle
Leverage for maximum
ease of operation.

Easily interchangeable 1/8 in. (3.2 mm)
and 3/16 in. (4.8 mm) punches and dies
supplied with tool.

Replacement Punches and Dies

CGP18 1/8 in. (3.2 mm) Replacement Punch Only (Die is part of frame) for CGPR

HPD18 1/8 in. Replacement Punch & Die Kit for HP18KR

HPD316 3/16 in. Replacement Punch & Die Kit for HP18KR

Optional Metric Punches and Dies for HP18KR

HPD41M 4.1 mm Replacement Punch & Die Kit

CAPACITIES	Material	Galvanized Steel 24 Gauge	Mild Steel 22 Gauge
CGPR	inches (mm)	.028 (0.71) up to 3 layers	.030 (0.76) up to 3 layers
HP18KR	inches (mm)	.028 (0.71) up to 2 layers	.024 (0.61) up to 2 layers

Catalog Number	Description	Punch in. (mm)	Variable Leverage Ratio (High / Low) throughout stroke	Punch / Frame	Length in. (mm)	Net Wt. oz. (g)
CGPR	Ceiling Grid Punch	1/8 (3.2)	6.7 to 1.0 - 8.4 to 1.0	Tool Steel / Alloy Steel	9.5 (241)	16 (454)
HP18KR	Hole Punch	1/8 (3.2) & 3/16 (4.8)	6.7 to 1.0 - 8.4 to 1.0	Tool Steel / Alloy Steel	9 (229)	16 (454)