

TurboShearNS



Work. Perform. Outlast.
Limited Lifetime Warranty



Attach to any drill to make fast rough-hewn straight, angled or scalloped cuts in roofing slate. Make fast straight, angled or curved cuts in 4mm to 8mm natural roofing slate. Cutting slate with finished side up produces an authentic-looking, hand-cut appearance. And a padded skid plate prevents scratches to the exposed slate finish. Cut thousands of linear feet of roofing slate quickly and easily all season long!



TSNS1

Pat. No. 9,649,702

360° Rotating Head

The 360-degree rotating head allows users to position and lock the drill so it doesn't interfere with material for quick, hassle-free cuts every time!

Capacities: Natural Roofing Slate - 4-8 mm

| Catalog Number | Description | Net Wt. oz. (g) | Net Wt. lbs. (kg) |
|--------------------------|--|-----------------|-------------------|
| TSNS1 | TurboShear, Natural Roofing Slate | — | 2.5 (1.13) |
| Replacement Parts | | | |
| TSDC | TurboShear Drill Clamp | 8 (227) | — |
| TSCG | TurboShear Chuck Guard | .96 (27) | — |
| TSNS1RB EV | TurboShear Replacement Blades & Skid Plate for TSNS1 | 9.28 (263) | — |

Drill Requirements:

1/4 in. (6.35 mm) Chuck,
Min. 14.4V - DC, Max 7A-AC

