



# WW-CP-202P

## PRINTED ALL-WEATHER CORROSION PROTECTION TAPE - 20MIL

| DESCRIPTION   | FEATURES   |
|---|--|
| WW-CP-202P is a printed, 20 mil, plasticized PVC tape with superior adhesion and corrosion protection. This tape can protect metal pipes, conduit and fittings against abrasion, corrosion or impacts. It is suitable for use above and below ground. | <ul style="list-style-type: none"> <li>• Black PVC backing</li> <li>• Excellent adhesion</li> <li>• Printed</li> <li>• Great protection in all weather conditions</li> </ul> |

| MATERIALS | BACKING         | ADHESIVE     | COLOR           | STANDARD SIZE (WIDTH X LENGTH) | PART NUMBER |
|-----------|-----------------|--------------|-----------------|--------------------------------|-------------|
|           | Plasticized PVC | Rubber based | Black - Printed | 2" x 100' (51mm x 30.5m)       | WW-CP-202P  |

| TECHNICAL PROPERTIES | CHARACTERISTIC              | TYPICAL VALUE | TEST METHOD |
|----------------------|-----------------------------|---------------|-------------|
|                      | Thickness (mils)            | 20            | ASTM D 1000 |
|                      | Breaking strength (lbs/in)  | 35            | ASTM D 1000 |
|                      | Elongation at break (%)     | 200           | ASTM D 1000 |
|                      | Adhesion to steel (oz/in)   | 20            | ASTM D 1000 |
|                      | Adhesion to backing (oz/in) | 20            | ASTM D 1000 |
|                      | Dielectric strength (V/mil) | 550           | ASTM D 1000 |

| RECOMMENDED USES  | STORAGE  | SHELF LIFE                          |
|---|--|-------------------------------------|
| For protection against abrasion, corrosion and impact, both above and below ground. | In original packaging, placed in a horizontal position, covered, between 5°C and 35°C. | 60 months from date of manufacture. |

Data in table represents average test results and are not to be used for specification purpose. Users should test the products' suitability for their intended use themselves.

**LIMITED WARRANTY:** NSI Industries LLC warrants that each of its products will be free from material and manufacture defects at the date of shipment (unless specified otherwise). NSI Industries LLC makes or gives no warranty to the distributor, its customers, or the product's end user regarding the product's merchantability and/or suitability for their/its intended use or purpose, and buyer shall assume all risks associated therewith. Provided that the product is proven to be defective, NSI Industries sole obligation and buyer's exclusive remedy shall be through the distributor, at NSI Industries' discretion, to replace, repair, or refund the product proved to be defective within the time period specified above. EXCEPT AS EXPRESSLY SET FORTH HEREIN, NSI INDUSTRIES MAKES OR GIVES NO OTHER WARRANTIES, EXPRESSED OR IMPLIED. Except where prohibited by law, NSI Industries LLC will not be liable for collateral, consequential, indirect or incidental damages arising out of, or connected in any way with the supply of products.

