Printing date 01/25/2024 Revised On 01/25/2024

1 Identification of the substance and manufacturer

Trade name: **SPRAY MATCH SOLVENT**

0000163395 Product code:

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:**

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.

Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.

Eye Irritation 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: GHS Hazard pictograms

Precautionary statements







Signal word Danger

Extremely flammable aerosol. **Hazard statements**

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection. IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

	•		The product is a mixture of the substances noted below with normal additions.	
	Dangerou	ıs components:		
Ī	67-64-1	Acetone		50-100%
	74-98-6	propane		15-25%
	106-97-8	n-butane		10-15%
	763-69-9	Ester EEP		≥5-<10%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Rinse mouth with water. Do not induce vomiting. After swallowing:

Most important symptoms and

effects: Dizziness

Indication of any immediate medical

No further relevant information available. attention needed:

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Special hazards: Can form explosive gas-air mixtures.

(Contd. on page 2)

Safety Data Sheet

Printing date 01/25/2024 Revised On 01/25/2024

Trade name: SPRAY MATCH SOLVENT

Protective equipment for

firefighters: A respiratory protective device may be necessary.

(Contd. of page 1)

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

67-64-1 Acetone

PEL (USA) Long-term value: 2400 mg/m³, 1000 ppm REL (USA) Long-term value: 590 mg/m³, 250 ppm

TLV (USA) Short-term value: 500 ppm

Long-term value: 250 ppm

A4, BEI

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm
REL (USA) Long-term value: 1800 mg/m³, 1000 ppm
TLV (USA) see Appendix F Minimal oxygen content (D, EX)

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 1000 ppm (EX)

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 25 mg/L

Hand protection:

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

Hygienic protection: Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment:A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be

worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Mitrile gloves.

The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Flammability (solid, gas):

Appearance: Aerosol.
Odor: Aromatic
Odor threshold: Not determined.

pH-value:
Melting point/Melting range
Boiling point:

Flash point:

Not determined.
Undetermined.
-44 °C (-47.2 °F)
-19 °C (-2.2 °F)

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Extremely flammable.

Lower Explosion Limit: 1.7 Vol % Upper Explosion Limit: 10.9 Vol %

Vapor pressure at 20 °C (68 °F): 233 hPa (174.8 mm Hg)

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet

Printing date 01/25/2024 Revised On 01/25/2024

Trade name: SPRAY MATCH SOLVENT

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density
Evaporation rate
Partition coefficient: n-octonal/water: Not determined.
Solubility:
Viscosity:
Not determined.
Not determined.
Not determined.
Not determined.

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials:

Hazardous decomposition:

No further relevant information available.

No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects: No data available.
Skin effects: No irritant effect.
Eve effects: Irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons

(HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated

solvents.

Bioaccumulative potential:
Mobility in soil:
Other adverse effects:

No further relevant information available.
No further relevant information available.
No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be

disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled. Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950 DOT UN1950

DOT Aerosols, flammable
ADR 1950 Aerosols

Transport hazard class(es):

Class 2.1 Gases

Special precautions for user: Warning: Gases

EMS Number: F-D,S-U

Packaging Group: --

UN 1950 AEROSOLS, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

Toxic Substances Control Act

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

(DSL): All ingredients are listed or exempted.

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

None of the ingredients in this product are listed.

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

(Contd. on page 4)

Page 4/4

Safety Data Sheet

Printing date 01/25/2024 Revised On 01/25/2024

1 mining date 5 1/25/2521	11011000 011 0 1/20/2021						
Trade name: SPRAY MATCH SOLVENT							
	(Contd. of page 3)						
EPA:							
67-64-1 Acetone	1						

	16 C	ther	information	
--	------	------	-------------	--

Contact: Regulatory Affairs