

## Safety Data Sheet

Printing date 01/24/2024

Revised On 01/24/2024

## 1 Identification of the substance and manufacturer

**Trade name:** RUST CONVERTER PRIMER  
**Product code:** 0000160045  
**Recommended use:** Paint and coatings application.  
**Uses advised against:** Any that differs from the recommended use.

## 2 Hazard(s) identification

## Classification of the substance or mixture

Flammable Aerosols 1 H222 Extremely flammable aerosol.  
 Gases under Pressure - Liquefied gas H280 Contains gas under pressure; may explode if heated.  
 Eye Irritation 2A H319 Causes serious eye irritation.  
 Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.  
 Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

## Additional information:

## GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

## Signal word

## Hazard statements

Danger  
 Extremely flammable aerosol.  
 Contains gas under pressure; may explode if heated.  
 Causes serious eye irritation.  
 May cause drowsiness or dizziness.

## Precautionary statements

May cause damage to organs through prolonged or repeated exposure.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Call a poison center/doctor if you feel unwell.  
 If eye irritation persists: Get medical advice/attention.  
 Store in a well-ventilated place.  
 Store locked up.  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

## 3 Composition/information on ingredients

## Chemical characterization: Mixtures

**Chemical Description:** This product is a mixture of the substances listed below with nonhazardous additions.

## Dangerous components:

|            |                        |        |
|------------|------------------------|--------|
| 67-64-1    | Acetone                | 15-25% |
| 74-98-6    | propane                | 15-25% |
| 540-88-5   | tert-butyl acetate     | 10-15% |
| 14807-96-6 | Talc                   | 10-15% |
| 106-97-8   | n-butane               | 5-10%  |
| 123-42-2   | diacetone alcohol      | 1-5%   |
| 57-55-6    | propylene glycol       | 1-5%   |
| 64742-89-8 | VM&P Naphtha           | 1-5%   |
| 108-10-1   | methyl isobutyl ketone | 1-5%   |
| 107-87-9   | Methyl Propyl Ketone   | 1-5%   |
| 108-65-6   | PM acetate             | 1-5%   |

## 4 First-aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.  
**After skin contact:** Remove contaminated clothing. Wash exposed area with soap and water.  
**After eye contact:** Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.  
**After swallowing:** Rinse mouth with water. Do not induce vomiting.  
**Most important symptoms and effects:** Dizziness  
**Indication of any immediate medical attention needed:** No further relevant information available.

(Contd. on page 2)

Trade name: RUST CONVERTER PRIMER

(Contd. of page 1)

**5 Fire-fighting measures**

**Extinguishing agents:** CO2, extinguishing powder or water spray. Fight larger fires with water spray.  
**Special hazards:** Can form explosive gas-air mixtures.  
**Protective equipment for firefighters:** A respiratory protective device may be necessary.

**6 Accidental release measures**

**Personal precautions, protective equipment and emergency procedures:** Use respiratory protective device against the effects of fumes/dust/aerosol.  
**Methods and material for containment and cleaning up:** Absorb liquid components with liquid-binding material.

**7 Handling and storage**

**Precautions for safe handling:** Use only in well ventilated areas.  
**Storage requirements:** Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

**8 Exposure controls/personal protection**

**Components with limit values that require monitoring at the workplace:**

**67-64-1 Acetone**

|           |  |
|-----------|--|
| PEL (USA) | Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm               |
| REL (USA) | Long-term value: 590 mg/m <sup>3</sup> , 250 ppm                 |
| TLV (USA) | Short-term value: 500 ppm<br>Long-term value: 250 ppm<br>A4, BEI |

**74-98-6 propane**

|           |  |
|-----------|--|
| PEL (USA) | Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm |
| REL (USA) | Long-term value: 1800 mg/m <sup>3</sup> , 1000 ppm |
| TLV (USA) | see Appendix F Minimal oxygen content ( D, EX)     |

**540-88-5 tert-butyl acetate**

|           |  |
|-----------|--|
| PEL (USA) | Long-term value: 950 mg/m <sup>3</sup> , 200 ppm     |
| REL (USA) | Long-term value: 950 mg/m <sup>3</sup> , 200 ppm     |
| TLV (USA) | Short-term value: 150 ppm<br>Long-term value: 50 ppm |

**106-97-8 n-butane**

|           |   |
|-----------|---|
| REL (USA) | Long-term value: 1900 mg/m <sup>3</sup> , 800 ppm |
| TLV (USA) | Short-term value: 1000 ppm<br>(EX)                |

**123-42-2 diacetone alcohol**

|           |   |
|-----------|---|
| PEL (USA) | Long-term value: 240 mg/m <sup>3</sup> , 50 ppm |
| REL (USA) | Long-term value: 240 mg/m <sup>3</sup> , 50 ppm |
| TLV (USA) | Long-term value: 50 ppm                         |

**57-55-6 propylene glycol**

|            |                                       |
|------------|---------------------------------------|
| WEEL (USA) | Long-term value: 10 mg/m <sup>3</sup> |
|------------|---------------------------------------|

**108-10-1 methyl isobutyl ketone**

|           |   |
|-----------|---|
| PEL (USA) | Long-term value: 410 mg/m <sup>3</sup> , 100 ppm  |
| REL (USA) | Short-term value: 300 mg/m <sup>3</sup> , 75 ppm<br>Long-term value: 205 mg/m <sup>3</sup> , 50 ppm |
| TLV (USA) | Short-term value: 75 ppm<br>Long-term value: 20 ppm<br>BEI, A3                                      |

**107-87-9 Methyl Propyl Ketone**

|           |  |
|-----------|--|
| PEL (USA) | Long-term value: 700 mg/m <sup>3</sup> , 200 ppm |
| REL (USA) | Long-term value: 530 mg/m <sup>3</sup> , 150 ppm |
| TLV (USA) | Short-term value: 150 ppm                        |

**108-65-6 PM acetate**

|            |                         |
|------------|-------------------------|
| WEEL (USA) | Long-term value: 50 ppm |
|------------|-------------------------|

(Contd. on page 3)

## Safety Data Sheet

Printing date 01/24/2024

Revised On 01/24/2024

Trade name: RUST CONVERTER PRIMER

(Contd. of page 2)

**Ingredients with biological limit values:****67-64-1 Acetone**

BEI (USA) 25 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: Acetone (nonspecific)

**108-10-1 methyl isobutyl ketone**

BEI (USA) 1 mg/L  
 Medium: urine  
 Time: end of shift  
 Parameter: MIBK

**Hygienic protection:**

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin.

Do not eat or drink while working.

**Breathing equipment:**

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

**Hand protection:**

Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

**Eye protection:**

Tightly sealed goggles

**9 Physical and chemical properties****Appearance:** Aerosol.**Odor:** Aromatic**Odor threshold:** Not determined.**pH-value:** Not determined.**Melting point/Melting range** Undetermined.**Boiling point:** -44.5 °C (-48.1 °F)**Flash point:** -19 °C (-2.2 °F)**Flammability (solid, gas):** Extremely flammable.**Decomposition temperature:** Not determined.**Auto igniting:** Product is not self-igniting.**Danger of explosion:** In use, may form flammable/explosive vapour-air mixture.**Lower Explosion Limit:** 1.7 Vol %**Upper Explosion Limit:** 10.9 Vol %**Vapor pressure:** Not determined.**Relative Density:** Between 0.77 and 0.85 (Water equals 1.00)**Vapor density** Not determined.**Evaporation rate** Not applicable.**Partition coefficient: n-octanol/water:** Not determined.**Solubility:** Not determined.**Viscosity:** Not determined.**Water:** 0.0 %**10 Stability and reactivity****Reactivity:** Stable at normal temperatures.**Conditions to avoid:** Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.**Chemical stability:** Not fully evaluated.**Possibility of hazardous reactions:** No dangerous reactions known.**Incompatible materials:** No further relevant information available.**Hazardous decomposition:** No dangerous decomposition products known.**11 Toxicological information****LD/LC50 values that are relevant for classification:****123-42-2 diacetone alcohol**

|        |      |                    |
|--------|------|--------------------|
| Oral   | LD50 | 4,000 mg/kg (rat)  |
| Dermal | LD50 | 13,630 mg/kg (rab) |

**108-10-1 methyl isobutyl ketone**

|            |          |                    |
|------------|----------|--------------------|
| Oral       | LD50     | 2,100 mg/kg (rat)  |
| Dermal     | LD50     | 16,000 mg/kg (rab) |
| Inhalative | LC50/4 h | 11 mg/l (ATE)      |

(Contd. on page 4)

## Safety Data Sheet

Printing date 01/24/2024

Revised On 01/24/2024

Trade name: RUST CONVERTER PRIMER

(Contd. of page 3)

8.3-16.6 mg/l (rat)

**108-65-6 PM acetate**

|            |          |                   |
|------------|----------|-------------------|
| Oral       | LD50     | 8,500 mg/kg (rat) |
| Inhalative | LC50/4 h | 35.7 mg/l (rat)   |

**Information on toxicological effects:** No data available.  
**Skin effects:** No irritant effect.  
**Eye effects:** Irritating effect.  
**Sensitization:** No sensitizing effects known.

**12 Ecological information**

**Aquatic toxicity:** Hazardous for water, do not empty into drains.  
**Persistence and degradability:** The product is degradable after prolonged exposure to natural weathering processes.  
**Other information:** This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.  
**Bioaccumulative potential:** No further relevant information available.  
**Mobility in soil:** No further relevant information available.  
**Other adverse effects:** No further relevant information available.

**13 Disposal considerations**

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.  
**Recommendation:** Completely empty cans should be recycled.  
**Recommended cleansing agent:** Water, if necessary with cleansing agents.

**14 Transport information**

|                               |                       |
|-------------------------------|-----------------------|
| UN-Number                     | UN1950                |
| DOT                           | UN1950                |
| DOT                           | Aerosols, flammable   |
| ADR                           | 1950 AEROSOLS         |
| Transport hazard class(es):   |                       |
| Class                         | 2.1 Gases             |
| Special precautions for user: | Warning: Gases        |
| EMS Number:                   | F-D,S-U               |
| Packaging Group:              | --                    |
| UN "Model Regulation":        | UN 1950 AEROSOLS, 2.1 |

**15 Regulatory information****SARA Section 355 (extremely hazardous substances):**

None of the ingredients in this product are listed.

**SARA Section 313 (Specific toxic chemical listings):**

108-10-1 | methyl isobutyl ketone

**Toxic Substances Control Act****(TSCA):** All hazardous ingredients are found on the inventory list of substances.**Canadian Domestic Substances List****(DSL):** All ingredients are listed or exempted.**Consumer Product Safety****Commission (CPSC):** This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.**California Proposition 65 chemicals known to cause cancer:**

108-10-1 | methyl isobutyl ketone

1333-86-4 | Carbon black

100-41-4 | ethyl benzene

**Prop 65 chemicals known to cause birth defects or reproductive harm:**

108-10-1 | methyl isobutyl ketone

**EPA:**

67-64-1 | Acetone

108-10-1 | methyl isobutyl ketone

**16 Other information****Contact:** Regulatory Affairs