

SUBMITTAL RECORD

JOB _____
 LOCATION _____
 SUBMITTED TO _____
 SUBMITTAL PREPARED BY _____
 APPROVED BY _____
 DATE _____




Submittal Form

VDS, NS

Hanging Strap

Duro Dyne provides Hanging Strap fabrics that are waterproof, grease, oil & acid resistant, and have low smoke & flame development. For maximum strength: put the two ends together and fold it over before securing to the ceiling or joist.



	VINYL DURO STRAP	NOVA STRAP
FLAME SPREAD & SMOKE DEVELOPMENT:	N/A	Less Than 25 / Less Than 50 ASTME 84
TENSILE STRENGTH:	Warp-70 lbs./In. Fill-70 lbs./In	Warp-70 lbs./In.; Fill-70 lbs./In
HEAT RESISTANCE:	200° F	200° F
TEAR STRENGTH:	Warp- 8 lbs./In. Fill-11 lbs./In	N/A
FABRIC:	Black vinyl coated polyester fill	Black or Silver Woven Polypropylene
TOTAL FABRIC THICKNESS:	.022" Approx.	.025" Approx.
QUANTITY PER CARTON:	10 rolls (Conveniently packaged in a dispenser box with cutting blade)	8 or 24 rolls per box
ADDITIONAL INFO:	N/A	Resistant to Grease, Oil, Gasoline and Acid.

HANGING STRAP			
ITEM#	MODEL	DESCRIPTION	SIZE
10181	VDS200C	Vinyl Duro Strap	1-1/2" x 200'
10163	NS175S	Nova Strap - Silver	1-3/4" x 300'
10165	NS300B	Nova Strap - Black	3" x 300'
10166	NS300S	Nova Strap - Silver	3" x 300'
10180	NS175B	Nova Strap- Black	1-3/4" x 300'

Best Installation Practices

The Air Duct Council recommends supporting flex duct at manufacturers recommended intervals or no greater than 4'. Maximum centerline sag shall be no more than 1/2" per foot. Hanging Strap must be a minimum of 1-1/2" wide. For more information, please visit the Air Duct Council "Supporting Flexible Duct" section 4.6.