

TurboShearFC



Make your drill a fiber cement siding shear! Cuts 5/16 in. (8 mm) fiber cement siding plank with minimal dust. A wide skid-plate on the head design stabilizes cutting action for extra-smooth results. This versatile shear also navigates curved-pattern cuts for window and door arches. One blade and skid plate set will last an average of 30 residential siding projects. You can even rotate the tool's skid plate to maximize cutting life.



TSF1
Pat. No. 9,649,702

360° Rotating Head

The 360-degree rotating head allows users to position and lock the drill so it doesn't interfere with material for quick, hassle-free cuts every time!



Drill Requirements:
1/4 in. (6.35 mm) Chuck,
Min. 14.4V - DC, Max 7A-AC



WARNING:

Fiber cement contains crystalline silica. Respirable silica contained in cutting dust is known to cause cancer.

Capacities: Fiber Cement Siding - 5/16in. (8 mm)

Catalog Number	Description	Net Wt. oz. (g)	Net Wt. lbs. (kg)
TSF1	TurboShear, Fiber Cement	—	2.5 (1.13)
Replacement Parts			
TSDC	TurboShear Drill Clamp	8 (227)	—
TSCG	TurboShear Chuck Guard	.96 (27)	—
TSF1RBN	TurboShear Replacement Blades for TSF1 (shown)	9.28 (263)	—

www.malcotools.com

SL17742A