

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Revision Date 04-Mar-2025 Version 2

1. Identification

Product identifier

Product Name COPPER ANTI-SEIZE LUBRICANT 16 OZ.

Other means of identification

Product Code 31163

Synonyms CAN Item Number 75454

Recommended use of the chemical and restrictions on use

Recommended Use Lubricant

Restrictions on use No information available

Details of the supplier of the safety data sheet

Manufacturer AddressMay Also Be Distributed by:ITW Permatex. Inc.ITW Permatex Canada

6875 Parkland Blvd. 101-2360 Bristol Circle

Solon, Ohio 44139 USA Oakville, ON Canada L6H 6M5 Telephone: 1-87-Permatex Telephone: (800) 924-6994

(866) 732-9502

E-mail address mail@permatex.com

Emergency telephone number

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

24-hour emergency phone number No information available

2. Hazard(s) identification

Classification

Carcinogenicity Category 1B

Label elements

Contains DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC; MAGNESIUM SILICATE



Danger

Hazard statements

May cause cancer.

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves, protective clothing, eye protection and face protection.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

Precautionary Statements - Storage

Store locked up.

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

27.25 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

27.25 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

84.75 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

84.75 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

82.25 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Other Information

Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Synonyms

CAN Item Number 75454.

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	30-60%	-	-
MAGNESIUM SILICATE	14807-96-6	10-30%	-	-
LIMESTONE	1317-65-3	10-30%	-	-
COPPER	7440-50-8	3-7%	-	-
GRAPHITE	7782-42-5	1-5%	-	-
AMORPHOUS SILICA	7631-86-9	1-5%	-	-

4. First-aid measures

Description of first aid measures

General advice IF exposed or concerned: Get medical advice/attention.

Inhalation Remove to fresh air.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

Consult a physician.

Skin contact Wash skin with soap and water.

Ingestion Rinse mouth.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Effects of Exposure May cause cancer.

Indication of any immediate medical attention and special treatment needed

5. Fire-fighting measures

surrounding environment.

Small Fire In case of fire, use water spray, foam, dry chemical, or CO2. Large Fire In case of fire, use water spray, foam, dry chemical, or CO2.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

No information available.

Hazardous combustion products No information available.

Explosion data

Sensitivity to mechanical impact None.
Sensitivity to static discharge None.

Special protective equipment and

precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation.

Other information Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact with

skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place.

8. Exposure controls/personal protection

Control Parameters Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
MAGNESIUM SILICATE	TWA: 2 mg/m ³ respirable	TWA: 20 mppcf if 1%	TWA: 2 mg/m³; containing no
14807-96-6	particulate matter particulate	Quartz or more, use Quartz	Asbestos and <1% Quartz
	matter containing no Asbestos		respirable dust
	and <1% Crystalline silica	(vacated) TWA: 2 mg/m ³	IDLH: 1000 mg/m ³
		respirable dust <1%	
		Crystalline silica, containing	
		no Asbestos	
		TWA: 20 mppcf if 1% Quartz	
		or more, use Quartz limit	
LIMESTONE	-	TWA: 15 mg/m ³ total dust	TWA: 10 mg/m³; total dust
1317-65-3		TWA: 5 mg/m³ respirable	TWA: 5 mg/m³; respirable
		fraction	dust
		(vacated) TWA: 15 mg/m ³	
		total dust	
		(vacated) TWA: 5 mg/m ³	
		respirable fraction	
COPPER	TWA: 0.2 mg/m ³ fume	TWA: 0.1 mg/m ³ fume	TWA: 1 mg/m³; dust and
7440-50-8		TWA: 1 mg/m³ dust and mist	mist
		(vacated) TWA: 0.1 mg/m³ Cu	
		dust, fume, mist	IDLH: 100 mg/m³ dust, fume
0.01.01.00			and mist
GRAPHITE 7700 10 5	TWA: 2 mg/m³ respirable	TWA: 15 mg/m ³ total dust	TWA: 2.5 mg/m³; natural
7782-42-5	particulate matter all forms	synthetic	respirable dust
	except graphite fibers	TWA: 5 mg/m³ respirable	IDLH: 1250 mg/m ³
		fraction synthetic	
		TWA: 15 mppcf respirable dust natural	
		(vacated) TWA: 2.5 mg/m ³	
		respirable dust natural	
		(vacated) TWA: 10 mg/m ³	
		total dust synthetic	
		(vacated) TWA: 5 mg/m ³	
		respirable fraction synthetic	
		TWA: 15 mppcf natural	
AMORPHOUS SILICA	_	(vacated) TWA: 6 mg/m ³	TWA: 6 mg/m ³ ;
7631-86-9		<1% Crystalline silica	IDLH: 3000 mg/m ³
1		TWA: 20 mppcf	
		: (80)/(% SiO2) mg/m³ TWA	

	Chemical name	Alberta	British Columbia	Ontario	Quebec
ı	MAGNESIUM SILICATE	TWA: 2 mg/m ³ ;	TWA: 2 mg/m ³ ;	TWA: 2 mg/m ³ ;	TWAEV: 2 mg/m ³ ;
	14807-96-6	respirable particulate	respirable particulate	respirable fraction	respirable dust
	LIMESTONE	TWA: 10 mg/m ³ ;	TWA: 10 mg/m ³ ; total	-	TWAEV: 10 mg/m3; total

1317-65-3		dust		dust
		TWA: 3 mg/m³;		
		respirable fraction		
		STEL: 20 mg/m ³ ;		
COPPER	TWA: 0.2 mg/m ³ ; fume	TWA: 1 mg/m³; dust and	TWA: 0.2 mg/m ³ ; fume	TWAEV: 0.2 mg/m ³ ;
7440-50-8	TWA: 1 mg/m ³ ; dust and		TWA: 1 mg/m ³ ; dust and	fume
	mist	TWA: 0.2 mg/m ³ ; fume	mist	TWAEV: 1 mg/m ³ ; dust
		-		and mist
GRAPHITE	TWA: 2 mg/m ³ ;	TWA: 2 mg/m ³ ;	TWA: 2 mg/m ³ ;	TWAEV: 2 mg/m ³ ;
7782-42-5	respirable	respirable	respirable particulate	respirable dust
			matter	

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
MAGNESIUM SILICATE	TWA: 2 mg/m³; particulate matter, respirable particulate matter	TWA: 2 mg/m³;	TWA: 2 mg/m³; particulate matter, respirable particulate matter	TWA: 2 mg/m³; particulate matter, respirable particulate matter
COPPER	TWA: 0.2 mg/m ³ ; fume	TWA: 0.2 mg/m ³ ; fume	TWA: 0.2 mg/m ³ ; fume	TWA: 0.2 mg/m ³ ; fume
GRAPHITE	TWA: 2 mg/m³; respirable particulate matter	TWA: 2 mg/m³; respirable fraction	TWA: 2 mg/m³; respirable particulate matter	TWA: 2 mg/m³; respirable particulate matter

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
MAGNESIUM SILICATE	TWA: 2 mg/m ³ ;	TWA: 2 mg/m ³ ;	TWA: 2 mg/m ³ ;	TWA: 20 mppcf;
	respirable fraction	particulate matter,	respirable fraction	
		respirable particulate		
		matter		
LIMESTONE	TWA: 10 mg/m ³ ;		TWA: 10 mg/m ³ ;	TWA: 30 mppcf;
	STEL: 20 mg/m ³ ;		STEL: 20 mg/m ³ ;	TWA: 10 mg/m³;
				STEL: 20 mg/m ³ ;
COPPER	TWA: 0.2 mg/m ³ ; fume	TWA: 0.2 mg/m ³ ; fume	TWA: 0.2 mg/m ³ ; fume	TWA: 0.2 mg/m ³ ; fume
	TWA: 1 mg/m ³ ; dust and		TWA: 1 mg/m ³ ; dust and	TWA: 1 mg/m³; dust and
	mist		mist	mist
	STEL: 3 mg/m ³ ; dust		STEL: 0.6 mg/m ³ ; fume	STEL: 0.2 mg/m ³ ; fume
	and mist		STEL: 3 mg/m ³ ; dust	STEL: 2 mg/m ³ ; dust
	STEL: 0.6 mg/m ³ ; fume		and mist	and mist
GRAPHITE	TWA: 2 mg/m ³ ;	TWA: 2 mg/m ³ ;	TWA: 2 mg/m ³ ;	TWA: 20 mppcf;
	respirable fraction	respirable particulate	respirable fraction	TWA: 30 mppcf;
	STEL: 4 mg/m ³ ;	matter	STEL: 4 mg/m ³ ;	TWA: 10 mg/m ³ ;
	respirable fraction		respirable fraction	_
AMORPHOUS SILICA				TWA: 300 particle/mL;
				TWA: 20 mppcf;
				TWA: 2 mg/m³;
				respirable mass

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear suitable gloves.

Skin and body protectionWear suitable protective clothing.

Respiratory protectionUse appropriate respiratory protection.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and

immediately after handling the product.

Thermal hazards No information available.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Paste / Gel Liquid

Appearance Paste
Color Copper
Odor Petroleum

Odor threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks • Method</u>

pH No data available
Melting point / freezing point
Boiling point / boiling range
Flash point
No data available
No data available
216 °C / 420.8 °F

Evaporation rate Not applicable Butyl acetate = 1

Flammability (solid, gas) No data available

Flammability Limit in Air

Upper flammability limit:

Lower flammability limit:

Vapor pressure

No data available
No data available

Vapor density No data available Air = 1

Relative density 1.21

Water solubility Insoluble in water Solubility(ies) No data available Partition coefficient No data available Autoignition temperature No data available Decomposition temperature No data available Kinematic viscosity No data available Dynamic viscosity No data available

Particle characteristics

Particle Size No data available
Particle Size Distribution No data available

Other information

Explosive propertiesNo information availableOxidizing propertiesNo information availableSoftening pointNo information availableMolecular weightNo information available

VOC content 0

DensityNo information availableBulk densityNo information available

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Hazardous polymerization No information available.

Conditions to avoid None known based on information supplied.

Incompatible materials None known based on information supplied.

Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available.

Eye contact Specific test data for the substance or mixture is not available.

Skin contact Specific test data for the substance or mixture is not available.

Ingestion Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity .

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

 ATEmix (oral)
 18,264.60 mg/kg

 ATEmix (dermal)
 6,326.10 mg/kg

 ATEmix (inhalation-gas)
 99,999.00 ppm

 ATEmix (inhalation-vapor)
 99,999.00 mg/l

 ATEmix (inhalation-dust/mist)
 35.60 mg/l

27.25 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

27.25 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

84.75 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

84.75 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

82.25 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
DISTILLATES (PETROLEUM),	> 15 g/kg (Rat)	> 5000 mg/kg (Rabbit)	-
HYDROTREATED HEAVY			
PARAFFINIC			
64742-54-7			
COPPER	-	-	> 5.11 mg/L (Rat) 4 h
7440-50-8			-
GRAPHITE	-	-	> 2000 mg/m³ (Rat) 4 h
7782-42-5			-
AMORPHOUS SILICA	= 7900 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	> 5.01 mg/L (Rat) 4 h
7631-86-9			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationNo information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC 64742-54-7	A2 - Suspected Human Carcinogen	Group 1 - Carcinogenic to humans	Known Human Carcinogen	Present
MAGNESIUM SILICATE 14807-96-6	A4 - Not Classifiable as a Human Carcinogen	Group 2A - Probably carcinogenic to humans	-	Present
AMORPHOUS SILICA 7631-86-9	-	Group 3 - Unclassifiable as to carcinogenicity in humans	-	-

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A2 - Suspected human carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 3 - Not classifiable as to carcinogenicity in humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposureNo information available.

Aspiration hazard No information available.

12. Ecological information

Ecotoxicity

Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC 64742-54-7	-	LC50: >5000mg/L (96h, Oncorhynchus mykiss)	-	EC50: >1000mg/L (48h, Daphnia magna)
MAGNESIUM SILICATE 14807-96-6	-	LC50: >100g/L (96h, Brachydanio rerio)	-	-
COPPER 7440-50-8	EC50: 0.0426 - 0.0535mg/L (72h, Pseudokirchneriella subcapitata) EC50: 0.031 - 0.054mg/L (96h,	LC50: 0.0068 - 0.0156mg/L (96h, Pimephales promelas) LC50: <0.3mg/L (96h, Pimephales promelas) LC50: =0.2mg/L (96h,	-	EC50: =0.03mg/L (48h, Daphnia magna)

Revision Date 04	-N	Иa	r-2	025
------------------	----	----	-----	-----

		Pimephales promelas) LC50: =0.052mg/L (96h, Oncorhynchus mykiss) LC50: =1.25mg/L (96h, Lepomis macrochirus) LC50: =0.3mg/L (96h, Cyprinus carpio) LC50: =0.8mg/L (96h, Cyprinus carpio) LC50: =0.112mg/L (96h,		
		Poecilia reticulata)		
GRAPHITE 7782-42-5	-	LC50: >100mg/L (96h, Danio rerio)	-	-
AMORPHOUS SILICA 7631-86-9	EC50: =440mg/L (72h, Pseudokirchneriella subcapitata)	LC50: =5000mg/L (96h, Brachydanio rerio)	-	EC50: =7600mg/L (48h, Ceriodaphnia dubia)

Persistence and degradability No information available.

Bioaccumulation There is no data for this product.

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused

products

Dispose of in accordance with local regulations. Dispose of waste in accordance with

environmental legislation.

Contaminated packaging Do not reuse empty containers.

US EPA Waste Number Waste designations and classifications should be determined by the end user based on the

application for which the product was used.

14. Transport information

DOT Not regulated

TDG Not regulated

MEX Not regulated

<u>IATA</u> Not regulated

<u>IMDG</u> Not regulated

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Complies Complies **DSL/NDSL EINECS/ELINCS** Complies Does not comply **ENCS IECSC** Complies **KECI** Complies Complies **PICCS AICS** Complies Complies **NZIoC**

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing Chemicals Inventory

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %	
COPPER - 7440-50-8	1.0	

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
COPPER 7440-50-8	-	X	Х	-

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Cnemical name	Hazardous Substances RQs	Substances RQs	Reportable Quantity (RQ)
COPPER	5000 lb /	-	RQ 5000 lb final RQ
7440-50-8	kg (final RQ)		RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
AMORPHOUS SILICA - 7631-86-9	*Carcinogen

*The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
MAGNESIUM SILICATE	X	X	X
14807-96-6			
LIMESTONE	X	X	X
1317-65-3			
COPPER	X	X	X
7440-50-8			
AMORPHOUS SILICA	-	X	X
7631-86-9			
GRAPHITE	X	X	X
7782-42-5			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards 1 Flammability 1 Instability 0 Special hazards - HMIS Health hazards * Flammability 1 Physical hazards 0 Personal protection X Chronic Hazard Star Legend *= Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

+ Sensitizers

Key literature references and sources for data used to compile the SDS

U.S. Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

U.S. Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program

International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set United Nations World Health Organization (WHO)

Revision Date 04-Mar-2025

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.