



PART NUMBER	NUMBER OF PORTS	WIRE RANGE CLASS B,C,D	WIRE RANGE CLASS K,M,I	LENGTH
IPLG3/0-3	3	3/0 - 4 AWG	2/0 - 2 AWG	2.63
IPLG3/0-4	4	3/0 - 4 AWG	2/0 - 2 AWG	3.41
IPLG3/0-6	6	3/0 - 4 AWG	2/0 - 2 AWG	4.97

- NOTES:
- CONNECTOR MANUFACTURED FROM 6061-T6 ALUMINUM ALLOY.
 - UL LISTED PER UL486A/B SPECIFICATIONS FOR 600V.
 - RATED FOR 90°C COPPER CONDUCTOR.
 - COLD TEMPERATURE RATED TO -45°C.
 - HIGH DIELECTRIC STRENGTH INSULATION IS ABRASION, CHEMICAL AND UV RESISTANT.

CONTACT NSi FOR SALES @ 800.321.5847

		POLARIS SALES . CO . INC	
<small>PROPRIETARY AND CONFIDENTIAL</small>		<small>11625 PROSPEROUS DRIVE ODESSA, FL 33556</small>	
<small>THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF POLARIS SALES CO. INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF POLARIS SALES CO. INC. IS PROHIBITED.</small>		TITLE: INSULATED 3/0 CONNECTOR GREY FINE STRANDED	
<small>DRAWN BY</small> S.PARRY	<small>NAME</small> S.PARRY	<small>DATE</small> 4/5/2022	DWG. NO. IPLG3/0-_SERIES
MATERIAL: 6061-T6511 ALUMINUM		SCALE: 1:1	SHEET: 1 OF 1