

TORK[®]



TPX100

LOW VOLTAGE LANDSCAPE AND SWIMMING POOL/SPA LIGHT TRANSFORMERS IN RAINPROOF ENCLOSURE. REPLACE DOOR AFTER WIRING.

SUITABLE FOR DIRECT CONNECTION TO UNDERWATER LIGHTS. MAY BE USED WITH NO NICHE FIXTURES.

INPUT: 120VOLT, 60Hz. 1.0AMPS MAX (AMPERES)

OUTPUT: 12 or 13VOLTS, 100 LAMP WATTS TOTAL ALL TAPS

⚠️ "CAUTION":

NOT FOR USE WITH SELF CONTAINED PORTABLE SPAS OR HOT TUBS. DO NOT INSTALL THIS EQUIPMENT WITHIN 5 FEET (3 METERS FOR CANADIAN INSTALLATIONS) OF INSIDE WALL OF POOL/SPA. INSTALLATION SHOULD BE DONE BY QUALIFIED PERSONNEL ACCORDING TO ALL LOCAL, STATE, PROVINCIAL AND NATIONAL ELECTRICAL CODES AND SHALL BE SUBJECT TO APPROVAL BY THE LOCAL INSPECTION AUTHORITY. FOR INDOOR/OUTDOOR USE. FOR USE WITH CERTIFIED NICHELESS SUBMERSIBLE LUMINAIRES. WARNING: RISK OF FIRE, IF INSTALLATION INVOLVES WIRING THROUGH A BUILDING STRUCTURE, SPECIAL WIRING METHODS ARE NEEDED. CONSULT A QUALIFIED ELECTRICIAN.

NE CONVIENT PAS AUX SPAS PORTABLES. NE PAS INSTALLER CE DISPOSITIF À MOINS DE 5 PIEDS (OU 3 MÈTRES POUR LES INSTALLATIONS AU CANADA) DE LA PAROI INTÉRIEURE D'UNE PISCINE OU D'UN SPA. L'INSTALLATION DEVRAIT ÊTRE EFFECTUÉE PAR UN TECHNICIEN QUALIFIÉ, RESPECTER LES CODES D'ÉLECTRICITÉ LOCAUX, PROVINCIAUX ET NATIONAUX ET ÊTRE SOUMISE À L'APPROBATION DE L'ORGANISME LOCAL D'INSPECTION. POUR USAGE À L'INTÉRIEUR OU L'EXTÉRIEUR. POUR USAGE AVEC DES LUMINAIRES SUBMERSIBLES SANS NICHE HOMOLOGUÉS. AVERTISSEMENT : RISQUE D'INCENDIE. SI L'INSTALLATION NÉCESSITE LE PASSAGE DE CÂBLES À TRAVERS UNE STRUCTURE, DES MÉTHODES DE CÂBLAGE PARTICULIÈRES DOIVENT ÊTRE UTILISÉES. CONSULTEZ UN ÉLECTRICIEN QUALIFIÉ.

↑ MOUNT AT LEAST 1FT.
(0.305 M) ABOVE
GROUND, WITH ARROWS
UP

↑ IF OVERLOADED, INTERNAL PROTECTOR
WILL OPEN. AUTOMATIC RESET MAY TAKE
15 MINUTES. TO CORRECT FAULT, REMOVE
SHORT OR OVERLOAD. NO USER
SERVICEABLE PARTS INSIDE.



NSI Industries
800.321.5847
nsiindustries.com

90059-723(E)
MADE IN CHINA

NSI Industries, LLC

TORK UNIT LABEL

p/n TPX-100

90059-723(E)

4" x 4"

1C/0

06/2023