

90mm

90mm

125mm

INSTRUCTIONS
Dénudez les fils 7/8 po (22.2 mm)
Il n'est pas nécessaire d'effectuer une torsion préalable ; maintenez les fils dénudés ensemble en veillant à ce que les extrémités soient égales. Conduisez légèrement les fils toronnés
Alignez les brins ou les conducteurs effilochés
Poussez les fils dans le connecteur et vissez jusqu'à ce que deux torsions soient visibles dans les fils

SPÉCIFICATIONS
Répertoire comme un connecteur de fil de type à pression
Température nominale : 105°C (221°F) max
Tension nominale : 600V max. pour le câblage des bâtiments ; 1000V max. pour les luminaires et les panneaux
À UTILISER AVEC UN CONDUCTEUR CUIVRE À CUIVRE

INSTRUCCIONES
Desfunde los cables 7/8" (22.2 mm)
No es necesario que estén previamente trenzados, sostenga los cables desforrados juntos con las puntas al mismo nivel. Meta un poco los cables trenzados
Alinee los cables trenzados o conductores deshilachados
Introduzca los cables en el conector y enrosque hasta que se vean dos trenzas en los cables

ESPECIFICACIONES
Certificado como conector de cables tipo a presión
Temperatura nominal: 105 °C (221 °F) máx.
Voltaje nominal: 600 V máximo en el cableado del edificio; 1000 V máximo en artefactos y letreros
PARA USARSE CON CONDUCTORES DE COBRE A COBRE

⚠ **WARNING:** Cancer and reproductive harm
⚠ **ADVERTENCIA:** Cáncer y daño reproductivo
⚠ **ADVERTISSEMENT:** Cancer et troubles de l'appareil reproducteur - www.P65Warnings.ca.gov

EASY-TWIST™
WINGED WIRE CONNECTORS

**SAME GRIP
LESS TWISTS**

Blue Winged Connectors
Raccords Ailes Bleu
Conectores Azules Con Clip
De Seguridad

50
Qty./Qte./Ctd
14-6 AWG
Solid & Stranded

WWC-B-C

WWC-B-C

50
Qty./Qte./Ctd
14-6 AWG
Solid & Stranded



Blue Winged Connectors
Raccords Ailes Bleu
Conectores Azules Con Clip
De Seguridad

**SAME GRIP
LESS TWISTS**

EASY-TWIST™
WINGED WIRE CONNECTORS

WIRE COMBINATIONS

EASY TWIST WINGED SCREW-ON CONNECTORS
For UL Listed, and CSA Certified*


CIRCULAR MILS	1520	2,570	3,248	7,743	8,218	10,384	19,387	26,106	31,149	52,645	41,532	52,500
AWG WIRE COMBINATIONS	3 #22	4 #22	2 #18	3 #16	2 #14	1 #10	3 #12	4 #12	3 #10	5 #12	4 #10	2 #6
WWC-T												
WWC-T												
WWC-R												
WWC-GR												
WWC-G												
WWC-B												

*For complete listing of wire combinations and voltage ratings, scan QR code or contact Customer Service at 800-321-5847



NSI INDUSTRIES LLC
EASY-TWIST™ CARTON
WWC-B-C_ET-TOWC_Packaging_Bag
v2
Dieline - 125.90.90
125mm x 90mm x 90mm
09/2024

DO NOT PRINT CYAN
LINE-PLACEMENT ONLY



BLACK



PMS 186 C

The colors on the package are CMYK, but they should match the spot colors shown above.

WARNING

Turn off power before installing or removing connectors.

PRECAUTION/ADVERTISSEMENT

Couper l'alimentation avant d'installer ou de retirer les raccords. / Apague la alimentación antes de instalar o retirar los conectores.

TO BE SOLD ONLY WITH INSTALLATION INSTRUCTIONS

INSTRUCTIONS

Strip wires 7/8" (22.2 mm)
Pre-twisting unnecessary, hold stripped wires together with ends even. Lead stranded wires slightly
Align any frayed strands or conductors
Push wires into connector and screw on until two twists are visible in wires

SPECIFICATIONS

Listed as a pressure-type wire connector
Temperature Rating: 105°C (221°F) max
Voltage Rating: 600V max building wiring;
1000V max in luminaires and signs
FOR USE WITH COPPER TO COPPER CONDUCTOR



NSI Industries
800.321.5847
nsiindustries.com

Made in Taiwan | Fabrique en Taiwan | Hecho en Taiwan



6 62381 36160 8