

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

1 Identification

Trade name: GOLD METALLIC
Other means of identification

Product code: 0000160812
Recommended use: Paint and coatings application.
Uses advised against: Any that differs from the recommended use.
Manufacturer/Supplier: Seymour of Sycamore
 917 Crosby Avenue
 Sycamore, IL 60178 USA
 phone: 815-895-9101
 www.seymourpaint.com

Emergency telephone number: 1-800-255-3924

Seymour of Sycamore
 3041 Dougall Avenue, Suite 503
 Windsor, ONT N9E 1S3 CANADA
 phone: 800-435-4482
 www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Aerosols 1	H222-H229	Extremely flammable aerosol. Pressurized container: may burst if heated.
Skin irritation 2	H315	Causes skin irritation.
Eye irritation 2A	H319	Causes serious eye irritation.
Reproductive toxicity 2	H361	Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure) 3	H336	May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure) 2	H373	May cause damage to organs through prolonged or repeated exposure.

Additional information:

GHS Hazard pictograms



GHS02 GHS07 GHS08

Signal word

Danger

Hazard-determining components of labeling:

Toluene
 Acetone
 butyl acetate

Hazard statements

Extremely flammable aerosol. Pressurized container: may burst if heated.
 Causes skin irritation.
 Causes serious eye irritation.
 Suspected of damaging fertility or the unborn child.
 May cause drowsiness or dizziness.
 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Avoid breathing fume/mist/vapors/spray.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 Wear protective gloves.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin: Wash with plenty of water.
 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 Get medical advice/attention if you feel unwell.
 Take off contaminated clothing and wash it before reuse.
 If skin irritation occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Store in a well-ventilated place.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
 Dispose of contents/container in accordance with local/regional/national/international regulations.
 May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be harmful or fatal.

Effects of chronic overexposure:

Classification according to (d)(1)(ii) of § 1910.1200

The SDS issuer does not object to the classifications provided by importers or manufacturers of precursor products.

Hazards not otherwise classified

There are no adverse physical or health effects known that are not covered by the hazard classes of the Hazard Communications Standard.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

Trade name: GOLD METALLIC

(Contd. of page 1)

3 Composition/information on ingredients

Chemical characterization: Mixtures
Chemical Description:

This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

67-64-1	Acetone	25-50%
108-88-3	Toluene	≥20-≤25%
74-98-6	propane	15-25%
123-86-4	butyl acetate	10-15%
106-97-8	n-butane	5-10%
86376-49-0	Brass Powder (Alloy)	5-10%

4 First-aid measures

Description of first aid measures
After inhalation:

Supply fresh air; consult doctor in case of complaints.

After skin contact:

Immediately wash with water and soap and rinse thoroughly. Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects:

Dizziness

Indication of any immediate medical attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing media
Extinguishing agents:
CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards:

Can form explosive gas-air mixtures.

Protective equipment for firefighters:

A respiratory protective device may be necessary.

Additional information

Cool endangered receptacles with water spray.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.

Environmental precautions:

Do not allow product to reach sewage systems or ground water.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Fire/explosion protection:

Keep respiratory protective device available.

Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic discharges.

Conditions for safe storage:
Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that
require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

67-64-1 Acetone

PEL	Long-term value: 2400 mg/m ³ , 1000 ppm
REL	Long-term value: 590 mg/m ³ , 250 ppm
TLV	Short-term value: 1187 mg/m ³ , 500 ppm
	Long-term value: 594 mg/m ³ , 250 ppm
	A4, BEI

108-88-3 Toluene

PEL	Long-term value: 200 ppm
	Ceiling limit value: 300; 500* ppm
	*10-min peak per 8-hr shift

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

Trade name: GOLD METALLIC

(Contd. of page 2)

REL Short-term value: 560 mg/m³, 150 ppm
Long-term value: 375 mg/m³, 100 ppm

TLV Long-term value: 20 ppm
BEI, OTO, A4

74-98-6 propane

PEL Long-term value: 1800 mg/m³, 1000 ppm

REL Long-term value: 1800 mg/m³, 1000 ppm

TLV see Appendix F Minimal oxygen content (D, EX)

123-86-4 butyl acetate

PEL Long-term value: 710 mg/m³, 150 ppm

REL Short-term value: 950 mg/m³, 200 ppm
Long-term value: 710 mg/m³, 150 ppm

TLV Short-term value: 712 mg/m³, 150 ppm
Long-term value: 238 mg/m³, 50 ppm

106-97-8 n-butane

REL Long-term value: 1900 mg/m³, 800 ppm

TLV Short-term value: 2370 mg/m³, 1000 ppm
(EX)

Ingredients with biological limit values:**67-64-1 Acetone**

BEI 25 mg/L
Medium: urine
Time: end of shift
Parameter: Acetone (nonspecific)

108-88-3 Toluene

BEI 0.02 mg/L
Medium: blood
Time: prior to last shift of workweek
Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine
Medium: urine
Time: end of shift
Parameter: o-Cresol with hydrolysis (background)

Exposure controls**Hygienic protection:**

Keep away from foodstuffs and animal feed. Wash hands after use.
Immediately remove all soiled and contaminated clothing.
Wash hands after use.
Store protective clothing separately.
Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Nitrile gloves.
The glove material must be impermeable and resistant to the substance.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties**General Information:**

Physical state: Aerosol

Odor: Aromatic

Odor threshold: Not determined.

Melting point/Melting range: Undetermined.

Boiling point: -44 °C (-47.2 °F)

Flammability: Extremely flammable.

Lower Explosion Limit: 1.7 Vol %

Upper Explosion Limit: 10.9 Vol %

Flash point: -19 °C (-2.2 °F)

Decomposition temperature: Not determined.

pH-value: Not determined.

Viscosity: Not determined.

Kinematic: Not determined.

Dynamic: Not determined.

Solubility: Not determined.

Vapor pressure: 40 PSI 2750 hPa

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

Trade name: GOLD METALLIC

(Contd. of page 3)

Vapor Pressure: 40 PSI, 2750 hPa
Relative Density: Between 0.77 and 0.85 (Water equals 1.00)
Vapor density: Not determined.
Particle characteristics: Not applicable.
Appearance: Aerosol.
Ignition temperature: Product is not self-igniting.
Danger of explosion: Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120 degrees fahrenheit.
 In use, may form flammable/explosive vapour-air mixture.

Evaporation rate: Not applicable.
Partition coefficient: n-octonal/water: Not determined.

10 Stability and reactivity

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.
Possibility of hazardous reactions: No dangerous reactions known.
Conditions to avoid: No further relevant information available.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

123-86-4 butyl acetate

Oral	LD50	14,000 mg/kg (rat)
Inhalative	LC50/4 h	>21 mg/l (rat)

Skin effects: Irritant to skin and mucous membranes.
Eye effects: Irritating effect.
Sensitization: No sensitizing effects known.
Aspiration hazard
Interactive effects No interactive effects between components are known.

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

Alternative sources for toxicological information

No non-standard sources for toxicological information where used.

12 Ecological information

Toxicity
Aquatic toxicity: Harmful to aquatic organisms.
 Hazardous for water, do not empty into drains.
Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.
Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), per and polyfluoroalkyl substances (PFA's), or chlorinated solvents.

Bioaccumulative potential: No further relevant information available.
Mobility in soil: No further relevant information available.

Results of PBT and vPvB assessment
PBT: Not applicable.
vPvB: Not applicable.

Other adverse effects:
Remark: Toxic for fish

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Waste treatment methods

Recommendation: Completely empty cans should be recycled.
Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950
DOT UN1950
 UN1950
UN proper shipping name:
DOT AEROSOLS, flammable

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

Trade name: GOLD METALLIC

(Contd. of page 4)

Transport hazard class(es):
Class 2.1 Gases
Marine pollutant: Yes
 Symbol (fish and tree)

DOT
Packaging Group: --
Special precautions for user: Warning: Gases
EMS Number: F-D,S-U

15 Regulatory information

Reglamentación y legislación en materia de seguridad, salud y medio ambiente específicas para la sustancia o la mezcla

Toxic Substances Control Act

(TSCA):

All ingredients are found on the inventory list of substances.

Consumer Product Safety

Commission (CPSC):

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

Hazardous Air Pollutants

108-88-3 | Toluene

California Proposition 65 chemicals known to cause cancer:

None of the ingredients in this product are listed.

Prop 65 chemicals known to cause birth defects or reproductive harm:

108-88-3 | Toluene

CANADIAN ENVIRONMENTAL

PROTECTION ACT:

All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

EPA:

67-64-1 | Acetone

GHS label elements

Precautionary statements

The product is classified and labeled according to the Globally Harmonized System (GHS).
 Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Do not spray on an open flame or other ignition source.
 Do not pierce or burn, even after use.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Avoid breathing fume/mist/vapors/spray.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 Wear protective gloves.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If on skin: Wash with plenty of water.
 If inhaled: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Call a poison center/doctor if you feel unwell.
 Specific treatment (see on this label).
 Get medical advice/attention if you feel unwell.
 Take off contaminated clothing and wash it before reuse.
 If skin irritation occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Store in a well-ventilated place.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 122 °F (50 °C).
 Dispose of contents/container in accordance with local/regional/national/international regulations.
 A Chemical Safety Assessment has not been carried out.

Chemical safety assessment:

16 Other information

This product was manufactured in the U.S.A.

The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact:

Regulatory Affairs

Date of previous version

05/20/2025

Date of preparation

01/13/2026

Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 PNEC: Predicted No-Effect Concentration (REACH)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 EPA: Environmental Protection Agency
 IARC: International Agency for the Research of Cancer
 NIOSH: National Institute for Occupational Safety and Health

(Contd. on page 6)

Safety Data Sheet
acc. to OSHA HCS

Date of issue: 01/13/2026

Revised On 01/13/2026

Trade name: GOLD METALLIC

(Contd. of page 5)

TSCA: Toxic Substances Control Act
CPSC: Consumer Product Safety Commission
TLV: Threshold Limit Value
PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit
BEL: Biological Exposure Limit
Aerosols 1: Aerosols – Category 1
Skin irritation 2: Skin corrosion/irritation – Category 2
Eye irritation 2A: Serious eye damage/eye irritation – Category 2A
Reproductive toxicity 2: Reproductive toxicity – Category 2
Specific target organ toxicity (single exposure) 3: Specific target organ toxicity (single exposure) – Category 3
Specific target organ toxicity (repeated exposure) 2: Specific target organ toxicity (repeated exposure) – Category 2