



FLEX TINT™

Right Color | Right Quantity | Right Now



INFO SHEET

Capture® log stain

People and wood are unpredictable.

Ran out of stain? Send a guy (and a truck full of gas) two hours to get more. Homeowner changed their mind about the color? There goes two days waiting for the new color to be delivered, not to mention the hassle of returning the other. With Sashco's Flex Tint jobsite stain tinting system, the stain flexibility you require is right where you need it: onsite. The answer to last-minute color or quantity changes is on your truck or in your trailer. You can prep, sample, make the color choice, and start staining without ever leaving the jobsite. Kill downtime and increase profits with Flex Tint. It's the right color, right quantity, right now.

Why Flex Tint for Capture® Log Stain??

- **Right color, right quantity, right now:** It's like your own mobile paint store. You choose how many of each color to always have on hand with pails of neutral base. No need to leave the jobsite.
- **Easy to mix:** A caulking gun, a drill-driven paint mixer, and 5-7 minutes are all that's needed.
- **Same performance:** It's the same color, durability, and application you've come to expect from Capture Log Stain.

Apply Capture Log Stain according to directions on the pail and on the Capture info sheet. See info sheet for final mixed stain technical specs, including stain coverage rates, dry times, etc.

Download it at Sashco.com/log-home.

Mixing Instructions

Watch the how-to video here:

sashco.com/flextintmix

- 1) Remove peel & stick color label from cartridge. Apply to 5 gal. pail next to the lot #/UPC label near the pail lid.
- 2) Remove lid from 5 gal. pail of Capture Log Stain neutral base.
- 3) Cut cartridge nub with Exacto® knife or cigar cutter.
- 4) Insert cartridge into standard caulking gun. Engage plunger until just secure in the gun.
- 5) Gun out product. Empty the entire contents of the cartridge into a 5 gal. pail of Capture Log Stain neutral base. *When empty, a small amount of the tint will remain at the very top of the cartridge. This is OK! We've filled the cartridge with a little extra so final color is not affected.*
- 6) Mix thoroughly using a drill-driven, squirrel cage-type mixing blade, for 5 to 7 minutes. Tint should be evenly distributed and no solids left in the bottom of the pail. There should be no streaks or milkiness.
- 7) Mix stain periodically throughout application. Turn the drill on for a few seconds every 20-30 minutes to ensure tint remains evenly distributed and doesn't settle to the bottom.

Coverage Rate: Use one full 10.5 oz. cartridge for every 5-gallon pail of Sashco's Capture neutral base. Do not dilute the tint pack. Using less tint



800-767-5656 • sashco.com

than recommended will diminish overall stain durability and performance.

Cleanup: While still wet, clean tools and equipment with soap and water. Discard empty containers in the trash.

Storage: To avoid dislodging cartridge plunger, do not crush. Follow pail storage instructions for mixed stain. Do not dilute tint.

Limited Warranty: For a detailed description of the warranty and exclusions, please visit sashco.com

Not tested or warrantied for use with other stain brands.

VOC content: Final mixed stain in 5 gal. pails < 250 g/L

FIRST AID TREATMENT: If swallowed, call a Poison Control Center or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

CAUTION: EYE IRRITANT. Do not swallow. Do not get in eyes. Do not get on skin or clothing. KEEP OUT OF REACH OF CHILDREN. Wear safety glasses.

