



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS
which includes the amended Hazardous Products Act (HPA) and the Hazardous Products
Regulation (HPR)

Revision Date 15-Oct-2024

Version 1

1. Identification

Product identifier

Product Name THREAD SEALANT W/PTFE 4 FL.OZ.

Other means of identification

Product Code 80632
UN number or ID number UN1133
Synonyms CAN Item Number 80634

Recommended use of the chemical and restrictions on use

Recommended Use Sealant
Restrictions on use No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex, Inc.
6875 Parkland Blvd.
Solon, Ohio 44139 USA
Telephone: 1-87-Permatex
(866) 732-9502

May Also Be Distributed by:

ITW Permatex Canada
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5
Telephone: (800) 924-6994

E-mail address mail@permatex.com

Emergency telephone number

Company Phone Number 866-732-9502
24 Hour Emergency Phone Number Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

24-hour emergency phone number No information available

2. Hazard(s) identification

Classification

Flammable liquids	Category 3
Carcinogenicity	Category 1B
Specific target organ toxicity (single exposure)	Category 1

Label elements

Contains TALC; TITANIUM DIOXIDE; METHANOL; METHYL ISOBUTYL KETONE



Danger

Hazard statements

Flammable liquid and vapor.
May cause cancer.
Causes damage to organs.

Precautionary Statements - Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves, protective clothing, eye protection and face protection.
Do not breathe dust.
Wash face, hands and any exposed skin thoroughly after handling.
Do not eat, drink or smoke when using this product.
Ground and bond container and receiving equipment.
Use non-sparking tools.
Take action to prevent static discharges.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Use explosion-proof electrical, ventilating and lighting equipment.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.
IF exposed or concerned: Call a POISON CENTER or doctor.
Specific treatment (see supplemental first aid instructions on this label).

Skin

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Fire

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Precautionary Statements - Storage

Store locked up.
Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

31.47105 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.
57.58395 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.
60.68895 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).
57.58395 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).
35.91105 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Other Information

May be harmful if swallowed. Harmful to aquatic life.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Synonyms

CAN Item Number 80634.

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
TALC	14807-96-6	15-40%	-	-
ETHANOL	64-17-5	10-30%	-	-
2-PROPANOL	67-63-0	1-5%	-	-
TITANIUM DIOXIDE	13463-67-7	1-5%	-	-
METHANOL	67-56-1	0.5-1.5%	-	-
METHYL ISOBUTYL KETONE	108-10-1	0.1-1%	-	-

4. First-aid measures

Description of first aid measures

General advice	IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the doctor in attendance.
Inhalation	Remove to fresh air. IF exposed or concerned: Get medical advice/attention.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. If symptoms persist, call a physician.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If symptoms persist, call a physician.
Ingestion	Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Call a physician.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms	No information available.
Effects of Exposure	May cause cancer. Causes damage to organs.

Indication of any immediate medical attention and special treatment needed

Note to physicians	Treat symptomatically.
---------------------------	------------------------

5. Fire-fighting measures

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
Small Fire	In case of fire, use water spray, foam, dry chemical, or CO ₂ .
Large Fire	In case of fire, use water spray, foam, dry chemical, or CO ₂ .
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Hazardous combustion products	No information available.

Explosion data

Sensitivity to mechanical impact None.
Sensitivity to static discharge Yes.

Special protective equipment and precautions for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures**

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage**Precautions for safe handling**

Advice on safe handling Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up.

8. Exposure controls/personal protection**Control Parameters****Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
---------------	-----------	----------	-------

TALC 14807-96-6	TWA: 2 mg/m ³ respirable particulate matter containing no Asbestos and <1% Crystalline silica	TWA: 20 mppcf if 1% Quartz or more, use Quartz limit (vacated) TWA: 2 mg/m ³ respirable dust <1% Crystalline silica, containing no Asbestos TWA: 20 mppcf if 1% Quartz or more, use Quartz limit	TWA: 2 mg/m ³ ; containing no Asbestos and <1% Quartz respirable dust IDLH: 1000 mg/m ³
ETHANOL 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	TWA: 1000 ppm; TWA: 1900 mg/m ³ ; IDLH: 3300 ppm
2-PROPANOL 67-63-0	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	TWA: 400 ppm; TWA: 980 mg/m ³ ; STEL: 500 ppm STEL: 1225 mg/m ³ IDLH: 2000 ppm
TITANIUM DIOXIDE 13463-67-7	TWA: 0.2 mg/m ³ nanoscale respirable particulate matter TWA: 2.5 mg/m ³ finescale respirable particulate matter	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	TWA: 2.4 mg/m ³ ; CIB 63 fine TWA: 0.3 mg/m ³ ; CIB 63 ultrafine, including engineered nanoscale IDLH: 5000 mg/m ³
METHANOL 67-56-1	TWA: 200 ppm STEL: 250 ppm pSk	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ Sdv	TWA: 200 ppm; TWA: 260 mg/m ³ ; STEL: 250 ppm STEL: 325 mg/m ³ IDLH: 6000 ppm
METHYL ISOBUTYL KETONE 108-10-1	TWA: 20 ppm STEL: 75 ppm	TWA: 100 ppm TWA: 410 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 205 mg/m ³ (vacated) STEL: 75 ppm (vacated) STEL: 300 mg/m ³	TWA: 50 ppm; TWA: 205 mg/m ³ ; STEL: 75 ppm STEL: 300 mg/m ³ IDLH: 500 ppm

Chemical name	Alberta	British Columbia	Ontario	Quebec
TALC 14807-96-6	TWA: 2 mg/m ³ ; respirable particulate	TWA: 2 mg/m ³ ; respirable particulate	TWA: 2 mg/m ³ ; respirable fraction	TWAEV: 2 mg/m ³ ; respirable dust
ETHANOL 64-17-5	TWA: 1000 ppm; TWA: 1880 mg/m ³ ;	STEL: 1000 ppm;	STEL: 1000 ppm;	STEV: 1000 ppm;
2-PROPANOL 67-63-0	TWA: 200 ppm; TWA: 492 mg/m ³ ; STEL: 400 ppm; STEL: 984 mg/m ³ ;	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;	TWAEV: 200 ppm; STEV: 400 ppm;
TITANIUM DIOXIDE 13463-67-7	TWA: 10 mg/m ³ ;	TWA: 10 mg/m ³ ; total dust TWA: 3 mg/m ³ ; respirable fraction	TWA: 10 mg/m ³ ;	TWAEV: 10 mg/m ³ ; total dust
METHANOL 67-56-1	TWA: 200 ppm; TWA: 262 mg/m ³ ; STEL: 250 ppm; STEL: 328 mg/m ³ ; pSk	TWA: 200 ppm; STEL: 250 ppm; Sk	TWA: 200 ppm; STEL: 250 ppm; dSk	TWAEV: 200 ppm; TWAEV: 262 mg/m ³ ; STEV: 250 ppm; STEV: 328 mg/m ³ ; Sd
METHYL ISOBUTYL KETONE 108-10-1	TWA: 50 ppm; TWA: 205 mg/m ³ ; STEL: 75 ppm; STEL: 307 mg/m ³ ;	TWA: 20 ppm; STEL: 75 ppm;	TWA: 20 ppm; STEL: 75 ppm;	TWAEV: 20 ppm; STEV: 75 ppm;

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
---------------	----------	---------------	---------------------------	-------------

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
TALC	TWA: 2 mg/m ³ ; particulate matter, respirable particulate matter	TWA: 2 mg/m ³ ;	TWA: 2 mg/m ³ ; particulate matter, respirable particulate matter	TWA: 2 mg/m ³ ; particulate matter, respirable particulate matter
ETHANOL	STEL: 1000 ppm;	STEL: 1000 ppm;	STEL: 1000 ppm;	STEL: 1000 ppm;
2-PROPANOL	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;
TITANIUM DIOXIDE	TWA: 0.2 mg/m ³ ; nanoscale respirable particulate matter TWA: 2.5 mg/m ³ ; finescale respirable particulate matter	TWA: 10 mg/m ³ ;	TWA: 0.2 mg/m ³ ; nanoscale respirable particulate matter TWA: 2.5 mg/m ³ ; finescale respirable particulate matter	TWA: 0.2 mg/m ³ ; nanoscale respirable particulate matter TWA: 2.5 mg/m ³ ; finescale respirable particulate matter
METHANOL	TWA: 200 ppm; STEL: 250 ppm; pSk	TWA: 200 ppm; STEL: 250 ppm; pSk	TWA: 200 ppm; STEL: 250 ppm; pSk	TWA: 200 ppm; STEL: 250 ppm; pSk
METHYL ISOBUTYL KETONE	TWA: 20 ppm; STEL: 75 ppm;	TWA: 20 ppm; STEL: 75 ppm;	TWA: 20 ppm; STEL: 75 ppm;	TWA: 20 ppm; STEL: 75 ppm;

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
TALC	TWA: 2 mg/m ³ ; respirable fraction	TWA: 2 mg/m ³ ; particulate matter, respirable particulate matter	TWA: 2 mg/m ³ ; respirable fraction	TWA: 20 mppcf;
ETHANOL	TWA: 1000 ppm; STEL: 1250 ppm;	STEL: 1000 ppm;	TWA: 1000 ppm; STEL: 1250 ppm;	TWA: 1000 ppm; TWA: 1900 mg/m ³ ; STEL: 1000 ppm; STEL: 1900 mg/m ³ ;
2-PROPANOL	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;	TWA: 200 ppm; STEL: 400 ppm;	TWA: 400 ppm; TWA: 980 mg/m ³ ; STEL: 500 ppm; STEL: 1225 mg/m ³ ; Sk
TITANIUM DIOXIDE	TWA: 10 mg/m ³ ; STEL: 20 mg/m ³ ;	TWA: 0.2 mg/m ³ ; nanoscale respirable particulate matter TWA: 2.5 mg/m ³ ; finescale respirable particulate matter	TWA: 10 mg/m ³ ; STEL: 20 mg/m ³ ;	TWA: 30 mppcf; TWA: 10 mg/m ³ ; STEL: 20 mg/m ³ ;
METHANOL	TWA: 200 ppm; STEL: 250 ppm; Sk	TWA: 200 ppm; STEL: 250 ppm;	TWA: 200 ppm; STEL: 250 ppm; pSd	TWA: 200 ppm; TWA: 260 mg/m ³ ; STEL: 250 ppm; STEL: 310 mg/m ³ ; Sk
METHYL ISOBUTYL KETONE	TWA: 50 ppm; STEL: 75 ppm;	TWA: 20 ppm; STEL: 75 ppm;	TWA: 50 ppm; STEL: 75 ppm;	TWA: 100 ppm; TWA: 410 mg/m ³ ; STEL: 125 ppm; STEL: 510 mg/m ³ ; Sk

Biological occupational exposure limits

Chemical name	ACGIH
2-PROPANOL 67-63-0	40 mg/L - urine (Acetone) - end of shift at end of workweek
METHANOL 67-56-1	15 mg/L - urine (Methanol) - end of shift
METHYL ISOBUTYL KETONE	1 mg/L - urine (MIBK) - end of shift

108-10-1

Appropriate engineering controls

Engineering controls Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Tight sealing safety goggles.

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Antistatic boots. Chemical resistant apron. Wear fire/flame resistant/retardant clothing.

Respiratory protection Use appropriate respiratory protection.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

Thermal hazards No information available.

9. Physical and chemical properties**Information on basic physical and chemical properties**

Physical state Paste / Gel Liquid
Appearance White Paste
Color White
Odor Alcohol
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	82 °C / 179.6 °F	
Flash point	25 °C / 77 °F	Tag Closed Cup
Evaporation rate	< 1	Butyl acetate = 1
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability limit:	12.7%	
Lower flammability limit:	2.3%	
Vapor pressure	33 mm Hg @ 68°F	
Vapor density	>1	Air = 1
Relative density	1.06-1.10	
Water solubility	Partially soluble None known No information available	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature	No data available	
Kinematic viscosity	No data available	
Dynamic viscosity	No data available	
Particle characteristics		
Particle Size	No data available	
Particle Size Distribution	No data available	

Other information

Explosive properties No information available

Oxidizing properties	No information available
Softening point	No information available
Molecular weight	No information available
VOC Content	29%
Density	No information available
Bulk density	No information available

10. Stability and reactivity

Reactivity	No information available.
Chemical stability	Stable under normal conditions.
Possibility of hazardous reactions	None under normal processing.
Hazardous polymerization	No information available.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	None known based on information supplied.
Hazardous decomposition products	None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available.
Eye contact	Specific test data for the substance or mixture is not available.
Skin contact	Specific test data for the substance or mixture is not available.
Ingestion	Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	No information available.
-----------------	---------------------------

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	3,921.70 mg/kg
ATEmix (dermal)	174,855.20 mg/kg
ATEmix (inhalation-gas)	99,999.00 ppm
ATEmix (inhalation-vapor)	411.1857 mg/l
ATEmix (inhalation-dust/mist)	302.40 mg/l

31.47105 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
57.58395 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
60.68895 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
57.58395 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
35.91105 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
ETHANOL 64-17-5	= 7060 mg/kg (Rat)	-	= 116.9 mg/L (Rat) 4 h = 133.8 mg/L (Rat) 4 h

2-PROPANOL 67-63-0	5050 mg/kg	12800 mg/kg	> 10000 ppm (Rat) 6 h
TITANIUM DIOXIDE 13463-67-7	> 2000 mg/kg (Rat)	-	> 5.09 mg/L (Rat) 4 h
METHANOL 67-56-1	= 6200 mg/kg (Rat)	= 15840 mg/kg (Rabbit)	= 22500 ppm (Rat) 8 h
METHYL ISOBUTYL KETONE 108-10-1	= 2080 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	2000 - 4000 ppm (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. May cause cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
TALC 14807-96-6	A4 - Not Classifiable as a Human Carcinogen	Group 2A - Probably carcinogenic to humans	-	Present
ETHANOL 64-17-5	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 1 - Carcinogenic to humans	Known Human Carcinogen	Present
2-PROPANOL 67-63-0	A4 - Not Classifiable as a Human Carcinogen	-	-	-
TITANIUM DIOXIDE 13463-67-7	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 2B - Possibly carcinogenic to humans	-	Present
METHYL ISOBUTYL KETONE 108-10-1	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 2B - Possibly carcinogenic to humans	-	Present

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to humans

Group 2A - Probably carcinogenic to humans

Group 2B - Possibly carcinogenic to humans

NTP (National Toxicology Program)

Known - Known Carcinogen

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicity No information available.

STOT - single exposure Causes damage to organs.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

12. Ecological information

Ecotoxicity Harmful to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
TALC 14807-96-6	-	LC50: >100g/L (96h, Brachydanio rerio)	-	-
ETHANOL 64-17-5	-	LC50: 12.0 - 16.0mL/L (96h, Oncorhynchus mykiss) LC50: >100mg/L (96h, Pimephales promelas) LC50: 13400 - 15100mg/L (96h, Pimephales promelas)	-	LC50: 9268 - 14221mg/L (48h, Daphnia magna) EC50: =2mg/L (48h, Daphnia magna)
2-PROPANOL 67-63-0	EC50: >1000mg/L (96h, Desmodesmus subspicatus) EC50: >1000mg/L (72h, Desmodesmus subspicatus)	LC50: =9640mg/L (96h, Pimephales promelas) LC50: =11130mg/L (96h, Pimephales promelas) LC50: >1400000µg/L (96h, Lepomis macrochirus)	-	EC50: =13299mg/L (48h, Daphnia magna)
METHANOL 67-56-1	-	LC50: =28200mg/L (96h, Pimephales promelas) LC50: >100mg/L (96h, Pimephales promelas) LC50: 19500 - 20700mg/L (96h, Oncorhynchus mykiss) LC50: 18 - 20mL/L (96h, Oncorhynchus mykiss) LC50: 13500 - 17600mg/L (96h, Lepomis macrochirus)	-	-
METHYL ISOBUTYL KETONE 108-10-1	EC50: =400mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 496 - 514mg/L (96h, Pimephales promelas)	-	EC50: =170mg/L (48h, Daphnia magna)

Persistence and degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
ETHANOL 64-17-5	-0.35
2-PROPANOL 67-63-0	0.05
METHANOL 67-56-1	-0.77
METHYL ISOBUTYL KETONE 108-10-1	1.9

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
US EPA Waste Number	Waste designations and classifications should be determined by the end user based on the application for which the product was used.

14. Transport information

DOT

UN number or ID number	UN1133
Proper shipping name	Adhesives
Transport hazard class(es)	3
Packing group	III
DOT Marine Pollutant	NP
Description	UN1133, Adhesives, 3, III
Special Provisions	B1, B52, IB3, T2, TP1
Emergency Response Guide Number	128

TDG

UN number or ID number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	3
Packing group	III
Description	UN1133, Adhesives, 3, III

MEX

UN number or ID number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	3
Packing group	III
Description	UN1133, Adhesives, 3, III, Limited Quantity
Special Provisions	223

ICAO (air)

UN number or ID number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	3
Packing group	III
Description	UN1133, Adhesives, 3, III
Special Provisions	A3

IATA

UN number or ID number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	3
Packing group	III
ERG Code	3L
Special Provisions	A3
Description	UN1133, Adhesives, 3, III

IMDG

UN number or ID number	UN1133
UN proper shipping name	Adhesives
Transport hazard class(es)	3
Packing group	III
EmS-No.	F-E, S-D
Special Provisions	223, 955
Description	UN1133, Adhesives, 3, III, Limited Quantity

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA	Complies
DSL/NDSL	Complies
EINECS/ELINCS	Does not comply
ENCS	Does not comply
IECSC	Complies
KECI	Complies
PICCS	Complies
AICS	Complies
NZIoC	Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing Chemicals Inventory

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
2-PROPANOL - 67-63-0	1.0
METHANOL - 67-56-1	1.0
METHYL ISOBUTYL KETONE - 108-10-1	0.1

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
METHANOL 67-56-1	5000 lb / kg (final RQ)	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
METHYL ISOBUTYL KETONE 108-10-1	5000 lb / kg (final RQ)	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
ETHANOL - 64-17-5	*Developmental (in alcoholic beverages)
TITANIUM DIOXIDE - 13463-67-7	*Carcinogen (airborne, unbound particles of respirable size)
METHANOL - 67-56-1	Developmental
METHYL ISOBUTYL KETONE - 108-10-1	Carcinogen Developmental

*The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product ; and the finished product is not an alcoholic beverage

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
TALC 14807-96-6	X	X	X
ETHANOL 64-17-5	X	X	X
2-PROPANOL 67-63-0	X	X	X
TITANIUM DIOXIDE 13463-67-7	X	X	X
WATER 7732-18-5	-	-	X
METHANOL 67-56-1	X	X	X
POLYTETRAFLUOROETHYLENE 9002-84-0	-	-	X
METHYL ISOBUTYL KETONE 108-10-1	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards 3 Flammability 3 Instability 0 Special hazards -
HMIS Health hazards 4 * Flammability 3 Physical hazards 0 Personal protection X
 Chronic Hazard Star Legend * = Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet**Legend**

SVHC: Substances of Very High Concern for Authorization:

PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances

vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity
 ATE: Acute Toxicity Estimate
 LC50: 50% Lethal Concentration
 LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
+	Sensitizers		

Key literature references and sources for data used to compile the SDS

U.S. Agency for Toxic Substances and Disease Registry (ATSDR)
 U.S. Environmental Protection Agency ChemView Database
 European Food Safety Authority (EFSA)
 U.S. Environmental Protection Agency
 Acute Exposure Guideline Level(s) (AEGL(s))
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
 U.S. Environmental Protection Agency High Production Volume Chemicals
 Food Research Journal
 Hazardous Substance Database
 International Uniform Chemical Information Database (IUCLID)
 Japan National Institute of Technology and Evaluation (NITE)
 Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
 NIOSH (National Institute for Occupational Safety and Health)
 National Library of Medicine's ChemID Plus (NLM CIP)
 National Library of Medicine's PubMed database (NLM PUBMED)
 U.S. National Toxicology Program (NTP)
 New Zealand's Chemical Classification and Information Database (CCID)
 International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications
 International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program
 International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set
 United Nations World Health Organization (WHO)

Revision Date 15-Oct-2024

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.