



Dependable. Reliable. Professional.

527-20

SELECT WINDOW & DOOR FLASHING TAPE

SPECIALTY TAPE



- Backing:** Polyethylene
- Adhesive:** Butyl Rubber
- Liner:** White Polyethylene Film
- Specifications:** N/A
- Colors:** Black
- Available Size:** 6 in x 50 ft
(152 mm x 15.2 m)

Applications

- Flashing and sealing around window and door installations
- Sealing sidewall sheathing seams and deck-to-wall joints
- Sealing building envelope penetration areas against air and moisture infiltration
- Sealing corner board abutments

Features

Benefits

Butyl Rubber Adhesive	<ul style="list-style-type: none"> • Provides a strong and immediate bond to most building surfaces • Compatible with silicone, butyl, polyurethane, and blended sealants or caulking materials • Excellent all-weather performance
Polyethylene Backing	<ul style="list-style-type: none"> • Tough and durable • Resists direct UV exposure for up to 1 year
Low VOC Content	<ul style="list-style-type: none"> • Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®

Typical Test Values

	Standard UOM	Metric UOM	Test Method
Total Thickness	17 mils	508 µm	ASTM D-1000
Adhesion to Steel	125 oz/in	13.68 N/cm	PSTC-101
Tensile Strength	28 lb/in	49.04 N/cm	ASTM D-1000
Installation Temperature	20 to 160 °F	-7 to 71 °C	
Operating Temperature	-20 to 180 °F	-29 to 82 °C	
Recommended Storage Conditions: 60 - 80 °F at 40-60% RH			
Standard Shelf Life (at 25 °C): 36 months from date of manufacture			

The information presented herein was prepared at VYBOND GROUP, INC. (Vybond Group, Inc. 2320 Bowling Green Road, Franklin, KY 42134) by qualified technical personnel. To VYBOND'S knowledge, it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state, and local laws and regulations. The data are submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which VYBOND assumes any legal responsibility.

