Seymour of Sycamore

3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA

Printing date 01/25/2024 Revised On 01/25/2024

1 Identification

Trade name: **UNIV.SOLVENTBLEND COATING (CC)**

000C160395 Product code:

Paint and coatings application. Recommended use:

Uses advised against: Any that differs from the recommended use.

Manufacturer/Supplier: Seymour of Sycamore

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

phone: 800-435-4482 www.seymourpaint.com www.seymourpaint.com

General Information: Health & Safety Department

Emergency telephone number: 1-800-255-3924

2 Hazard identification

Classification of the substance or mixture

Flammable Aerosols - Category 1 H222-H229 Extremely flammable aerosol. Pressurized container: may

burst if heated.

Gases Under Pressure - Liquefied Gas H280 Contains gas under pressure; may explode if heated.

Causes serious eye irritation. Eye Irritation - Category 2A H319 Specific Target Organ Toxicity - Single Exposure - Category 3 H336 May cause drowsiness or dizziness.

Specific Target Organ Toxicity - Repeated Exposure - Category 2 H373 May cause damage to organs through prolonged or

repéated exposure.

Additional information:

GHS Hazard pictograms

Precautionary statements









GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard-determining components of

labeling:

Acetone **Hazard statements**

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure. If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Do not breathe dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Effects of chronic overexposure: May cause permanent brain and nervous system damage. Repeated overexposure can also

damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the

contents may be harmful or fatal.

3 Composition/Information on ingredients

Chemical characterization: Mixtures

This product is a mixture of the substances listed below with nonhazardous additions. Chemical Description:

Offerfical Description.		i Description.	This product is a mixture of the substances heled below with hormazardous additions.		
	Dangerou	us components:			
	67-64-1	Acetone		50-100% w/w *	
	74-98-6	propane		15-25% w/w *	
	106-97-8	n-butane		10-15% w/w *	
	763-69-9	Ester EEP		≥5-<10% w/w *	

^{*} Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

Supply fresh air; consult doctor in case of complaints. After inhalation:

Remove contaminated clothing. Wash exposed area with soap and water. After skin contact:

(Contd. on page 2)

Safety Data Sheet according to HPR, Schedule 1

Printing date 01/25/2024 Revised On 01/25/2024

Trade name: UNIV.SOLVENTBLEND COATING (CC)

After eye contact:

(Contd. of page 1) Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Information for doctor:

Most important symptoms and

effects:

Dizziness

Indication of any immediate medical attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures.

Special hazards:

Protective equipment for

firefighters:

A respiratory protective device may be necessary.

Rinse mouth with water. Do not induce vomiting.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Use respiratory protective device against the effects of fumes/dust/aerosol. Do not allow product to reach sewage systems or ground water.

Environmental precautions:

Methods and material for containment and cleaning up:

Absorb liquid components with liquid-binding material.

PAC-2:		
67-64-1	Acetone	3200* ppm
74-98-6	propane	17000** ppm
763-69-9	Ester EEP	18 ppm
108-65-6	PM acetate	1,000 ppm

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Fire/explosion protection:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e.

electric lights. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from

electrostatic discharges.

Conditions for safe storage:

Storage requirements:

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/ Personal protection

Components with limit values that require monitoring at the workplace:
AT A 4 A (

67-64-1 Acetone

EL STEL: 500 ppm TWA: 250 ppm

EV STEL: 750 ppm TWA: 500 ppm

74-98-6 propane

EL | Simple asphyxiant; EX

EV TWA: 1,000 ppm revoked as of 01/01/18

106-97-8 n-butane

EL STEL: 1000 ppm EX

763-69-9 Ester EEP

EV TWA: 300 mg/m³, 50 ppm

Exposure controls

Immediately remove all soiled and contaminated clothing. Hygienic protection:

Wash hands after use.

Avoid contact with the eves and skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In

cases where short and/or long term overexposure exists, a NIOSH approved respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygiene.

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

(Contd. on page 3)

Safety Data Sheet according to HPR, Schedule 1

Printing date 01/25/2024 Revised On 01/25/2024

Trade name: UNIV.SOLVENTBLEND COATING (CC)

Eye protection: Tightly sealed goggles (Contd. of page 2)

9 Physical and chemical properties

Appearance: Aerosol.
Odor: Aromatic
Odor threshold: Not determined.
pH-value: Not determined.

Melting point/Melting range

Boiling point:

Not determined.
Undetermined.
-44 °C

Flash point: -19 °C

Flammability (solid, gas): Extremely flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % 10.9 Vol % 10.9 Vol % Vapor pressure at 20 °C: 233 hPa

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapor density

Evaporation rate
Partition coefficient: n-octonal/water: Not determined.

Solubility:
Viscosity:

Not determined.
Not determined.
Not determined.
Not determined.

Water:

MIR Value: 0.69 0.74

10 Stability and reactivity

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid No further relevant information available.
Incompatible materials: No further relevant information available.
Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects:

Skin effects: No irritant effect. Eye effects: Irritating effect.

Sensitization: No sensitizing effects known.

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential:
Mobility in soil:
Other adverse effects:

No further relevant information available.
No further relevant information available.
No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be

disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation:Completely empty cans should be recycled.
Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1950 DOT/TDG UN1950

(Contd. on page 4)

(Contd. of page 3)

Safety Data Sheet according to HPR, Schedule 1

Revised On 01/25/2024 Printing date 01/25/2024

Trade name: UNIV.SOLVENTBLEND COATING (CC)

Transport hazard class(es):

DOT, ADR

Class 2.1 Gases No

Marine pollutant:

Special precautions for user: EMS Number: Warning: Gases F-D,S-U

Transport in bulk according to Annex II of MARPOL73/78 and

the IBC Code Not applicable.

ADR

Packaging Group:

15 Regulatory information

Toxic Substances Control Act

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

CANADIAN ENVIRONMENTAL

PROTECTION ACT: All hazardous ingredients for this product appear on the Canadian Domestic Substance List.

A Chemical Safety Assessment has not been carried out. Chemical safety assessment:

16 Other information

Contact:

Date of the latest revision of the

safety data sheet

Regulatory Affairs

01/25/2024