

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Revision Date 31-Oct-2025 Version 2

1. Identification

Product identifier

Product Name PX MOTOSEAL GASKET MAKER 2.7FO

Other means of identification

Product Code 29132

UN number or ID number UN1133

Synonyms CAN Item Number 38401

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Restrictions on use No information available

Details of the supplier of the safety data sheet

Manufacturer Address May Also Be Distributed by:

ITW Permatex, Inc. ITW Permatex Canada 6875 Parkland Blvd. 101-2360 Bristol Circle

Solon, Ohio 44139 USA

Telephone: 1-87-Permatex

Oakville, ON Canada L6H 6M5

Telephone: (800) 924-6994

(866) 732-9502

E-mail address mail@permatex.com

Emergency telephone number

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

24-hour emergency phone number No information available

2. Hazard(s) identification

Classification

Flammable liquids	Category 3
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Reproductive toxicity	Category 1B

Label elements

Contains XYLENE; CALCIUM CARBONATE; CHLORINATED PARAFFIN; TITANIUM DIOXIDE; 2,2-METHYLENEBIS(4-METHYL-6-TERTIARYBUTYL PHENOL)



Danger

Hazard statements

Flammable liquid and vapor.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May damage fertility or the unborn child.

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves, protective clothing, eye protection and face protection.

Avoid breathing dust, fume, gas, mist, vapors and spray.

Use only outdoors or in a well-ventilated area.

Wash face, hands and any exposed skin thoroughly after handling.

Ground and bond container and receiving equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Use explosion-proof electrical, ventilating and lighting equipment.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see supplemental first aid instructions on this label).

Eves

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice and attention.

Skin

IF ON SKIN: Wash with plenty of water and soap.

If skin irritation occurs: Get medical advice and attention.

Take off contaminated clothing and wash it before reuse.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor if you feel unwell.

Fire

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Precautionary Statements - Storage

Store locked up.

Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

Unknown acute toxicity

0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

0 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

71.75 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

71.75 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

13.97 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Other Information

May be harmful if swallowed. May be harmful in contact with skin. Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Synonyms CAN Item Number 38401.

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
XYLENE	1330-20-7	15-40%	-	-
CALCIUM CARBONATE	471-34-1	10-30%	-	-
2-Butoxyethanol	111-76-2	10-30%	-	-
CHLORINATED PARAFFIN	63449-39-8	5-10%	-	-
TITANIUM DIOXIDE	13463-67-7	1-5%	-	-
2,2-METHYLENEBIS(4-METHY	119-47-1	0.1-1%	-	-
L-6-TERTIARYBUTYL				
PHENOL)				

4. First-aid measures

Description of first aid measures

General advice IF exposed or concerned: Get medical advice/attention. Show this safety data sheet to the

doctor in attendance.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur. If symptoms

persist, call a physician. If breathing has stopped, give artificial respiration. Get medical

attention immediately.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes

and shoes. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce

vomiting. Get medical attention.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s)

involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid

contact with skin, eyes or clothing. Avoid breathing vapors or mists.

Most important symptoms and effects, both acute and delayed

Symptoms May cause redness and tearing of the eyes. Burning sensation. Coughing and/ or wheezing.

Difficulty in breathing.

Revision Date 31-Oct-2025

Effects of Exposure May cause adverse reproductive effects - such as birth defect, miscarriages, or infertility.

Suspected of causing cancer.

Indication of any immediate medical attention and special treatment needed

Note to physiciansTreat symptomatically.

5. Fire-fighting measures

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing media Do not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Explosion data

Sensitivity to mechanical impact None. Sensitivity to static discharge Yes.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Avoid breathing

vapors or mists.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor

suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat,

hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or

explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Remove contaminated clothing and shoes. Take off contaminated clothing and wash before reuse. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.

8. Exposure controls/personal protection

Control Parameters Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
XYLENE 1330-20-7	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m³	-
CALCIUM CARBONATE 471-34-1	-	-	TWA: 10 mg/m³; total dust TWA: 5 mg/m³; respirable dust
2-Butoxyethanol 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m³ dSk Sdv	TWA: 5 ppm; TWA: 24 mg/m³; IDLH: 700 ppm
TITANIUM DIOXIDE 13463-67-7	TWA: 0.2 mg/m³ nanoscale respirable particulate matter TWA: 2.5 mg/m³ finescale respirable particulate matter	TWA: 15 mg/m³ total dust (vacated) TWA: 10 mg/m³ total dust	TWA: 2.4 mg/m³; CIB 63 fine TWA: 0.3 mg/m³; CIB 63 ultrafine, including engineered nanoscale IDLH: 5000 mg/m³

Chemical name	Alberta	British Columbia	Ontario	Quebec
XYLENE	TWA: 100 ppm;	TWA: 100 ppm;	TWA: 100 ppm;	TWAEV: 100 ppm;
1330-20-7	TWA: 434 mg/m ³ ;	STEL: 150 ppm;	STEL: 150 ppm;	TWAEV: 434 mg/m ³ ;
	STEL: 150 ppm;			STEV: 150 ppm;
	STEL: 651 mg/m ³ ;			STEV: 651 mg/m ³ ;
CALCIUM CARBONATE	TWA: 10 mg/m ³ ;	-	-	TWAEV: 10 mg/m ³ ; total
471-34-1				dust
2-Butoxyethanol	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 20 ppm;	TWAEV: 20 ppm;
111-76-2	TWA: 97 mg/m ³ ;			
TITANIUM DIOXIDE	TWA: 10 mg/m ³ ;	TWA: 10 mg/m ³ ; total	TWA: 10 mg/m ³ ;	TWAEV: 10 mg/m3; total
13463-67-7		dust	-	dust
		TWA: 3 mg/m³;		
		respirable fraction		1

	Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
Γ	XYLENE	TWA: 20 ppm;	TWA: 100 ppm; STEL: 150 ppm;	TWA: 20 ppm;	TWA: 20 ppm;

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
2-Butoxyethanol	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 20 ppm;	TWA: 20 ppm;
TITANIUM DIOXIDE	TWA: 0.2 mg/m³; nanoscale respirable particulate matter TWA: 2.5 mg/m³; finescale respirable particulate matter	TWA: 10 mg/m³;	TWA: 0.2 mg/m³; nanoscale respirable particulate matter TWA: 2.5 mg/m³; finescale respirable particulate matter	TWA: 0.2 mg/m³; nanoscale respirable particulate matter TWA: 2.5 mg/m³; finescale respirable particulate matter

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
XYLENE	TWA: 100 ppm; STEL: 150 ppm;	TWA: 20 ppm;	TWA: 100 ppm; STEL: 150 ppm;	TWA: 100 ppm; TWA: 435 mg/m³; STEL: 150 ppm; STEL: 650 mg/m³; Sk
CALCIUM CARBONATE	TWA: 10 mg/m³; STEL: 20 mg/m³;		TWA: 10 mg/m³; STEL: 20 mg/m³;	TWA: 30 mppcf; TWA: 10 mg/m³; STEL: 20 mg/m³;
2-Butoxyethanol	TWA: 20 ppm; STEL: 30 ppm;	TWA: 20 ppm;	TWA: 20 ppm; STEL: 30 ppm;	TWA: 50 ppm; TWA: 240 mg/m³; STEL: 150 ppm; STEL: 720 mg/m³; Sk
CHLORINATED PARAFFIN	Designated substance		Designated Chemical Substance	
TITANIUM DIOXIDE	TWA: 10 mg/m³; STEL: 20 mg/m³;	TWA: 0.2 mg/m³; nanoscale respirable particulate matter TWA: 2.5 mg/m³; finescale respirable particulate matter	TWA: 10 mg/m³; STEL: 20 mg/m³;	TWA: 30 mppcf; TWA: 10 mg/m³; STEL: 20 mg/m³;

Biological occupational exposure limits

Chemical name	ACGIH
XYLENE	0.3 g/g creatinine - urine (total of all isomers of
1330-20-7	Methylhippuric acids) - end of shift
2-Butoxyethanol	200 mg/g creatinine - urine (Butoxyacetic acid with
111-76-2	hydrolysis) - end of shift

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Tight sealing safety goggles.

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Antistatic boots. Chemical resistant

apron. Wear fire/flame resistant/retardant clothing.

use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and

evacuation may be required.

General hygiene considerations

Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Paste / Gel Liquid **Appearance Gray Paste** Color Gray Odor Aromatic

Odor threshold No information available

Property Values Remarks • Method

No data available pН Melting point / freezing point No data available Boiling point / boiling range No data available Flash point 31 °C / 87.8 °F

Tag Closed Cup **Evaporation rate** < 1 Butyl acetate = 1

Flammability (solid, gas) No data available

Flammability Limit in Air

Upper flammability limit: 7.0% Lower flammability limit: 0.9%

Vapor pressure No data available

Vapor density >1 Air = 1

Relative density 1.189 Negligible Water solubility Solubility(ies) No data available No data available Partition coefficient No data available **Autoignition temperature Decomposition temperature** No data available Kinematic viscosity No data available No data available Dynamic viscosity

Particle characteristics

No data available **Particle Size Particle Size Distribution** No data available

Other information

Explosive properties No information available **Oxidizing properties** No information available No information available Softening point No information available Molecular weight **VOC** content 45%

Density No information available

Bulk density No information available

10. Stability and reactivity

Reactivity No information available.

Stable under normal conditions. **Chemical stability**

None under normal processing. Possibility of hazardous reactions

Conditions to avoid Heat, flames and sparks. Excessive heat.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents. Hazardous decomposition products Carbon oxides. Hydrogen chloride. Oxides of sulfur. Aldehydes.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. May cause irritation of

respiratory tract. Harmful by inhalation. (based on components).

Eye contact Specific test data for the substance or mixture is not available. Causes serious eye irritation.

(based on components). May cause redness, itching, and pain.

Skin contact Specific test data for the substance or mixture is not available. Causes skin irritation. (based

on components).

Ingestion Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Redness. May cause redness and tearing of the eyes. Coughing and/ or wheezing.

Acute toxicity Harmful by inhalation.

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

 ATEmix (oral)
 2,340.90 mg/kg

 ATEmix (dermal)
 2,061.20 mg/kg

 ATEmix (inhalation-gas)
 99,999.00 ppm

 ATEmix (inhalation-vapor)
 99,999.00 mg/l

 ATEmix (inhalation-dust/mist)
 2.9104 mg/l

Unknown acute toxicity

0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

0 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

71.75 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

71.75 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

13.97 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
XYLENE	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h
1330-20-7			
CALCIUM CARBONATE	= 6450 mg/kg (Rat)	> 2000 mg/kg (Rat)	> 3 mg/L (Rat) 4 h
471-34-1			
2-Butoxyethanol	= 470 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
111-76-2			= 486 ppm (Rat) 4 h
CHLORINATED PARAFFIN	> 11700 mg/kg (Rat)	-	-
63449-39-8			
TITANIUM DIOXIDE	> 2000 mg/kg (Rat)	-	> 5.09 mg/L (Rat) 4 h
13463-67-7			-
2,2-METHYLENEBIS(4-METHYL-6-TE	> 10000 mg/kg (Rat)	> 10000 mg/kg (Rabbit)	-
RTIARYBUTYL PHENOL)			
119-47-1			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. Suspected of causing cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
XYLENE	A4 - Not Classifiable as		-	-
1330-20-7	a Human Carcinogen	Unclassifiable as to		
		carcinogenicity in		
		humans		
2-Butoxyethanol	A3 - Confirmed Animal	Group 3 -	-	-
111-76-2	Carcinogen with	Unclassifiable as to		
	Unknown Relevance to	carcinogenicity in		
	Humans	humans		
CHLORINATED PARAFFIN	-	Group 2B - Possibly	-	Present
63449-39-8		carcinogenic to humans		
TITANIUM DIOXIDE	A3 - Confirmed Animal	Group 2B - Possibly	-	Present
13463-67-7	Carcinogen with	carcinogenic to humans		
	Unknown Relevance to			
	Humans			

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly carcinogenic to humans

Group 3 - Not classifiable as to carcinogenicity in humans

Occupational Safety and Health Administration of the US Department of Labor

X - Present

Reproductive toxicityContains a known or suspected reproductive toxin. Classification based on data available

for ingredients. May damage fertility or the unborn child.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
XYLENE	-	LC50: =13.4mg/L (96h,	-	EC50: =3.82mg/L (48h,
1330-20-7		Pimephales promelas)		water flea)
		LC50: 2.661 -		LC50: =0.6mg/L (48h,
		4.093mg/L (96h,		Gammarus lacustris)
		Oncorhynchus mykiss)		·

		_	•	,
		LC50: 13.5 - 17.3mg/L		
		(96h, Oncorhynchus		
		mykiss)		
		LC50: 13.1 - 16.5mg/L		
		(96h, Lepomis		
		macrochirus)		
		LC50: =19mg/L (96h,		
		Lepomis macrochirus)		
		LC50: 7.711 -		
		9.591mg/L (96h,		
		Lepomis macrochirus)		
		LC50: 23.53 -		
		29.97mg/L (96h,		
		Pimephales promelas)		
		LC50: =780mg/L (96h,		
		Cyprinus carpio)		
		LC50: >780mg/L (96h,		
		Cyprinus carpio)		
		LC50: 30.26 -		
		40.75mg/L (96h,		
		Poecilia reticulata)		
2-Butoxyethanol	_	LC50: =1490mg/L (96h,	_	EC50: >1000mg/L (48h,
111-76-2		Lepomis macrochirus)		Daphnia magna)
111702		LC50: =2950mg/L (96h,		Daprinia magna)
		Lepomis macrochirus)		
CHLORINATED PARAFFIN		LC50: >300mg/L (96h,		
63449-39-8	-	Lepomis macrochirus)	_	- I
03449-39-0		LC50: >0.0109mg/L		
		(96h, Oncorhynchus		
		mykiss)		
		LC50: 94.5 - 271mg/L		
		(96h, Oncorhynchus		
		mykiss)		
		LC50: >0.1mg/L (96h,		
		Lepomis macrochirus)		
		LC50: >100mg/L (96h,		
		Pimephales promelas)		

Persistence and degradability

No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
XYLENE	3.15
1330-20-7	
2-Butoxyethanol	0.81
111-76-2	
CHLORINATED PARAFFIN	6.82
63449-39-8	
2,2-METHYLENEBIS(4-METHYL-6-TERTIARYBUTYL PHENOL)	6.25
119-47-1	

Other adverse effects

No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld

containers.

US EPA Waste Number Waste designations and classifications should be determined by the end user based on the

application for which the product was used.

14. Transport information

DOT

UN number or ID number UN1133 Proper shipping name Adhesives

Transport hazard class(es) 3 Packing group Ш **DOT Marine Pollutant**

Marine pollutant XYLENE, 2-BUTOXYETHANOL, Description UN1133. Adhesives, 3, III **Special Provisions** B1, B52, IB3, T2, TP1

Emergency Response Guide 128

Number

TDG

UN number or ID number UN1133 **UN** proper shipping name Adhesives

Transport hazard class(es) 3 **Packing group** Ш

XYLENE Marine pollutant name

Description UN1133, Adhesives, 3, III

MEX

UN number or ID number UN1133 **UN proper shipping name** Adhesives Transport hazard class(es) Packing group Ш

Description UN1133, Adhesives, 3, III

Special Provisions 223

ICAO (air)

UN number or ID number UN1133 **UN** proper shipping name Adhesives Transport hazard class(es)

Packing group

Description UN1133, Adhesives, 3, III

Special Provisions АЗ

IATA

UN1133 **UN** number or ID number **UN** proper shipping name Adhesives

Transport hazard class(es) 3 **Packing group** Ш **ERG Code** 3L **Special Provisions** А3

Description UN1133, Adhesives, 3, III

IMDG

UN number or ID number UN1133 **UN proper shipping name** Adhesives

Transport hazard class(es) 3 Ш Packing group F-E, S-D EmS-No. **Special Provisions** 223, 955

Description UN1133, Adhesives, 3, III, Marine pollutant

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Complies DSL/NDSL Complies **EINECS/ELINCS** Complies **ENCS** Complies **IECSC** Complies KECI Complies Complies **PICCS** Complies **AICS** Complies **NZIoC**

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing Chemicals Inventory

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %	
XYLENE - 1330-20-7	1.0	
2-Butoxyethanol - 111-76-2	1.0	

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
XYLENE 1330-20-7	100 lb	-	-	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name Hazardous Substanc	RQs Extremely Hazardous Reportable Quantity (RQ)
----------------------------------	--

		Substances RQs	
XYLENE	100 lb /	-	RQ 100 lb final RQ
1330-20-7	kg (final RQ)		RQ 45.4 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65	
TITANIUM DIOXIDE - 13463-67-7	*Carcinogen (airborne, unbound particles of respirable size)	
BUTYL BENZYL PHTHALATE - 85-68-7	Developmental	
CARBON BLACK - 1333-86-4	*Carcinogen (airborne, unbound particles of respirable size)	

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
XYLENE 1330-20-7	X	X	X
2-Butoxyethanol 111-76-2	X	X	X
CHLORINATED PARAFFIN 63449-39-8	-	X	-
TITANIUM DIOXIDE 13463-67-7	X	X	Х
ADIPIC ACID 124-04-9	X	Х	Х
MAGNESIUM OXIDE 1309-48-4	Х	Х	Х
BUTYL BENZYL PHTHALATE 85-68-7	Х	Х	Х
CARBON BLACK 1333-86-4	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA Health hazards 2 Flammability 3 Instability 0 Special hazards - Health hazards 2 Flammability 3 Physical hazards 0 Personal protection X Chronic Hazard Star Legend *= Chronic Health Hazard*

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)
Ceiling Maximum limit value * Skin designation

+ Sensitizers

Key literature references and sources for data used to compile the SDS

U.S. Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

U.S. Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set United Nations World Health Organization (WHO)

Revision Date 31-Oct-2025

Revision NoteNo information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.