

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Revision Date 22-Jul-2025 Version 2

1. Identification

Product identifier

Product Name 98H HIGH TACK GASKET SEALANT 4 FL.OZ

Other means of identification

Product Code 80062

UN number or ID number UN1133

Synonyms CAN Item Number 58981

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Restrictions on use No information available

Details of the supplier of the safety data sheet

Manufacturer Address May Also Be Distributed by:

ITW Permatex, Inc. ITW Permatex Canada 6875 Parkland Blvd. 101-2360 Bristol Circle

Solon, Ohio 44139 USA Oakville, ON Canada L6H 6M5 Telephone: 1-87-Permatex Telephone: (800) 924-6994

(866) 732-9502

E-mail address mail@permatex.com

Emergency telephone number

24 Hour Emergency Phone Number Chem-Tel: 800-255-3924

International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

24-hour emergency phone number No information available

2. Hazard(s) identification

Classification

Flammable liquids	Category 2
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3

Specific target organ toxicity (repeated exposure)	Category 1	
Aspiration hazard	Category 1	

Label elements

Contains ACETONE; N-HEXANE; ROSIN; CARBON BLACK



Danger

Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

Causes damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Precautionary Statements - Prevention

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves, protective clothing, eye protection and face protection.

Wash face, hands and any exposed skin thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

Use only outdoors or in a well-ventilated area.

Do not breathe dust.

Do not eat, drink or smoke when using this product.

Ground and bond container and receiving equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Keep container tightly closed.

Use explosion-proof electrical, ventilating and lighting equipment.

Keep cool.

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see supplemental first aid instructions on this label).

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice and attention.

Skin

IF ON SKIN: Wash with plenty of water and soap.

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice and attention.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or doctor if you feel unwell.

Ingestion

IF SWALLOWED: Immediately call a POISON CENTER or doctor.

Do NOT induce vomiting.

Fire

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Precautionary Statements - Storage

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

9.7 % of the mixture consists of ingredient(s) of unknown acute oral toxicity.

9.7 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity.

98.6 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas).

84.1 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor).

61.6 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist).

Other Information

May be harmful if inhaled. Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Synonyms

CAN Item Number 58981.

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
ACETONE	67-64-1	15-40%	-	-
N-HEXANE	110-54-3	10-30%	-	-
ROSIN	8050-09-7	7-13%	-	-
CARBON BLACK	1333-86-4	0.5-1.5%	-	-

4. First-aid measures

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get

medical advice/attention. Immediate medical attention is required.

Inhalation Remove to fresh air. Aspiration into lungs can produce severe lung damage. If breathing

has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult,

(trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep

eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes

and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic

reactions see a physician.

Ingestion Do NOT induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious

person. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

Get immediate medical attention.

Self-protection of the first aider

Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness. May

cause redness and tearing of the eyes. Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

Effects of Exposure May cause adverse reproductive effects - such as birth defect, miscarriages, or infertility.

Causes damage to organs through prolonged or repeated exposure. Suspected of causing

cancer.

Indication of any immediate medical attention and special treatment needed

Note to physicians May cause sensitization in susceptible persons. Treat symptomatically. Because of the

danger of aspiration, emesis or gastric lavage should not be employed unless the risk is

justified by the presence of additional toxic substances.

5. Fire-fighting measures

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Large Fire CAUTION: Use of water spray when fighting fire may be inefficient.

Unsuitable extinguishing mediaDo not scatter spilled material with high pressure water streams.

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Product is or

contains a sensitizer. May cause sensitization by skin contact.

Explosion data

Sensitivity to mechanical impact None. Sensitivity to static discharge Yes.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear.

Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. See

section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the

product must be grounded. Do not touch or walk through spilled material.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up

Methods for containment Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor

suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other

non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert

absorbent material. Pick up and transfer to properly labeled containers.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. Handling and storage

Precautions for safe handling

Advice on safe handling

Use personal protection equipment. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Remove contaminated clothing and shoes.

Conditions for safe storage, including any incompatibilities

Storage Conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children. Store away from other materials.

8. Exposure controls/personal protection

Control Parameters Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
ACETONE	TWA: 250 ppm	TWA: 1000 ppm	TWA: 250 ppm;
67-64-1	STEL: 500 ppm	TWA: 2400 mg/m ³	TWA: 590 mg/m ³ ;
		(vacated) TWA: 750 ppm	IDLH: 2500 ppm
		(vacated) TWA: 1800 mg/m ³	
		(vacated) STEL: 2400 mg/m ³	
		The acetone STEL does not	
		apply to the cellulose acetate	
		fiber industry. It is in effect for	
		all other sectors.	
		(vacated) STEL: 1000 ppm	
N-HEXANE	TWA: 50 ppm	TWA: 500 ppm	TWA: 50 ppm;
110-54-3	pSk	TWA: 1800 mg/m ³	TWA: 180 mg/m³;
		(vacated) TWA: 50 ppm	IDLH: 1100 ppm
		(vacated) TWA: 180 mg/m ³	
ROSIN	TWA: 0.001 mg/m³ total resin	(vacated) TWA: 0.1 mg/m ³	TWA: 0.1 mg/m ³ ;
8050-09-7	acids inhalable particulate	Formaldehyde	Formaldehyde
	matter		
	DS		
	RS		
CARBON BLACK	TWA: 3 mg/m³ inhalable	TWA: 3.5 mg/m ³	TWA: 3.5 mg/m ³ ;

Γ	1333-86-4	particulate matter	(vacated) TWA: 3.5 mg/m ³	TWA: 0.1 mg/m ³ ; Carbon
			-	black in presence of Polycyclic
				aromatic hydrocarbons PAH
				IDLH: 1750 mg/m ³

Chemical name	Alberta	British Columbia	Ontario	Quebec
ACETONE	TWA: 500 ppm;	TWA: 250 ppm;	TWA: 250 ppm;	TWAEV: 250 ppm;
67-64-1	TWA: 1200 mg/m ³ ;	STEL: 500 ppm;	STEL: 500 ppm;	STEV: 500 ppm;
	STEL: 750 ppm;			
	STEL: 1800 mg/m ³ ;			
N-HEXANE	TWA: 50 ppm;	TWA: 20 ppm;	TWA: 50 ppm;	TWAEV: 50 ppm;
110-54-3	TWA: 176 mg/m ³ ;	Sk	dSk	TWAEV: 176 mg/m³;
	pSk			Sd
ROSIN	-	TWA: 0.001 mg/m ³ ;	: ;	TWAEV: 0.001 mg/m ³ ;
8050-09-7		inhalable		inhalable aerosol
		DS		fraction
		RS		: ;
CARBON BLACK	TWA: 3.5 mg/m ³ ;	TWA: 3 mg/m ³ ;	TWA: 3 mg/m ³ ;	TWAEV: 3 mg/m ³ ;
1333-86-4	_	inhalable	inhalable particulate	inhalable dust
			matter	

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
ACETONE	TWA: 250 ppm;	TWA: 250 ppm;	TWA: 250 ppm;	TWA: 250 ppm;
//OLIGINE	STEL: 500 ppm;	STEL: 500 ppm;	STEL: 500 ppm;	STEL: 500 ppm;
N-HEXANE	TWA: 50 ppm;	TWA: 50 ppm;	TWA: 50 ppm;	TWA: 50 ppm;
	pSk	pSk	pSk	pSk
ROSIN	TWA: 0.001 mg/m ³ ;		TWA: 0.001 mg/m ³ ;	TWA: 0.001 mg/m ³ ;
	inhalable particulate		inhalable particulate	inhalable particulate
	matter		matter	matter
	DS		DS	DS
	RS		RS	RS
CARBON BLACK	TWA: 3 mg/m ³ ;	TWA: 3 mg/m ³ ;	TWA: 3 mg/m ³ ;	TWA: 3 mg/m ³ ;
	inhalable particulate	inhalable fraction	inhalable particulate	inhalable particulate
	matter		matter	matter

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
ACETONE	TWA: 500 ppm; STEL: 750 ppm;	TWA: 250 ppm; STEL: 500 ppm;	TWA: 500 ppm; STEL: 750 ppm;	TWA: 1000 ppm; TWA: 2400 mg/m³; STEL: 1250 ppm; STEL: 3000 mg/m³;
N-HEXANE	TWA: 50 ppm; STEL: 62.5 ppm; Sk	TWA: 50 ppm;	TWA: 50 ppm; STEL: 62.5 ppm; pSd	TWA: 100 ppm; TWA: 360 mg/m³; STEL: 125 ppm; STEL: 450 mg/m³;
ROSIN		TWA: 0.001 mg/m³; inhalable particulate matter		
CARBON BLACK	TWA: 3.5 mg/m³; STEL: 7 mg/m³;	TWA: 3 mg/m³; inhalable particulate matter	TWA: 3.5 mg/m³; STEL: 7 mg/m³;	TWA: 3.5 mg/m³; STEL: 7 mg/m³;

Biological occupational exposure limits

Chemical name	ACGIH
ACETONE	25 mg/L - urine (Acetone) - end of shift
67-64-1	
N-HEXANE	0.5 mg/L - urine (2,5-Hexanedione without hydrolysis) -

110-54-3 end of shift

Appropriate engineering controls

Engineering controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Tight sealing safety goggles.

Hand protection Wear suitable gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Antistatic boots. Chemical resistant

apron. Wear fire/flame resistant/retardant clothing.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required. Use

appropriate respiratory protection.

General hygiene considerations Do not eat, drink or smoke when using this product. Contaminated work clothing should not

be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Wear suitable gloves and eye/face protection. Avoid contact with skin, eyes or clothing.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid

Appearance No information available

Color Red

OdorNo information availableOdor thresholdNo information available

Property Values Remarks • Method

pHNo data availableMelting point / freezing pointNo data availableBoiling point / boiling range57 °C / 134.6 °FFlash point-18 °C / -0.4 °F

Evaporation rate > 1 Ether = 1

Flammability (solid, gas) No data available

Flammability Limit in Air

Upper flammability limit: 13.0%
Lower flammability limit: 2.0%
Vapor pressure 400 mm Hg

Vapor density 2.5 Air = 1

Relative density 0.86 - 0.89 Water solubility Partially soluble Solubility(ies) No data available Partition coefficient No data available **Autoignition temperature** No data available **Decomposition temperature** No data available No data available Kinematic viscosity No data available Dynamic viscosity

Particle characteristics

Particle SizeNo data availableParticle Size DistributionNo data available

Other information

Explosive properties
Oxidizing properties
No information available
VOC content
14.5%

Density No information available Bulk density No information available

10. Stability and reactivity

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions None under normal processing.

Conditions to avoid Heat, flames and sparks.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available. Aspiration into lungs can

produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal. May cause irritation of respiratory tract. May cause drowsiness or dizziness. May be

harmful if inhaled.

Eye contact Specific test data for the substance or mixture is not available. May cause irritation. Causes

serious eye irritation. (based on components). May cause redness, itching, and pain.

Skin contact May cause sensitization by skin contact. Specific test data for the substance or mixture is

not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). Repeated exposure may cause skin dryness

or cracking. Causes skin irritation.

Ingestion Specific test data for the substance or mixture is not available. Potential for aspiration if

swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. Difficulty in breathing. Coughing and/ or wheezing. Dizziness.

Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and

vomiting.

Acute toxicity .

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral) 7,321.00 mg/kg

 ATEmix (dermal)
 6,968.60 mg/kg

 ATEmix (inhalation-gas)
 99,999.00 ppm

 ATEmix (inhalation-vapor)
 185.50 mg/l

 ATEmix (inhalation-dust/mist)
 104.00 mg/l

9.7 % of the mixture consists of ingredient(s) of unknown acute oral toxicity

9.7 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity

98.6 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)

84.1 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)

61.6 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
ACETONE	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m ³ (Rat) 8 h
67-64-1			
N-HEXANE = 25 g/kg (Rat)		= 3000 mg/kg (Rabbit)	= 48000 ppm (Rat) 4 h
110-54-3			
ROSIN	= 7600 mg/kg (Rat) = 3000	> 2500 mg/kg (Rabbit)	= 1.5 mg/L (Rat) 4 h
8050-09-7	mg/kg (Rat)		
CARBON BLACK	> 10000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 4.6 mg/m³ (Rat) 4 h
1333-86-4			

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Respiratory or skin sensitization May cause an allergic skin reaction.

Germ cell mutagenicity No information available.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for

ingredients. Suspected of causing cancer.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

	Chemical name	ACGIH	IARC	NTP	OSHA
Ī	ACETONE	A4 - Not Classifiable as	-	-	-
	67-64-1	a Human Carcinogen			
Ī	CARBON BLACK	A3 - Confirmed Animal	Group 2B - Possibly	-	Present
	1333-86-4	Carcinogen with	carcinogenic to humans		
		Unknown Relevance to	-		
1		Humans			

Reproductive toxicity Contains a known or suspected reproductive toxin. Classification based on data available

for ingredients. Suspected of damaging fertility or the unborn child.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposureCauses damage to organs through prolonged or repeated exposure.

Aspiration hazard May be fatal if swallowed and enters airways.

12. Ecological information

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
			microorganisms	
ACETONE	-	LC50: 4.74 - 6.33mL/L	-	EC50: 10294 -
67-64-1		(96h, Oncorhynchus		17704mg/L (48h,
		mykiss)		Daphnia magna)
		LC50: 6210 - 8120mg/L		EC50: 12600 -
		(96h, Pimephales		12700mg/L (48h,
		promelas)		Daphnia magna)
		LC50: =8300mg/L (96h,		
		Lepomis macrochirus)		
N-HEXANE	-	LC50: 2.1 - 2.98mg/L	-	-
110-54-3		(96h, Pimephales		
		promelas)		
ROSIN	EC50: =400mg/L (72h,	-	-	EC50: 3.8 - 5.4mg/L
8050-09-7	Desmodesmus			(48h, Daphnia magna)
	subspicatus)]

Persistence and degradability

No information available.

Bioaccumulation

Component Information

our portion and a state of the		
Chemical name	Partition coefficient	
ACETONE	CETONE -0.24	
67-64-1		
N-HEXANE	4	
110-54-3		
ROSIN	7.7	
8050-09-7		

Other adverse effects

No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products

Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

US EPA Waste Number

Waste designations and classifications should be determined by the end user based on the application for which the product was used.

14. Transport information

DOT

UN number or ID number
Proper shipping name
Transport hazard class(es)
Packing group
UN1133
Adhesives
3
II

DOT Marine Pollutant

P

Marine pollutant N-HEXANE.

Description UN1133, Adhesives, 3, II, Limited Quantity

Special Provisions 149, B52, IB2, T4, TP1, TP8

Emergency Response Guide 128

Number

TDG

UN number or ID number
UN proper shipping name
Transport hazard class(es)
UN1133
Adhesives
3

Packing group

Marine pollutant name N-HEXANE

Description UN1133, Adhesives, 3, II

MEX

UN number or ID number UN1133 UN proper shipping name Adhesives Transport hazard class(es) 3

Transport hazard class(es) 3
Packing group ||

Description UN1133, Adhesives, 3, II, Limited Quantity

ICAO (air)

UN number or ID number UN1133 UN proper shipping name Adhesives Transport hazard class(es) 3

Packing group

Description UN1133, Adhesives, 3, II

Special Provisions A3

IATA

UN number or ID number UN1133 UN proper shipping name Adhesives

Transport hazard class(es)

Packing group

ERG Code

Special Provisions

3

3

A3

Description UN1133, Adhesives, 3, II, Limited Quantity

IMDG

UN number or ID number
UN proper shipping name
Transport hazard class(es)
UN1133
Adhesives
3

Packing group II F-E, S-D

Description UN1133, Adhesives, 3, II, (-18°C c.c.), Limited Quantity

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Complies DSL/NDSL Complies

EINECS/ELINCS

Not determined

Not determined

IECSC

KECI

PICCS

AICS

Not determined

Complies

Complies

Not determined

Not determined

Not determined

Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing Chemicals Inventory

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

Chemical name	SARA 313 - Threshold Values %
N-HEXANE - 110-54-3	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive

Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Environmental reopence compensatio	Traina Elability 7 tot (GET (GE) t)	10 01 11 002).	
Chemical name	Hazardous Substances RQs	Extremely Hazardous	Reportable Quantity (RQ)
		Substances RQs	
ACETONE	5000 lb /		RQ 5000 lb final RQ
67-64-1	kg (final RQ)		RQ 2270 kg final RQ
N-HEXANE	5000 lb /	-	RQ 5000 lb final RQ
110-54-3	kg (final RQ)		RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
N-HEXANE - 110-54-3	Developmental
CARBON BLACK - 1333-86-4	*Carcinogen (airborne, unbound particles of respirable size)
RHODAMINE - 81-88-9	Carcinogen

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
ACETONE	X	X	X
67-64-1			
N-HEXANE	X	X	X

110-54-3			
ROSIN	-	-	X
8050-09-7			
CARBON BLACK	X	X	X
1333-86-4			
ZINC STEARATE	X	X	X
557-05-1			
RHODAMINE	X	X	X
81-88-9			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA
HMISHealth hazards2Flammability3Instability0Special hazards-Chronic Hazard Star Legend*= Chronic Health Hazard*= Chronic Health Hazard

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend

SVHC: Substances of Very High Concern for Authorization:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances

STOT: Specific Target Organ Toxicity

ATE: Acute Toxicity Estimate LC50: 50% Lethal Concentration

LD50: 50% Lethal Dose

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

+ Sensitizers

Key literature references and sources for data used to compile the SDS

U.S. Agency for Toxic Substances and Disease Registry (ATSDR)

U.S. Environmental Protection Agency ChemView Database

European Food Safety Authority (EFSA)

U.S. Environmental Protection Agency

Acute Exposure Guideline Level(s) (AEGL(s))

U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act

U.S. Environmental Protection Agency High Production Volume Chemicals

Food Research Journal

Hazardous Substance Database

International Uniform Chemical Information Database (IUCLID)

Japan National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)

NIOSH (National Institute for Occupational Safety and Health)

National Library of Medicine's ChemID Plus (NLM CIP)

National Library of Medicine's PubMed database (NLM PUBMED)

U.S. National Toxicology Program (NTP)

New Zealand's Chemical Classification and Information Database (CCID)

International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set

United Nations World Health Organization (WHO)

Revision Date

Revision Note

No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.