

# CRIMPING TOOLS



## N12ID DIELESS HYDRAULIC CRIMPING TOOL

- Dieless indent style crimping head does not require interchangeable crimping dies
- Flip-open Crimping head rotates 350° to get into tight locations
- Two-speed pump provides rapid crimping cycle time
- Lightweight and strong fiberglass handles
- Includes carrying case



## N1240 U-DIE HYDRAULIC CRIMPING TOOL

- Accepts KC12, KA12 and KD12 crimping dies as well as industry “U” style dies
- Head design results in lower weight and improved durability - tested to 50,000 crimp cycles
- Two-speed pump to reduce cycle time
- Ram automatically retracts when crimp cycle is complete
- Crimping heads rotate 360° with 1.65” opening
- Includes carrying case



### PRODUCT SPECIFICATIONS

CATEGORY #	DESCRIPTION	CRIMPING RANGE		CRIMPING FORCE	DIMENSIONS (Length)	WEIGHT
		COPPER	ALUMINUM			
N12ID	Dieless hydraulic crimping tool	4 AWG-1000 MCM	6 AWG-1000 MCM	24,250 - 24,925 lbs	26"	15 lbs
N1240	12 Ton U-Die hydraulic crimping tool	8 AWG-750 MCM	8 AWG-750 MCM	24,000 lbs (12 Ton)	21.5"	12.2 lbs

\*UL and cUL classified with Anderson®, Blackburn®, FCI Burndy®, ILSCO®, Panduit®, Thomas & Betts®, and Penn-Union® color coded connectors. The products listed above are registered trademarks of Anderson®, Blackburn®, Burndy®, ILSCO®, Panduit®, Thomas & Betts®, and Penn-Union®.

