Printing date 01/03/2024 Revised On 01/03/2024

1 Identification of the substance and manufacturer

Trade name: **ALUMINUM (MRO) GALLONS**

Product code: 0000011411

Recommended use: Paint and coatings application.

Uses advised against: Any that differs from the recommended use.

Seymour of Sycamore Manufacturer/Supplier:

917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101

www.seymourpaint.com

1-800-255-3924 **Emergency telephone number:**

Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482

www.seymourpaint.com

2 Hazard(s) identification

Classification of the substance or mixture

Flammable Liquids 2 H225 Highly flammable liquid and vapor. Eye Irritation 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Additional information: **GHS Hazard pictograms**





Signal word

Danger

Hazard statements Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated exposure. Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Precautionary statements Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
64742-47-8	Mineral Spirits	25-50%
7429-90-5	Aluminum flake	5-10%
64742-89-8	VM&P Naphtha	5-10%
64742-95-6	Solvent naphtha, light aromatic	1-5%

4 First-aid measures

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Rinse opened eye for several minutes under running water.

Rinse out mouth and then drink plenty of water. After swallowing: Rinse mouth with water. Do not induce vomiting

Most important symptoms and

No further relevant information available. effects:

Indication of any immediate medical

attention needed: No further relevant information available.

5 Fire-fighting measures

Special hazards: No further relevant information available.

Protective equipment for firefighters: No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures: Wear protective equipment. Keep unprotected persons away.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

Printing date 01/03/2024 Revised On 01/03/2024

Trade name: ALUMINUM (MRO) GALLONS

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Storage requirements: Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.

Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

7429-90-5 Aluminum flake

PEL (USA) Long-term value: 15*; 5** mg/m³
*Total dust; ** Respirable fraction

REL (USA) Long-term value: 10* 5** mg/m³

as Al*Total dust**Respirable/pyro powd./welding f.

TLV (USA) | Long-term value: 1* mg/m³ as AI; *as respirable fraction, A4

Keep away from foodstuffs and animal feed. Wash hands after use. Hygienic protection:

Wash hands after use

Do not eat or drink while working.

Not required. Breathing equipment:

Hand protection: Nitrile gloves.

The glove material must be impermeable and resistant to the substance.

Tightly sealed goggles Eye protection:

9 Physical and chemical properties

Appearance: Liquid.

Odor threshold: Not determined. Not determined. Melting point/Melting range Undetermined. Boiling point: 85 °C (185 °F) -19 °C (-2.2 °F) Flash point: Flammability (solid, gas): Highly flammable. **Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

In use, may form flammable/explosive vapour-air mixture. Danger of explosion:

Lower Explosion Limit: 0.5 Vol % 6.5 Vol % **Upper Explosion Limit:** Vapor pressure: Not determined. Vapor density Not determined. Not determined. Evaporation rate Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Not determined. Viscosity:

10 Stability and reactivity

Conditions to avoid: No decomposition if used according to specifications.

No dangerous reactions known.

Possibility of hazardous reactions: Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

Information on toxicological effects: No data available. Skin effects: No irritant effect. Eye effects: No irritating effect.

Sensitization: No sensitizing effects known.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes

This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated Other information: solvents.

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet

Printing date 01/03/2024 Revised On 01/03/2024

Trade name: ALUMINUM (MRO) GALLONS

Bioaccumulative potential:

No further relevant information available.

Mobility in soil:

Other adverse effects:

No further relevant information available.

No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation:

Completely empty cans should be recycled.

Recommended cleansing agent:

Water, if necessary with cleansing agents.

14 Transport information

UN-Number UN1263 ADR 1263 Paint

Transport hazard class(es):

Class 3 Flammable liquids

Marine pollutant: N

Special precautions for user: Warning: Flammable liquids

EMS Number: F-E,S-E

UN "Model Regulation": UN1263, Paint, 3, II

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

7429-90-5 Aluminum flake

Toxic Substances Control Act

(TSCA): All hazardous ingredients are found on the inventory list of substances.

Canadian Domestic Substances List

(DSL): All ingredients are listed or exempted.

Consumer Product Safety

Comission (CPSC): This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

None of the ingredients in this product are listed.

Prop 65 chemicals known to cause birth defects or reproductive harm:

None of the ingredients is listed.

EPA:

None of the ingredients is listed.

16 Other information

Contact: Regulatory Affairs